ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

17 00 [2594]

Date of Preparation Oct 7, 2024

PRODUCT NUMBER

C133722

PRODUCT NAME

KRYSTAL® SL High-Solids Conversion Varnish, Dull

MANUFACTURER'S NAME

M. L. CAMPBELL

101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

C133722 = | Acute | Chronic | Fire |

Product Weight 7.84 lb/gal	•	ific Gravity 94			SH POINT °F PMCC	
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	Ν	Y	Υ	Υ	0.2	0.2
p-Chlorobenzotrifluoride 98-56-6	Ν	N	Ν	N	9	6
1-Butanol 71-36-3	N	Y	Y	N	4	5
2-Methyl-1-propanol 78-83-1	N	Y	N	N	2	2
Acetone 67-64-1	N	Y	N	N	43	51
n-Butyl Acetate 123-86-4	N	Y	N	Ν	1	1

Volatile Organic Compounds - U.S. EPA / Canada

	C133722		
	LB/Gal	g/L	
Coating Density	7.84	939	
	By wt	By vol	
Total Volatiles	62.3%	69.5%	
Federally exempt solvents			
Water	0.1%	0.0%	
Acetone	43.2%	51.4%	
P-Chlorobenzotrifluoride	8.8%	6.2%	
Organic Volatiles	10.3%	11.8%	
Percent Non-Volatile	37.7%	30.5%	
VOC Content	LB/Gal	g/L	
Total	0.80	96	
Less exempt solvents	1.90	227	
Of solids	2.63	316	
Of solids	0.27 lb/lb	0.27 kg/kg	
	By wt		
By wt LVP-VOC	10.2%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.50

Volatile Organic Compounds - California

	C133722		
	LB/Gal	g/L	
Coating Density	7.84	939	
	By wt	By vol	
Total Volatiles	62.3%	69.5%	
Exempt solvents			
Water	0.1%	0.0%	
Acetone	43.2%	51.4%	
P-Chlorobenzotrifluoride	8.8%	6.2%	
Organic Volatiles	10.3%	11.8%	
Percent Non-Volatile	37.7%	30.5%	
VOC Content	LB/Gal	g/L	
Total	0.80	96	
Less exempt solvents	1.90	227	
Of solids	2.63	316	
Of solids	0.27 lb/lb	0.27 kg/kg	
	By wt		
By wt LVP-VOC	10.2%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.45

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	C133722	
	LB/Gal	g/L
Coating Density	7.84	939
	By wt	By vol
Total Volatiles	62.3%	69.5%
Exempt solvents		
Water	0.1%	0.0%
Acetone	43.2%	51.4%
P-Chlorobenzotrifluoride	8.8%	6.2%
Organic Volatiles	10.3%	11.8%
Percent Non-Volatile	37.7%	30.5%
VOC Content	LB/Gal	g/L
Total	0.80	96
Less exempt solvents	1.90	227
Of solids	2.63	316
Of solids	0.27 lb/lb	0.27 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	C133722	
	By wt	By vol
Total Volatiles	62.3%	69.5%
VOC Content	LB/Gal	g/L
Total	4.88	585

Volatile Organic Compounds - EU Directive 2010/75/EU

	C133722	
	By wt	By vol
Total Volatiles	62.3%	69.5%
VOC Content	LB/Gal	g/L
Total	4.88	585

Volatile Organic Compounds - Mexico

	C133722		
	LB/Gal	g/L	
Coating Density	7.84	939	
	By wt	By vol	
Total Volatiles	62.3%	69.5%	
Exempt solvents			
Water	0.1%	0.0%	
Acetone	43.2%	51.4%	
Organic Volatiles	19.1%	18.0%	
Percent Non-Volatile	37.7%	30.5%	
VOC Content	LB/Gal	g/L	
Total	1.49	179	
Less exempt solvents	3.08	369	
Of solids	4.90	587	
Of solids	0.50 lb/lb	0.50 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	C133722		
	LB/Gal	kg/L	
Volatile HAPS	0.01	0.001	
Of solids	0.04	0.005	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend 7.03 lb/gal Photochemically Reactive No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.