



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Fast Reducer VOC Exempt

Code(s): VC16936

Description: Fast Reducer VOC Exempt is a high quality acetone meant for reducing low VOC solvent borne coatings. VC16936 should also be used as a general purpose clean up solvent.

Uses: VC16936 is recommended as a reducer for any low VOC ML Campbell solvent borne coating and as a general purpose clean up solvent.

Other MLC Products: Fast Reducer VOC Exempt can be used with any ML Campbell low VOC solvent borne coating.

Physical Properties (packaged)
Weight per Gallon: 6.59
Flash Point (PMCC): -4F
Packaged VOC: 0.0 g/l
Photochemically Reactive: No

Surface Preparation
New Work: Remove any dirt, grease or other contamination and sand as required.
Old Work: Strip old finishes completely and remove all contaminants from the surface. Make sure surface is dry. Finish as new work.

Mixing
Mix into coatings thoroughly.

Application Procedure
Refer to spray equipment suppliers, recommendations for fine lacquer atomizing spray guns, air caps, and fluid needles.
Note: Hot spray application is not recommended. If hot spray equipment is used, temperature settings should never be over 110°F or 43° C.

Equipment Clean Up
Use lacquer thinner to clean up all equipment.
Dispose of dirty solvent and cleaning rags in a safe and approved manner.
Solvent or lacquer-soaked rags should be stored in water-filled, closed containers prior to disposal.

Packaging/Shipping
Available Units: Gallons, Pails and Drums.

Shelf Life and Storage
36 Months

DOT Classification

UN1090

Acetone

3

PGII

(ERG#127)

Caution

- **THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*