

WOOD FINISHING SYSTEMS

# **Product Information (PI) Sheet**

**Product: Water Borne 2K Catalyst** 

Code(s): C119257

**Description:** Water Borne 2K Catalyst was developed to be used in various ML Campbell interior and exterior water borne 2K products. See base component product data sheets for recommended catalyst amounts for each product.

Physical Properties (packaged)	
Weight per Gallon:	8.97 lb/gal
Flash Point (PMCC):	168° F or 76° C
Packaged VOC:	333 g/l or 2.78 lbs/gallon
Photochemically Reactive:	No

## Mixing

Use C119257 Water Borne 2K Catalyst by weight or volume – see base component product data sheet for recommended catalyst amount. Weigh or measure catalyst then pour inot product while stirring. Stir mixture thoroughly for 3-5 minutes and never shake mixture. Do not over catalyze.

## Packaging/Shipping

Available Units: Quarts

# Shelf Life and Storage

- 12 month shelf life
- Store in a cool dry area in the original sealed containers.
- Do not store aroudn any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent materials.

Flammable Liquid

#### DOT Classification Red Label

UN 2924

# **B/L** Description

Paint UN 2924 PG II

## Caution

## • THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.

• Use only after all safety information is understood.

• Refer to the Material Safety Data Sheet (MSDS) for additional information.

#### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.



Notes	
The information, rating, and options stated here pertain to the material currently offered and represent the	
results of tests believed to be reliable. However, due to variations in customer handling and methods of	
application that are not known or under our control, M.L. Campbell cannot make any warranties as to the	
end result. Thank you for using M.L. Campbell Wood Finishing products.	

