



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: WoodSong II Furniture Glaze Base

Code(s): N22090

Description: WoodSong II Furniture Glaze Base is an oil base glaze tinting base.

Uses: Intended use is to create a look of depth and richness of color.

Table with 2 columns: Property and Value. Rows include: Weight per Gallon (7.5 ± .25 lbs.), Viscosity - Ford #4 at 77°F/25°C (10 -13 seconds), % Solids - by Weight (34.0 ± 2.5), % Solids - by Volume (24.0 ± 2.5), Flash Point (PMCC) (104°F or 40°C), VOC* (592 g/l (4.94 lb/gallon)), Photochemically Reactive (No), and a footnote about theoretical VOC.

Reduction
No reduction is needed. If open time needs to be shortened, naphtha can be used.

Application Procedure
The glaze is used to give more depth or three dimensional look. The glaze should be applied over a sealed stain or pigmented finish. The glaze may be applied by spray, brush or cloth. Before the glaze starts to get tacky (up to 1 hour) the excess should be cleaned off using a cloth or brush leaving the desired effect. After final wipe the glaze should be let to dry 30 to 45 minutes before desired top coat is applied.
Note: Glazes are decorative finishes and users are responsible for durability depending on application and look desired. Caution should be taken because adhesion of sealer and lacquer coats will be affected by amount of glaze applied. It should be noted that when using special finishes, the end use of the piece being finished should be considered. In most cases the piece being finished should not be employed in high wear areas. The creation and use of any specialty finish is decorative and users are responsible for the durability depending on the application and the desired look. Actual effect may vary due to application techniques and environmental conditions.

Tinting

Colors can be matched by mixing WoodSong II Furniture Glaze Base with the MLC IC Colorants. The glaze is supplied to allow the addition of 10 oz. colorants or 5% by weight of the dye concentrates per gallon. Colors in the M.L. Campbell Color System that require a clear base may be matched by using the M.L. Campbell Lacquer Tinting Formula Book. Nine popular glaze color formulas have been developed and are shown on the Glaze Sell Sheet.

Equipment Clean Up

- Use mineral spirits or naphtha to clean up all equipment.
- Dispose of dirty cleaning rags in a safe and approved manner.
- Glaze soaked rags should be stored in a water filled containers prior to disposal.

Packaging/Shipping

Available Units: Gallons

Shelf Life and Storage

- Store in cool, dry areas in the original sealed containers.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification

Flammable Liquid

Red Label

UN1263

B/L Description

Paint

UN1263

3

Pg II

Caution

- **THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*