

Product Information (PI) Sheet

Product: Flow Enhancer #2

Code(s) : C163

Description: Flow Enhancer #2 is a premium slow reducer/ retarder specially formulated for conditions of high heat and humidity. Flow Enhancer #2 consists of a quality blend of Glycol Ethers and Ester Solvents. This product will effectively help enhance the flow of ML Campbell products and will help reduce bubbling and blushing caused by the effects of high heat and humidity during application by keeping the top layer of film open longer. Flow Enhancer #2 will eliminate lapping.

Other Products: Can be used as a Reducer / Retarder in all M.L. Campbell solvent products.

Physical Properties (packaged)	
Weight per Gallon:	7.82 lbs. ± .2lbs
Flash Point (PMCC):	83 ° F or 28.3°C
Packaged VOC:	937 g/l (7.81 lbs/gal.)
Photochemically Reactive:	No

Application Procedure
Flow Enhancer #2 may be used in cold spray, airless spray or hot spray applications. The use of Flow Enhancer #2 will slow the drying time in proportions to the amount used. Generally, the addition of 5-10% per gallon is recommended. Maximum addition recommended is 10% per gallon. DO NOT use in water borne coatings.

Packaging/Shipping
Available Units: Gallons and Pails.

Shelf Life and Storage
<ul style="list-style-type: none"> • Store in a cool dry area in the original sealed containers. • Do not store around any source of flames or sparks. • Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification		
Flammable Liquid	Red Label	UN 1263

B/L Description			
Paint	UN 1263	3	PG II

Caution
<ul style="list-style-type: none"> • THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY. • Use only after all safety information is understood. • Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*