



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Care Catalyst Low VOC

Code(s): C143 1

Description: Care Catalyst Low VOC was specially developed to catalyze all M.L. Campbell 550 and 275 Low VOC Post-Catalyzed products. C143 1 is a more concentrated catalyst, so mixing ratios for this product should be followed carefully - see mixing section below (mixing ratios are 20:1 per gallon). Lower VOC levels can also be achieved in other M.L. Campbell Post-Catalyzed products by using C143 1 Care Catalyst Low VOC.

Physical Properties (packaged)
Weight per Gallon: 7.66 lbs. ± 0.2
Flash Point (PMCC): 52°F
Packaged VOC: 594 g/l (4.95 lbs./gallon)
Photochemically Reactive: No

Mixing
Use C143 1 Care Catalyst at 5% per gallon (20:1 ratio). Do not over catalyze.

Packaging/Shipping
Available Units: Gallons and Pails.

Shelf Life and Storage
• Store in cool, dry areas in the original sealed containers.
• Do not store around any source of flames or sparks.
• Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification
Flammable Liquid Red Label UN 1263

B/L Description
Paint UN 2924 3 PG II

## Caution

- **THESE PRODUCTS ARE DESIGNED FOR PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Safety Data Sheet (SDS) for additional information.

### Product Notes:

- **INDUSTRIAL USE ONLY.**
- This product must be mixed with other components before use.
- Before opening the packages, **READ AND FOLLOW WARNING LABELS AND DATA SHEETS ON ALL COMPONENTS.**

### Product Use:

- **WARNING:** Product is flammable and corrosive.  
**WARNING:** Caution should be used when dispensing, handling, transferring, and using this product. Follow appropriate transfer procedures to control and minimize the generation of static and flammable vapors.
- **HANDLING RECOMMENDATIONS**
  - Wear protective gloves, protective clothing and eye or face protection.
  - Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources.
  - No smoking.
  - Use explosion-proof electrical, ventilating or lighting equipment.
  - Use non-sparking tools.
  - Take action to prevent static discharges.
  - Use only outdoors or in a well-ventilated area.
  - Do not breathe vapor.
  - Wash all contaminated surfaces thoroughly after handling.
  - Thoroughly wipe down container surfaces after use using a mild alkaline solution.
  - Avoid the practice of “pouring off” or repackaging material into smaller volume plastic containers for distribution or resale.

Please refer to the Product Data Sheet and the Safety Data Sheet for additional and important safety information. If you have any questions regarding these products, please contact your M.L. Campbell® sales representative.

## Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

## Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. Thank you for using M.L. Campbell Wood Finishing products.