



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Amazing Glaze III

Code(s): MC120117

Description: Amazing Glaze III is a one component glaze tint base. Amazing Glaze III does not require vinyl and saves shop time since it is designed to be rubbed off in as little as 1 minute.

Uses: Intended to create a three dimensional look and provide depth and richness of color.

Table with 2 columns: Property and Value. Properties include Weight per Gallon, % Solids - by Weight, % Solids - by Volume, Flash Point (PMCC), Color, Sheen (60° Glossmeter), Packaged VOC, and Photochemically Reactive.

Application Procedure
Amazing Glaze III can be applied over any M.L.Campbell lacquer. Sanding between coats of all M.L. Campbell products is always recommended. Apply Amazing Glaze III by spray application only. Remove excess with a Scotch Brite gray pad or ultra fine sanding sponge to achieve desired effect. Excess glaze can be removed as quickly as 1 minute after application but should be removed before 2 – 3 hours. You must also topcoat Amazing Glaze with an M.L. Campbell clear finish.

Reduction
Reduction is not recommended.

Tinting
Colors can be achieved by mixing Amazing Glaze III with Huls 844 Colorants. The glaze is supplied to allow the addition of 5 ozs. 844 colorant or 5% by weight of the dye concentrates per gallon. Colors in the M.L. Campbell Color System that require a clear base may be matched by using the M.L. Campbell Lacquer Tinting Formula Book. Nine popular glaze color formulas have been developed and are shown on the Woodsong Glaze Color strip : use 50% of the tint formula.

Refer to spray equipment suppliers, recommendations for fine lacquer atomizing spray guns, air caps, and fluid needles.
Note: Hot spray application is not recommended. If hot spray equipment is used, temperature settings should never be over 110°F or 43° C.

Equipment Clean Up

- Use lacquer thinner to clean up all equipment.
- Dispose of dirty solvent and cleaning rags in a safe and approved manner.
- Solvent or lacquer-soaked rags should be stored in water-filled, closed containers prior to disposal.

Packaging/Shipping

Available Units: Quarts and Gallons.

Shelf Life and Storage

- Store in original sealed containers in a cool, dry area.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non – sparking tools and inert absorbent materials.

DOT Classification

Flammable Liquid,	Red Label	UN 1263		
-------------------	-----------	---------	--	--

B/L Description

Paint	UN 1263	3	PGII	
-------	---------	---	------	--

Caution

- **THESE PRODUCTS ARE DESIGNED FOR PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*