



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Proxpeel Strippable Booth Coating White

Code(s) : P839930

Description: Proxpeel White is a peelable liquid plastic spray booth and masking coating, supplied at spraying viscosity. Proxpeel offers excellent spray characteristics, dries in 10-15 minutes under normal room temperature conditions and is removable in large sheets.

Physical Properties (packaged)
Weight per Gallon: 8.00 lbs. ± .2lbs
% Solids - by Weight: 26 - 31
Theoretical Coverage at 1 mil dry: 331 sq. ft. / gallon
Flash Point (PMCC): 20 °F or -7°C
Packaged VOC: 572 g/l (5.61 lbs/gal.)

Surface Preparation
New Work: Remove any dirt, grease or other contaminants and sand as required.
Old Work: Strip old finishes completely and remove all contaminants from the surface. Make sure surface is dry. Finish as New Work.

Application Procedure
Apply with conventional spray equipment or brush.
Refer to spray equipment suppliers recommendations for fine lacquer atomizing spray guns, air caps and fluid needles. Note: Hot spray application is not recommended. If hot spray equipment is used, temperature setting should never be over 110°F or 39°C.

Equipment Cleanup
Use C18936 lacquer thinner to clean up all equipment.
Dispose of dirty solvent and cleaning rags in a safe and approved manner.
Solvent or lacquer soaked rags should be stored in water-filled closed containers prior to disposal.

Packaging/Shipping
Available Units: Pails and Drums.

Shelf Life and Storage
Store in a cool dry area in the original sealed containers.
Do not store around any source of flames or sparks.
Spills should be cleaned up with non-sparking tools and inert absorbent material.
If stored in temperatures below 30°F (-1°C) this product may gel. If so, warming to room temperature will restore it to useable condition.

DOT Classification
Flammable Liquid Red Label UN 1263

B/L Description
Paint UN 1263 3 PG II

Caution

- **THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*