



WOOD FINISHING SYSTEMS

M.L. Campbell
224 Catherine Street
Fort Erie, Ontario L2A 5M9 Canada
Tel: 1(800) 364-1359
Web: www.mlcampbell.com

Product Information (PI) Sheet

Product: Fast Lacquer Thinner

Code(s): C189 36

Description: C189 36 Fast Lacquer Thinner is an economy blend of solvents specifically designed to be used as a clean up solvent for nitrocellulose, pre-catalyzed, post catalyzed, butyrate and acrylic lacquers. If used in MLC Products C189 36 may cause flow, leveling and bubbling issues; therefore, it is recommended that C189 36 be used as a gun cleaner.

Other Products: M.L. Campbell Lacquer Thinner C160 36 is recommended for thinning most M.L. Campbell solvent based products.

Table with Physical Properties (packaged): Weight per Gallon: 6.68, Flash Point (PMCC): 21 F, Packaged VOC: 6.70 lb/ gal 803 g/l, Photochemically Reactive: Yes

Table with Reduction: If blushing occurs, use M.L. Campbell's C162 Flow Enhancer 1, or C161 1 Care Retarder.

Table with Application Procedure: Refer to spray equipment suppliers, recommendations for fine lacquer atomizing spray guns, air caps, and fluid needles. Note: Hot spray application is not recommended. If hot spray equipment is used, temperature settings should never be over 110°F or 43° C.

Table with Equipment Clean Up: Dispose of dirty solvent and cleaning rags in a safe and approved manner. Solvent or lacquer-soaked rags should be stored in water-filled, closed containers prior to disposal.

Table with Package Weight: Pails and Drums

Table with DOT Classification: Flammable Liquid, Red Label, UN 1263

Table with B/L Description: Paint, UN1263, PG II

Table with Caution: THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY. Use only after all safety information is understood. Refer to the Material Safety Data Sheet (MSDS) for additional information.

### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*