

## Product Information (PI) Sheet

**Product:** Flow Enhancer 1

**Code(s):** C162

**Description:** Flow Enhancer 1 is a premium slow reducer specially formulated for conditions of high heat and humidity. It consists of a quality blend of Glycol Ethers and Ester Solvents. This product will effectively help to enhance the flow of our products and will help to reduce bubbling and blushing caused by the effects of high heat and humidity during application. Flow Enhancer 1 will reduce dry spray and lapping.

**Other Products:** Flow Enhancer 1 can be used as a Retarder/Reducer in all M.L. Campbell solvent products.

### Physical Properties (packaged)

<b>Weight per Gallon:</b>	7.57 lbs.
<b>Flash Point (PMCC):</b>	83°F or 28.3°C
<b>VOC:</b>	907 g/l (7.57 lbs./gallon)
<b>Photochemically Reactive:</b>	No

### Application Procedure

Flow Enhancer 1 may be used in cold spray, airless spray or hot spray applications. Refer to specific products for recommended amounts. The use of Flow Enhancer 1 will slow the drying time in proportions to the amount used. **Do not use in waterborne coatings.**

### Packaging/Shipping

**Available Units:** Gallons and Pails.

### Shelf Life and Storage

- Store in cool, dry areas in the original sealed containers.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

### DOT Classification

Flammable Liquid	Red Label	UN1263
------------------	-----------	--------

### B/L Description

Paint	UN 1263	3	PG II
-------	---------	---	-------

### Caution

- **THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.**
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

### Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products.*