

SAFETY DATA SHEET

C116628

Section 1. Identification

Product name : KLEARVAR® Conversion Varnish Clear
Gloss

Product code : C116628

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : M. L. CAMPBELL
101 W. Prospect Avenue
Cleveland, OH 44115

National contact : M.L. CAMPBELL
224 Catherine Street
Fort Erie, Ontario L2A 5M9

Emergency telephone number of the company : (800) 424-9300

Product Information Telephone Number : (800) 364-1359

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 4.9% (oral), 30.5% (dermal), 26.9% (inhalation)

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 8/29/2025 **Date of previous issue** : 7/29/2025

C116628 KLEARVAR® Conversion Varnish Clear
Gloss

Version : 26.01

1/31

SHW-85-NA-GHS-CA

Section 2. Hazards identification

Hazard statements	: Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Contains Formaldehyde - a potential cancer hazard. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	Identifiers
Ethyl Acetate	16.41	141-78-6
2-Methyl-1-propanol	9.6	78-83-1
n-Butyl Acetate	8.99	123-86-4
Acetone	6.4	67-64-1
Isobutylated Urea-Formaldehyde Polymer	5.58	68002-18-6
Ethanol	5.4	64-17-5
Lt. Aliphatic Hydrocarbon Solvent	4.86	64742-89-8
Toluene	3.82	108-88-3

Date of issue/Date of revision	: 8/29/2025	Date of previous issue	: 7/29/2025	Version	: 26.01	2/31
C116628	KLEARVAR® Conversion Varnish Clear Gloss				SHW-85-NA-GHS-CA	

Section 3. Composition/information on ingredients

2-methoxy-1-methylethyl acetate	1.71	108-65-6
Xylene, mixed isomers	1.05	1330-20-7
Light Aromatic Hydrocarbons	0.99	64742-95-6
Dibutyl Phthalate	0.26	84-74-2
Ethylbenzene	0.21	100-41-4
1,3,5-Trimethylbenzene	0.14	108-67-8
1,2,4-Trimethylbenzene	0.14	95-63-6
Formaldehyde (max.)	0.09	50-00-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Date of issue/Date of revision	: 8/29/2025	Date of previous issue	: 7/29/2025	Version	: 26.01	3/31
C116628	KLEARVAR® Conversion Varnish Clear Gloss			SHW-85-NA-GHS-CA		

Section 4. First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Remark	: Flammable liquid.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Contains a formaldehyde-based resin which, under certain conditions of use, may release formaldehyde. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical
----------------------------	---

Section 7. Handling and storage

(ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Ethyl Acetate	141-78-6	ACGIH TLV (United States, 1/2024) TWA 8 hours: 400 ppm. TWA 8 hours: 1440 mg/m ³ . NIOSH REL (United States, 10/2020) TWA 10 hours: 400 ppm. TWA 10 hours: 1400 mg/m ³ . OSHA PEL (United States, 5/2018) TWA 8 hours: 400 ppm. TWA 8 hours: 1400 mg/m ³ .
2-Methyl-1-propanol	78-83-1	ACGIH TLV (United States, 1/2024) TWA 8 hours: 50 ppm. TWA 8 hours: 152 mg/m ³ . NIOSH REL (United States, 10/2020) TWA 10 hours: 50 ppm. TWA 10 hours: 150 mg/m ³ . OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 300 mg/m ³ .
n-Butyl Acetate	123-86-4	ACGIH TLV (United States, 1/2024) [Butyl acetates] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 150 ppm. TWA 10 hours: 710 mg/m ³ . STEL 15 minutes: 200 ppm. STEL 15 minutes: 950 mg/m ³ . OSHA PEL (United States, 5/2018) TWA 8 hours: 150 ppm. TWA 8 hours: 710 mg/m ³ .
Acetone	67-64-1	ACGIH TLV (United States, 1/2024) A4. TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.

Section 8. Exposure controls/personal protection

Isobutylated Urea-Formaldehyde Polymer Ethanol	68002-18-6 64-17-5	<p>NIOSH REL (United States, 10/2020) TWA 10 hours: 250 ppm. TWA 10 hours: 590 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 2400 mg/m³.</p> <p>None.</p> <p>ACGIH TLV (United States, 1/2024) A3. STEL 15 minutes: 1000 ppm.</p> <p>NIOSH REL (United States, 10/2020) TWA 10 hours: 1000 ppm. TWA 10 hours: 1900 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m³.</p>
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	<p>ACGIH TLV (United States, 1/2024) [branched hexane isomers] A3. TWA 8 hours: 200 ppm.</p> <p>ACGIH TLV (United States, 1/2024) [hexane] A3. Absorbed through skin. TWA 8 hours: 100 ppm.</p> <p>NIOSH REL (United States, 10/2020) [HEXANE ISOMERS] TWA 10 hours: 100 ppm. TWA 10 hours: 350 mg/m³. CEIL 15 minutes: 510 ppm. CEIL 15 minutes: 1800 mg/m³.</p>
Toluene	108-88-3	<p>ACGIH TLV (United States, 1/2024) A4. Ototoxicant. TWA 8 hours: 20 ppm.</p> <p>OSHA PEL Z2 (United States, 2/2013) TWA 8 hours: 200 ppm. CEIL: 300 ppm. AMP 10 minutes: 500 ppm.</p> <p>NIOSH REL (United States, 10/2020) TWA 10 hours: 100 ppm. TWA 10 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 560 mg/m³.</p>
2-methoxy-1-methylethyl acetate	108-65-6	<p>OARS WEEL (United States, 9/2024) TWA 8 hours: 50 ppm.</p>
Xylene, mixed isomers	1330-20-7	<p>ACGIH TLV (United States, 1/2024) [p-xylene and mixtures containing p-xylene] A4. Ototoxicant. TWA 8 hours: 20 ppm.</p> <p>OSHA PEL (United States, 5/2018) [Xylenes] TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.</p>
Light Aromatic Hydrocarbons Dibutyl Phthalate	64742-95-6 84-74-2	<p>None.</p> <p>ACGIH TLV (United States, 1/2024) TWA 8 hours: 5 mg/m³.</p> <p>NIOSH REL (United States, 10/2020) TWA 10 hours: 5 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 5 mg/m³.</p>
Ethylbenzene	100-41-4	<p>ACGIH TLV (United States, 1/2024) A3.</p>

Section 8. Exposure controls/personal protection

1,3,5-Trimethylbenzene	108-67-8	<p>Ototoxicant. TWA 8 hours: 20 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 100 ppm. TWA 10 hours: 435 mg/m³. STEL 15 minutes: 125 ppm. STEL 15 minutes: 545 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³. ACGIH TLV (United States, 1/2024) [trimethyl benzene, isomers] TWA 8 hours: 10 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 25 ppm. TWA 10 hours: 125 mg/m³. ACGIH TLV (United States, 1/2024) A4. TWA 8 hours: 10 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 25 ppm. TWA 10 hours: 125 mg/m³. ACGIH TLV (United States, 1/2024) A1. Skin sensitizer , Inhalation sensitizer. STEL 15 minutes: 0.3 ppm. TWA 8 hours: 0.1 ppm. OSHA PEL Z2 (United States, 2/2013) TWA 8 hours: 0.75 ppm. STEL 15 minutes: 2 ppm. NIOSH REL (United States, 10/2020) NIA. TWA 10 hours: 0.016 ppm. CEIL 15 minutes: 0.1 ppm. OSHA PEL (United States, 5/2018) TWA 8 hours: 0.75 ppm. STEL 15 minutes: 2 ppm.</p>
1,2,4-Trimethylbenzene	95-63-6	
Formaldehyde (max.)	50-00-0	

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Isobutyl alcohol	78-83-1	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 60 ppm. TWA 8 hours: 50 ppm. CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 50 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 50 ppm. CA Quebec Provincial (Canada, 2/2024) TWA_{AEV} 8 hours: 50 ppm. TWA_{AEV} 8 hours: 152 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 50 ppm. OEL 8 hours: 152 mg/m³.</p>
n-butyl acetate	123-86-4	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 200 ppm. TWA 8 hours: 150 ppm.</p>

Section 8. Exposure controls/personal protection

acetone	67-64-1	<p>CA British Columbia Provincial (Canada, 9/2024) [butyl acetate, all isomers] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) [butyl acetates, all isomers] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) [butyl acetates] STEV 15 minutes: 150 ppm. TWAEV 8 hours: 50 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 15 minutes: 200 ppm. OEL 15 minutes: 950 mg/m³. OEL 8 hours: 150 ppm. OEL 8 hours: 713 mg/m³.</p> <p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 750 ppm. TWA 8 hours: 500 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 250 ppm. STEV 15 minutes: 500 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 1200 mg/m³. OEL 15 minutes: 1800 mg/m³. OEL 8 hours: 500 ppm. OEL 15 minutes: 750 ppm.</p>
Ethyl alcohol	64-17-5	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 1250 ppm. TWA 8 hours: 1000 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) STEL 15 minutes: 1000 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) STEL 15 minutes: 1000 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) C3. STEV 15 minutes: 1000 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 1000 ppm. OEL 8 hours: 1880 mg/m³.</p>
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	<p>CA Saskatchewan Provincial (Canada, 4/2021) [Hexane] STEL 15 minutes: 1000 ppm. TWA 8 hours: 500 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) [hexane, all isomers except n-</p>

Section 8. Exposure controls/personal protection

		<p>hexane] TWA 8 hours: 200 ppm. CA British Columbia Provincial (Canada, 9/2024) [hexane] Absorbed through skin. Notes: No British Columbia exposure limit at this time CA Ontario Provincial (Canada, 6/2019) [Hexane isomers, other than n-hexane] TWA 8 hours: 500 ppm. STEL 15 minutes: 1000 ppm. CA Quebec Provincial (Canada, 2/2024) [Hexane] TWA EV 8 hours: 500 ppm. TWA EV 8 hours: 1760 mg/m³. STEL 15 minutes: 1000 ppm. STEL 15 minutes: 3500 mg/m³. CA Alberta Provincial (Canada, 3/2023) [Dimethylbutane] OEL 8 hours: 1760 mg/m³. OEL 15 minutes: 1000 ppm. OEL 15 minutes: 3500 mg/m³. OEL 8 hours: 500 ppm. CA Alberta Provincial (Canada, 3/2023) [Hexane] OEL 8 hours: 1760 mg/m³. OEL 8 hours: 500 ppm. OEL 15 minutes: 3500 mg/m³. OEL 15 minutes: 1000 ppm.</p>
toluene	108-88-3	<p>CA Saskatchewan Provincial (Canada, 4/2021) Absorbed through skin. STEL 15 minutes: 60 ppm. TWA 8 hours: 50 ppm. CA British Columbia Provincial (Canada, 9/2024) Repr. TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) Ototoxicant. TWA EV 8 hours: 20 ppm. CA Alberta Provincial (Canada, 3/2023) Absorbed through skin. OEL 8 hours: 50 ppm. OEL 8 hours: 188 mg/m³.</p>
Xylene	1330-20-7	<p>CA Saskatchewan Provincial (Canada, 4/2021) [Xylene] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA British Columbia Provincial (Canada, 9/2024) [xylene (o, m & p isomers)] TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm. CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA Quebec Provincial (Canada, 2/2024)</p>

Section 8. Exposure controls/personal protection

n-Dibutyl phthalate	84-74-2	<p>[Xylene] TWA EV 8 hours: 100 ppm. TWA EV 8 hours: 434 mg/m³. STEV 15 minutes: 150 ppm. STEV 15 minutes: 651 mg/m³. CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene] OEL 8 hours: 100 ppm. OEL 15 minutes: 651 mg/m³. OEL 15 minutes: 150 ppm. OEL 8 hours: 434 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 10 mg/m³. TWA 8 hours: 5 mg/m³. CA British Columbia Provincial (Canada, 9/2024) Repr. TWA 8 hours: 5 mg/m³. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 5 mg/m³. CA Quebec Provincial (Canada, 2/2024) TWA EV 8 hours: 5 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 5 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. CA British Columbia Provincial (Canada, 9/2024) Carc 2B. TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) C3. TWA EV 8 hours: 20 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 100 ppm. OEL 8 hours: 434 mg/m³. OEL 15 minutes: 543 mg/m³. OEL 15 minutes: 125 ppm.</p>
Ethylbenzene	100-41-4	

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Ethyl Acetate	141-78-6	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 400 ppm.
2-Methyl-1-propanol	78-83-1	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 50 ppm.
n-Butyl Acetate	123-86-4	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm.
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 500 ppm. STEL 15 minutes: 750 ppm.
Ethanol	64-17-5	NOM-010-STPS-2014 (Mexico, 4/2016) A3. STEL 15 minutes: 1000 ppm.

Section 8. Exposure controls/personal protection

Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	ACGIH TLV (United States, 1/2024) [branched hexane isomers] A3. TWA 8 hours: 200 ppm.
Toluene	108-88-3	ACGIH TLV (United States, 1/2024) [hexane] A3. Absorbed through skin. TWA 8 hours: 100 ppm.
Xylene, mixed isomers	1330-20-7	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 20 ppm.
Dibutyl Phthalate	84-74-2	NOM-010-STPS-2014 (Mexico, 4/2016) [Xileno, mezcla] A4. STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.
		NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 5 mg/m ³ .

Biological exposure indices (United States)

Ingredient name	Exposure indices
Acetone	ACGIH BEI (United States, 1/2024) BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
Toluene	ACGIH BEI (United States, 1/2024) BEI: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift. BEI: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift. BEI: 0.02 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.
Xylene, mixed isomers	ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)] BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
Ethylbenzene	ACGIH BEI (United States, 1/2024) BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Acetone	Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift.
Toluene	Official Mexican STANDARD NOM-

Section 8. Exposure controls/personal protection

Xylene, mixed isomers

047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)

BEI: 0.05 mg/L, toluene [in blood]. Sampling time: sample time not specified.

BEI: 1.6 g/g creatinine [Basal level. The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the value; non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], hippuric acid [in urine]. Sampling time: at the end of the work shift.

BEI: 0.5 mg/L [Basal level. The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the value], o-cresol [in urine]. Sampling time: at the end of the work shift.

Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) [xilenos (grado técnico o comercial)]

BEI: 1.5 g/g creatinine, methyl hippuric acids [in urine]. Sampling time: at the end of the work shift.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Date of issue/Date of revision

: 8/29/2025

Date of previous issue

: 7/29/2025

Version : 26.01

13/31

C116628

KLEARVAR® Conversion Varnish Clear
Gloss

SHW-85-NA-GHS-CA

Section 8. Exposure controls/personal protection

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

: Liquid.

Color

: Clear.

Odor

: Not available.

Odor threshold

: Not available.

pH

: Not applicable.

Melting point/freezing point

: Not available.

Boiling point or initial boiling point and boiling range

: 55°C (131°F)

Flash point

: Closed cup: 16°C (60.8°F) [Pensky-Martens Closed Cup]

Evaporation rate

: 5.6 (butyl acetate = 1)

Flammability

: Flammable liquid.

Lower and upper explosion limit/flammability limit

: Lower: 0.9%
Upper: 19%

Vapor pressure

: 24 kPa (180 mm Hg)

Relative vapor density

: 1.5 [Air = 1]

Relative density

: 0.93

Density

: 0.93 g/cm³

Solubility(ies)

:

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water

: Not applicable.

Auto-ignition temperature

: Not available.

Section 9. Physical and chemical properties

Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)
Molecular weight	: Not applicable.
Particle characteristics	
Median particle size	: Not applicable.
Heat of combustion	: 17.426 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Result

Ethyl Acetate

Rat - Oral - LD50

5620 mg/kg

2-Methyl-1-propanol

Rat - Oral - LD50

2460 mg/kg

Rabbit - Dermal - LD50

3400 mg/kg

Rat - Inhalation - LC50 Vapor

19200 mg/m³ [4 hours]

n-Butyl Acetate

Rat - Oral - LD50

10768 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes

Rabbit - Dermal - LD50

>17600 mg/kg

Acetone

Rat - Oral - LD50

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor

Isobutylated Urea-Formaldehyde Polymer

Rat - Oral - LD50

Section 11. Toxicological information

	>5 g/kg <u>Toxic effects:</u> Olfaction - Other changes Behavioral - Somnolence (general depressed activity) Behavioral - Food intake (animal) Rabbit - Dermal - LD50
Ethanol	>5 g/kg <u>Toxic effects:</u> Skin After systemic exposure - Dermatitis, other Rat - Oral - LD50
	7 g/kg Rat - Inhalation - LC50 Vapor
Toluene	124700 mg/m ³ [4 hours] Rat - Oral - LD50
	636 mg/kg Rat - Inhalation - LC50 Vapor
2-methoxy-1-methylethyl acetate	49 g/m ³ [4 hours] Rat - Oral - LD50
	8532 mg/kg Rabbit - Dermal - LD50
Xylene, mixed isomers	>5 g/kg Rat - Oral - LD50
	4300 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes Rat - Inhalation - LC50 Gas.
	6700 ppm [4 hours] <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)
Light Aromatic Hydrocarbons	Rat - Oral - LD50
	8400 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other changes
Dibutyl Phthalate	Rat - Oral - LD50
	5010 mg/kg
Ethylbenzene	Rat - Oral - LD50
	3500 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes
	Rabbit - Dermal - LD50
1,3,5-Trimethylbenzene	>5000 mg/kg Rat - Oral - LD50
	5000 mg/kg Rat - Inhalation - LC50 Vapor
1,2,4-Trimethylbenzene	24000 mg/m ³ [4 hours] Rat - Oral - LD50
	5 g/kg Rat - Inhalation - LC50 Vapor
Formaldehyde (max.)	18000 mg/m ³ [4 hours] Rat - Oral - LD50
	100 mg/kg Rabbit - Dermal - LD50
	270 mg/kg Rat - Inhalation - LC50 Gas.
	250 ppm [4 hours]

Conclusion/Summary [Product] : Not available.

Section 11. Toxicological information

Skin corrosion/irritation

Product/ingredient name

Result

n-Butyl Acetate

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Acetone

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Ethanol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 395 mg

Rabbit - Skin - Mild irritant

Amount/concentration applied: 400 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Toluene

Pig - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 250 uL

Rabbit - Skin - Mild irritant

Amount/concentration applied: 435 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 500 mg

Xylene, mixed isomers

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

Ethylbenzene

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

1,3,5-Trimethylbenzene

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Formaldehyde (max.)

Human - Skin - Mild irritant

Duration of treatment/exposure: 72 hours

Amount/concentration applied: 150 ug l

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Rabbit - Skin - Mild irritant

Amount/concentration applied: 540 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 50 mg

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 2 mg

Rabbit - Skin - Severe irritant

Amount/concentration applied: 0.8 %

Mouse - Skin - Moderate irritant

Amount/concentration applied: 7 %

Section 11. Toxicological information

Rat - Skin - Moderate irritant

Amount/concentration applied: 7 %

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Result

n-Butyl Acetate

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Acetone

Human - Eyes - Mild irritant

Amount/concentration applied: 186300 ppm

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 10 uL

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg

Isobutylated Urea-Formaldehyde Polymer

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Ethanol

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 0.066666667 minutes

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 1 hours

Amount/concentration applied: 50 pph

Toluene

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 0.5 minutes

Amount/concentration applied: 100 mg

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 870 ug

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 2 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 0.1 MI

Xylene, mixed isomers

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Light Aromatic Hydrocarbons

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Ethylbenzene

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

1,3,5-Trimethylbenzene

Rabbit - Eyes - Mild irritant

Section 11. Toxicological information

Formaldehyde (max.)

Duration of treatment/exposure: 24 hours
Amount/concentration applied: 500 mg
Human - Eyes - Mild irritant
Duration of treatment/exposure: 6 minutes
Amount/concentration applied: 1 ppm
Rabbit - Eyes - Severe irritant
Duration of treatment/exposure: 24 hours
Amount/concentration applied: 750 ug
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 750 ug
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 37 %
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 10 mg
Mouse - Eyes - Moderate irritant
Amount/concentration applied: 3 %

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
Ethanol	-	1	-
Toluene	-	3	-
Xylene, mixed isomers	-	3	-
Ethylbenzene	-	2B	-
Formaldehyde (max.)	+	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Result

Ethyl Acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-Methyl-1-propanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
n-Butyl Acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Acetone	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Ethanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Lt. Aliphatic Hydrocarbon Solvent	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Toluene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-methoxy-1-methylethyl acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Xylene, mixed isomers	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Light Aromatic Hydrocarbons	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
1,3,5-Trimethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
1,2,4-Trimethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Formaldehyde (max.)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (respiratory system) - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name

Result

Section 11. Toxicological information

Toluene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Xylene, mixed isomers	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Formaldehyde (max.)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Aspiration hazard

Product/ingredient name

Result

Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1
1,3,5-Trimethylbenzene	ASPIRATION HAZARD - Category 1
1,2,4-Trimethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
stomach pains
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
KLEARVAR® Conversion Varnish Clear	24113.5	21427.7	N/A	N/A	N/A
Ethyl Acetate	5620	N/A	N/A	N/A	N/A
2-Methyl-1-propanol	2460	3400	N/A	N/A	N/A
n-Butyl Acetate	10768	N/A	N/A	N/A	N/A
Acetone	5800	N/A	N/A	N/A	N/A
Ethanol	7000	N/A	N/A	124.7	N/A
Toluene	N/A	N/A	N/A	49	N/A
2-methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Xylene, mixed isomers	4300	2500	N/A	N/A	N/A
Light Aromatic Hydrocarbons	8400	N/A	N/A	N/A	N/A
Dibutyl Phthalate	5010	N/A	N/A	N/A	N/A
Ethylbenzene	3500	N/A	N/A	11	N/A
1,3,5-Trimethylbenzene	5000	N/A	N/A	24	N/A
1,2,4-Trimethylbenzene	5000	N/A	N/A	18	N/A
Formaldehyde (max.)	500	270	250	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name

Ethyl Acetate

Result

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia cucullata*

Age: 11 days

154 mg/l [48 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Fish - Indian catfish - *Heteropneustes fossilis*

Size: 14.16 cm; Weight: 25.54 g

212.5 mg/l [96 hours]

Effect: Mortality

Acute - EC50 - Fresh water

Algae - Green algae - *Selenastrum sp.*

2500 mg/l [96 hours]

Effect: Population

Chronic - NOEC - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Embryo

Age: <24 hours

75.6 mg/l [32 days]

Effect: Mortality

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: ≤24 hours

2.4 mg/l [21 days]

Effect: Mortality

2-Methyl-1-propanol

Acute - LC50 - Fresh water

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*

Weight: 1.67 g

1330 mg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*

600 mg/l [48 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: ≤24 hours

4 mg/l [21 days]

Effect: Reproduction

n-Butyl Acetate

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g

18 mg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*

32 mg/l [48 hours]

Effect: Mortality

Acetone

Acute - EC50 - Fresh water

Algae - Green algae - *Selenastrum sp.*

7200 mg/l [96 hours]

Effect: Population

Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.95 mg/l [96 hours]

Section 12. Ecological information

Effect: Reproduction
Chronic - NOEC - Fresh water
 Crustaceans - Daphnia - *Daphniidae*
 0.016 ml/l [21 days]
Effect: Population
Chronic - NOEC - Marine water
 Fish - Threespine stickleback - *Gasterosteus aculeatus* - Larvae
Age: 7 days
 5 µg/l [42 days]
Effect: Population
Acute - LC50 - Marine water
 ISO
 Crustaceans - Calanoid copepod - *Acartia tonsa* - Copepodid
 4.42589 ml/l [48 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Guppy - *Poecilia reticulata*
Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g
 5600 ppm [96 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
 42 mg/l [4 days]
Effect: Mortality
Acute - EC50 - Marine water
 Algae - Green algae - *Ulva pertusa*
 17.921 mg/l [96 hours]
Effect: Reproduction
Chronic - NOEC - Marine water
 Algae - Green algae - *Ulva pertusa*
 4.995 mg/l [96 hours]
Effect: Reproduction
Chronic - NOEC - Fresh water
 Daphnia - Water flea - *Daphnia magna* - Neonate
Age: <24 hours
 100 µl/l [21 days]
Effect: Mortality
Chronic - NOEC - Fresh water
 Fish - Eastern mosquitofish - *Gambusia holbrooki* - Larvae
Age: 3 days
 0.375 µl/l [12 weeks]
Effect: Morphology
Acute - EC50 - Fresh water
 Daphnia - Water flea - *Daphnia magna*
 2 mg/l [48 hours]
Effect: Intoxication
Acute - LC50 - Fresh water
 US EPA
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
Weight: 0.32 g
 >10 pph [96 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Coho salmon, silver salmon - *Oncorhynchus kisutch* - Fry
Weight: 1 g
 5500 µg/l [96 hours]
Effect: Mortality

Ethanol

Lt. Aliphatic Hydrocarbon Solvent

Toluene

Section 12. Ecological information

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Juvenile (Fledgling, Hatchling, Weanling)

6000 µg/l [48 hours]

Effect: Intoxication

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: ≤24 hours

1 mg/l [21 days]

Effect: Mortality

Acute - EC50 - Fresh water

Algae - Green algae - *Raphidocelis subcapitata*

12.5 mg/l [72 hours]

Effect: Growth

Acute - LC50 - Marine water

Crustaceans - Daggerblade grass shrimp - *Palaemon pugio*

8500 µg/l [48 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 days; Size: 18.4 mm; Weight: 0.077 g

13.4 mg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

US EPA

Crustaceans - Opossum shrimp - *Americamysis bahia*

0.87 mg/l [48 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

OECD

Daphnia - Water flea - *Daphnia magna*

0.07 mg/l [21 days]

Effect: Reproduction

Chronic - NOEC

OECD

Algae - Green algae - *Scenedesmus sp.* - Exponential growth phase

100 µg/l [96 hours]

Effect: Biochemistry

Acute - EC50 - Marine water

Algae - Dinoflagellate - *Karenia brevis* - Exponential growth phase

0.0034 ppm [96 hours]

Effect: Growth

Acute - LC50 - Fresh water

US EPA

Fish - Bluegill - *Lepomis macrochirus* - Juvenile (Fledgling, Hatchling, Weanling)

0.48 mg/l [96 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

US EPA

Fish - Medaka, high-eyes - *Oryzias latipes* - Adult

Age: 18 weeks; Weight: 0.235 to 0.383 g

15.6 µg/l [218 days]

Effect: Reproduction

Acute - LC50 - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*

Xylene, mixed isomers

Dibutyl Phthalate

Ethylbenzene

Section 12. Ecological information

4200 µg/l [96 hours]

Effect: Mortality

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: ≤24 hours

2.93 mg/l [48 hours]

Effect: Intoxication

Acute - EC50 - Fresh water

Algae - Green algae - *Raphidocelis subcapitata*

3600 µg/l [96 hours]

Effect: Population

Acute - LC50 - Marine water

Crustaceans - Dungeness or edible crab - *Cancer magister* - Zoea

Age: 1

13 mg/l [48 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Fish - Goldfish - *Carassius auratus*

Age: 1 to 1.5 years; Size: 13 to 20 cm; Weight: 20 to 80 g

12.52 mg/l [96 hours]

Effect: Mortality

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

Age: ≤24 hours

0.4 mg/l [21 days]

Effect: Reproduction

Acute - LC50 - Marine water

Crustaceans - Scud - *Elasmopus pecteniscus* - Adult

4910 µg/l [48 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 34 days

7720 µg/l [96 hours]

Effect: Mortality

Chronic - NOEC - Marine water

Algae - Brown algae - *Phyllospora comosa* - Embryo

Age: 7 days

1 mg/l [96 hours]

Effect: Mortality

Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*

1.41 ppm [96 hours]

Effect: Mortality

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Embryo

Age: 8 hours

3.26 mg/l [48 hours]

Effect: Development

Chronic - NOEC - Fresh water

Crustaceans - European crayfish - *Astacus astacus* - Egg

3000 ppm [21 days]

Effect: Mortality

Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

Size: 9.4 mm

1,3,5-Trimethylbenzene

1,2,4-Trimethylbenzene

Formaldehyde (max.)

Section 12. Ecological information

0.442 mg/l [96 hours]

Effect: Reproduction

Chronic - NOEC - Fresh water

Fish - Nile tilapia - *Oreochromis niloticus* - Fingerling

Weight: 1.8 g

1.56 mg/l [12 weeks]

Effect: Cells

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Product/ingredient name

Result

Isobutylated Urea-Formaldehyde Polymer

OECD
7% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Ethyl Acetate	-	-	Readily
2-Methyl-1-propanol	-	-	Readily
n-Butyl Acetate	-	-	Readily
Acetone	-	-	Readily
Isobutylated Urea-Formaldehyde Polymer	-	-	Not readily
Ethanol	-	-	Readily
Toluene	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Light Aromatic Hydrocarbons	-	-	Readily
Ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Ethyl Acetate	-	30	Low
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	High
Toluene	-	90	Low
Xylene, mixed isomers	-	8.1 to 25.9	Low
Light Aromatic Hydrocarbons	-	10 to 2500	High
Dibutyl Phthalate	-	165.96	Low
1,3,5-Trimethylbenzene	-	161	Low
1,2,4-Trimethylbenzene	-	243	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects






No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- <u>ERG No.</u> 128	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). <u>ERG No.</u> 128	- <u>ERG No.</u> 128	-	<u>Emergency schedules</u> F-E, S-E

Section 14. Transport information

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

: **Australia inventory (AIIIC)**: Not determined.
China inventory (IECSC): Not determined.
Japan inventory (CSCL): Not determined.
Japan inventory (ISHL): Not determined.
Korea inventory (KECI): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.
Taiwan Chemical Substances Inventory (TCSI): Not determined.
Thailand inventory: Not determined.
Turkey inventory: Not determined.
Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		3
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 8/29/2025

Date of issue/Date of revision : 8/29/2025

Date of previous issue : 7/29/2025

Version : 26.01

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

