SAFETY DATA SHEET

V140952

Section 1. Identification

Product name	: ARROYO® 1K Waterborne Clear Topcoat Clear / Dull
Product code	: V140952
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related materia	l.
Manufacturer	: M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300
Product Information	: (800) 364-1359

Clear / Dull

Telephone Number

Section 2. Hazards identification

GHS label elements	(oral), 6.1% (dermal), 6.1% (inhalation)
Hazard pictograms	
Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction.
Precautionary statements	
Prevention	: Wear protective gloves. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	: Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
elements	cancel and bitth delects of other reproductive harm. TOR INDUSTRIAL ODE ONET.
elements Date of issue/Date of revision	: 12/13/2024 Date of previous issue : 10/2/2024 Version : 10.01 1/1

Section 2. Hazards identification

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
2-Methoxymethylethoxypropanol	<10	34590-94-8
Fumed Amorphous Silica	≤3	112945-52-5
Polypropylene glycol alkyl phenyl ether	≤1	9064-13-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.				
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providi aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effect persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a colla tie, belt or waistband.				
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.				
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.				

Most important symptoms/effects, acute and delayed

Clear / Dull

Potential acute health eff	ects	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: May cause an allergic skin reaction.	
Date of issue/Date of revision	: 12/13/2024 Date of previous issue : 10/2/2024	Version : 10.01 2/12
V140952 ARROYO® 1K	Waterborne Clear Topcoat	SHW-85-NA-GHS-US

Section 4. First aid measures

Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	s/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	g
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".

Date of issue/Date	of revision	: 12/13/2024	Date of previous issue	: 10/2/2024	Version : 10.01	3/12
V140952	ARROYO® 1K Waterb Clear / Dull	orne Clear Topo	coat		SHW-85-NA-GHS-US	

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name				CAS #	Exposure limits			
2-Methoxymethylethoxypropanol		34590-94-8		ACGIH TLV (United States, 1/2024). [(2-Methoxymethylethoxy)propanol] Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 606 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 909 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2020). Absorbed through skin. TWA: 100 ppm 10 hours.				
Date of issue/D	ate of revision	: 12/13/2024	Date of pre	vious issue	: 10/2/2024	Version : 10.01	4/12	
V140952 ARROYO® 1K Waterborne Clear Topcoat Clear / Dull					SHW-85-NA-GHS-US			

Section 8. Exposure controls/personal protection

		TWA: 600 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 900 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 600 mg/m ³ 8 hours.
Fumed Amorphous Silica	112945-52-5	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m ³ 10 hours.
Polypropylene glycol alkyl phenyl ether	9064-13-5	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Dipropylene glycol monomethyl ether	34590-94-8	 CA Alberta Provincial (Canada, 3/2023). Absorbed through skin. OEL: 100 ppm 8 hours. OEL: 909 mg/m³ 15 minutes. OEL: 606 mg/m³ 8 hours. OEL: 150 ppm 15 minutes. CA British Columbia Provincial (Canada, 8/2023). [dipropylene glycol methyl ether] TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 2/2024). [Dipropylene glyco monomethyl ether] Absorbed through skin. TWAEV: 100 ppm 8 hours. STEV: 150 ppm 15 minutes. STEV: 100 ppm 8 hours. STEV: 150 ppm 15 minutes. STEV: 150 ppm 15 minutes. STEV: 909 mg/m³ 15 minutes. STEV: 909 mg/m³ 15 minutes. STEV: 909 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. STEL: 150 ppm 15 minutes. STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. TWA: 100 ppm 15 minutes. TWA: 100 ppm 15 minutes. TEL: 150 ppm 15 minutes. TEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
2-Methoxymethylethoxypropanol	34590-94-8	NOM-010-STPS-2014 (Mexico, 4/2016). [(Metil-2-metoxietoxi) propanol] Absorbed through skin. TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

Section 8. Exposure controls/personal protection

No exposure indices known.

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	 Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
ndividual protection measure	es
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Clear.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 8.5
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.

Date of issue/Date of	of revision	: 12/13/2024	Date of previous issue	: 10/2/2024	Version	: 10.01	6/12
	V140952 ARROYO® 1K Waterborne Clear Topcoat Clear / Dull		coat		SHW-85-	NA-GHS-US	

Section 9. Physical and chemical properties

Evaporation rate	: 0	: 0.8 (butyl acetate = 1)		
Flammability	: N	: Not available.		
Lower and upper explosion limit/flammability limit	: Lower: 1.1% Upper: 14%			
Vapor pressure	: 2	: 2.3 kPa (17.5 mm Hg)		
Relative vapor density	: 1	: 1 [Air = 1]		
Relative density	: 1	1.03		
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: N	Not applicable.		
Auto-ignition temperature	: N	Not available.		
Decomposition temperature	: Not available.			
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	: Not applicable.			
Heat of combustion	: 2	2.627 kJ/g		

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Fumed Amorphous Silica	LD50 Oral	Rat	3160 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Methoxymethylethoxypropanol	Eyes - Mild irritant Eyes - Mild irritant	Human Rabbit	-	8 mg 24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Date of issue/Date	of revision	: 12/13/2024	Date of previous issue	: 10/2/2024	Version	: 10.01	7/12
V140952	ARROYO® 1K Waterbo Clear / Dull	orne Clear Topo	oat		SHW-85-	NA-GHS-US	

Section 11. Toxicological information

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Fumed Amorphous Silica	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate : Not available. effects Potential delayed effects : Not available. Long term exposure Potential immediate : Not available.

Potential immediate	: Not availab
effects	

Date of issue/Date of	f revision	: 12/13/2024	Date of previous issue	: 10/2/2024	Version	: 10.01	8/12
	RROYO® 1K Waterbo Clear / Dull	orne Clear Topo	coat		SHW-85-	NA-GHS-US	

Section 11. Toxicological information

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
-	

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	e of revision	: 12/13/2024	Date of previous issue	: 10/2/2024	Version	:10.01	9/12
V140952	ARROYO® 1K Wa Clear / Dull	aterborne Clear Top	coat		SHW-85-	NA-GHS-US	

Section 14. Transport information

UN proper shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	-	-	_		
hazard class(es)Packing groupEnvironmental hazardsAdditional				-	-
Environmental hazards Additional	-	-	-	-	-
hazards Additional	-	-	-	-	-
	No.	No.	No.	No.	No.
information	-	-	-	-	-
Special precautions f ransport in bulk acc o IMO instruments	conside mode of suitably to shipm of the pe dangero and on a	odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pro- ous goods must be tr all actions in case of able.	e presence of a ship etc.), does not indica isport. All packaging with the applicable oduct for transport. I ained on all of the ri	oping description for ate that the product g must be reviewed to regulations is the se People loading and sks deriving from th	a particular is packaged for suitability prior ple responsibility unloading

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-Methyl-4-isothiazolin-3-one

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

: 10/2/2024

Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification
SKIN SENSITIZATION - Category 1		Calculation method
<u>History</u>		+
Date of printing	: 12/13/2024	
Date of issue/Date of revision	: 12/13/2024	
Date of previous issue	: 10/2/2024	
Version	: 10.01	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Preventior as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	icient of Pollution From Ships, 1973

V Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date	of revision	: 12/13/2024	Date of previous issue	:10/2/2024
V140952	ARROYO® 1K Waterb Clear / Dull	orne Clear Topo	coat	

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.