

SAFETY DATA SHEET

According to 29 CFR 1910.1200
W115749

Section 1. Identification

Product name : MagnaClaw™ Pre-Cat Primer/Undercoater
Product code : W115749
Other means of identification : Not available.
Product type : Liquid.
Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : M. L. CAMPBELL
101 W. Prospect Avenue
Cleveland, OH 44115

Emergency telephone number of the company : (800) 424-9300

Product Information Telephone Number : (800) 364-1359

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
CARCINOGENICITY - Category 1B
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 2.7% (oral), 22% (dermal), 17.8% (inhalation)

GHS label elements

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure. (lungs)

Date of issue/Date of revision : 5/3/2026

Date of previous issue : 7/29/2025

Version : 38

1/28

W115749

MagnaClaw™ Pre-Cat Primer/Undercoater

SHW-85-NA-GHS-US

Section 2. Hazards identification

Precautionary statements

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
- Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **FOR INDUSTRIAL USE ONLY.** Contains Formaldehyde - a potential cancer hazard. This product must be mixed with other components before use. Before opening the packages, **READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.** Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Hazards not otherwise classified** : **DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.
- Hazards identified when used** : No known significant effects or critical hazards.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

Ingredient name	% by weight	Identifiers
n-Butyl Acetate	≥10 - ≤25	123-86-4
Calcium Carbonate	≤13	1317-65-3
Talc	≥10 - ≤25	14807-96-6
Acetone	≤10	67-64-1
Ethanol	≤10	64-17-5
2-Propanol	≤10	67-63-0
Ethyl Acetate	≤10	141-78-6
Titanium Dioxide	≤5	13463-67-7
Cellulose Nitrate	≤5	9004-70-0

Section 3. Composition/information on ingredients

1-Butanol	≤4.8	71-36-3
Dialkyl (C9-C11) Phthalates	≤5	68515-49-1
Cellulose Nitrate	≤3	9004-70-0
2-methoxy-1-methylethyl acetate	≤3	108-65-6
Isobutylated Urea-Formaldehyde Polymer	≤3	68002-18-6
2-Methyl-1-propanol	≤1.4	78-83-1
Xylene, mixed isomers	<1	1330-20-7
Light Aromatic Hydrocarbons	<1	64742-95-6
Heavy Aliphatic Solvent	≤0.3	64742-82-1
trimethylbenzene	≤0.3	25551-13-7
Ethylbenzene	≤0.3	100-41-4
Hydrotreated Heavy Petroleum Naphtha	≤0.3	64742-48-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Section 4. First aid measures

- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 - pain
 - watering
 - redness

- Inhalation** : Adverse symptoms may include the following:
 - nausea or vomiting
 - headache
 - drowsiness/fatigue
 - dizziness/vertigo
 - unconsciousness
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

- Skin contact** : Adverse symptoms may include the following:
 - pain or irritation
 - redness
 - blistering may occur
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

- Ingestion** : Adverse symptoms may include the following:
 - stomach pains
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
 - carbon dioxide
 - carbon monoxide
 - nitrogen oxides
 - metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Remark** : Flammable liquid.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Contains a formaldehyde-based resin which, under certain conditions of use, may release formaldehyde. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat,

Section 7. Handling and storage

sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
n-Butyl Acetate	123-86-4	ACGIH TLV (United States, 1/2025) [Butyl acetates] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 150 ppm. TWA 10 hours: 710 mg/m ³ . STEL 15 minutes: 200 ppm. STEL 15 minutes: 950 mg/m ³ . OSHA PEL (United States, 5/2018) TWA 8 hours: 150 ppm. TWA 8 hours: 710 mg/m ³ .
Calcium Carbonate	1317-65-3	NIOSH REL (United States, 10/2020) [calcium carbonate] TWA 10 hours: 10 mg/m ³ . Form: Total. TWA 10 hours: 5 mg/m ³ . Form: Respirable fraction. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m ³ . Form: Total dust. TWA 8 hours: 5 mg/m ³ . Form: Respirable fraction.
Talc	14807-96-6	ACGIH TLV (United States, 1/2025) A4. TWA 8 hours: 2 mg/m ³ . Form: Respirable fraction. NIOSH REL (United States, 10/2020) TWA 10 hours: 2 mg/m ³ . Form: Respirable fraction.
Acetone	67-64-1	ACGIH TLV (United States, 1/2025) A4. TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 250 ppm.

Section 8. Exposure controls/personal protection

Ethanol	64-17-5	<p>TWA 10 hours: 590 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 2400 mg/m³. ACGIH TLV (United States, 1/2025) A3. STEL 15 minutes: 1000 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 1000 ppm. TWA 10 hours: 1900 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m³.</p>
2-Propanol	67-63-0	<p>ACGIH TLV (United States, 1/2025) A4. TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 400 ppm. TWA 10 hours: 980 mg/m³. STEL 15 minutes: 500 ppm. STEL 15 minutes: 1225 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 400 ppm. TWA 8 hours: 980 mg/m³.</p>
Ethyl Acetate	141-78-6	<p>ACGIH TLV (United States, 1/2025) TWA 8 hours: 400 ppm. TWA 8 hours: 1440 mg/m³. NIOSH REL (United States, 10/2020) TWA 10 hours: 400 ppm. TWA 10 hours: 1400 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 400 ppm. TWA 8 hours: 1400 mg/m³.</p>
Titanium Dioxide	13463-67-7	<p>ACGIH TLV (United States, 1/2025) A3. TWA 8 hours: 2.5 mg/m³. Form: respirable fraction, finescale particles. NIOSH REL (United States, 10/2020) NIA. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m³. Form: Total dust.</p>
Cellulose Nitrate 1-Butanol	9004-70-0 71-36-3	<p>None. ACGIH TLV (United States, 1/2025) TWA 8 hours: 20 ppm. NIOSH REL (United States, 10/2020) Absorbed through skin. CEIL: 50 ppm. CEIL: 150 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 300 mg/m³.</p>
Dialkyl (C9-C11) Phthalates Cellulose Nitrate 2-methoxy-1-methylethyl acetate	68515-49-1 9004-70-0 108-65-6	<p>None. None. OARS WEEL (United States, 6/2025) TWA 8 hours: 50 ppm.</p>
Isobutylated Urea-Formaldehyde Polymer 2-Methyl-1-propanol	68002-18-6 78-83-1	<p>None. ACGIH TLV (United States, 1/2025) TWA 8 hours: 50 ppm. TWA 8 hours: 152 mg/m³. NIOSH REL (United States, 10/2020)</p>

Section 8. Exposure controls/personal protection

Xylene, mixed isomers	1330-20-7	<p>TWA 10 hours: 50 ppm. TWA 10 hours: 150 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 300 mg/m³.</p> <p>ACGIH TLV (United States, 1/2025) [p-xylene and mixtures containing p-xylene] A4. Ototoxicant. TWA 8 hours: 20 ppm.</p> <p>OSHA PEL (United States, 5/2018) [Xylenes] TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.</p>
Light Aromatic Hydrocarbons Heavy Aliphatic Solvent trimethylbenzene	64742-95-6 64742-82-1 25551-13-7	<p>None.</p> <p>None.</p> <p>ACGIH TLV (United States, 1/2025) [trimethyl benzene, isomers] TWA 8 hours: 10 ppm.</p> <p>ACGIH TLV (United States, 1/2025) A3. Ototoxicant. TWA 8 hours: 20 ppm.</p> <p>NIOSH REL (United States, 10/2020) TWA 10 hours: 100 ppm. TWA 10 hours: 435 mg/m³. STEL 15 minutes: 125 ppm. STEL 15 minutes: 545 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.</p>
Ethylbenzene	100-41-4	<p>None.</p> <p>None.</p> <p>ACGIH TLV (United States, 1/2025) A3. Ototoxicant. TWA 8 hours: 20 ppm.</p> <p>NIOSH REL (United States, 10/2020) TWA 10 hours: 100 ppm. TWA 10 hours: 435 mg/m³. STEL 15 minutes: 125 ppm. STEL 15 minutes: 545 mg/m³.</p> <p>OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.</p>
Hydrotreated Heavy Petroleum Naphtha	64742-48-9	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
n-butyl acetate	123-86-4	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 200 ppm. TWA 8 hours: 150 ppm.</p> <p>CA British Columbia Provincial (Canada, 6/2025) [butyl acetate, all isomers] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) [butyl acetates, all isomers] STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) [butyl acetates] STEV 15 minutes: 150 ppm. TWAEV 8 hours: 50 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 15 minutes: 200 ppm. OEL 15 minutes: 950 mg/m³. OEL 8 hours: 150 ppm. OEL 8 hours: 713 mg/m³.</p>
talc (none asbestiform)	14807-96-6	<p>CA Saskatchewan Provincial (Canada, 4/2021)</p>

Section 8. Exposure controls/personal protection

acetone	67-64-1	<p>TWA 8 hours: 2 mg/m³. Form: respirable fraction.</p> <p>CA British Columbia Provincial (Canada, 6/2025)</p> <p>TWA 8 hours: 2 mg/m³. Form: respirable. Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica.</p> <p>CA Ontario Provincial (Canada, 6/2019)</p> <p>TWA 8 hours: 2 mg/m³. Form: respirable particulate matter.</p> <p>TWA 8 hours: 2 fibers/cm³.</p> <p>CA Quebec Provincial (Canada, 2/2024)</p> <p>TWAEV 8 hours: 2 mg/m³. Form: respirable aerosol fraction.</p> <p>CA Alberta Provincial (Canada, 3/2023)</p> <p>OEL 8 hours: 2 mg/m³. Form: respirable particulate.</p> <p>CA Saskatchewan Provincial (Canada, 4/2021)</p> <p>STEL 15 minutes: 750 ppm.</p> <p>TWA 8 hours: 500 ppm.</p> <p>CA British Columbia Provincial (Canada, 6/2025)</p> <p>TWA 8 hours: 250 ppm.</p> <p>STEL 15 minutes: 500 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019)</p> <p>TWA 8 hours: 250 ppm.</p> <p>STEL 15 minutes: 500 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024)</p> <p>TWAEV 8 hours: 250 ppm.</p> <p>STEV 15 minutes: 500 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023)</p> <p>OEL 8 hours: 1200 mg/m³.</p> <p>OEL 15 minutes: 1800 mg/m³.</p> <p>OEL 8 hours: 500 ppm.</p> <p>OEL 15 minutes: 750 ppm.</p>
Ethyl alcohol	64-17-5	<p>CA Saskatchewan Provincial (Canada, 4/2021)</p> <p>STEL 15 minutes: 1250 ppm.</p> <p>TWA 8 hours: 1000 ppm.</p> <p>CA British Columbia Provincial (Canada, 6/2025)</p> <p>STEL 15 minutes: 1000 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019)</p> <p>STEL 15 minutes: 1000 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024)</p> <p>C3.</p> <p>STEV 15 minutes: 1000 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023)</p> <p>OEL 8 hours: 1000 ppm.</p> <p>OEL 8 hours: 1880 mg/m³.</p>
Isopropyl alcohol	67-63-0	<p>CA Saskatchewan Provincial (Canada, 4/2021)</p> <p>STEL 15 minutes: 400 ppm.</p> <p>TWA 8 hours: 200 ppm.</p> <p>CA British Columbia Provincial (Canada,</p>

Section 8. Exposure controls/personal protection

Normal butyl alcohol	71-36-3	<p>6/2025) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 200 ppm. STEV 15 minutes: 400 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 15 minutes: 984 mg/m³. OEL 8 hours: 200 ppm. OEL 15 minutes: 400 ppm. OEL 8 hours: 492 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 30 ppm. TWA 8 hours: 20 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 15 ppm. C: 30 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 20 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 60 mg/m³. OEL 8 hours: 20 ppm. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 60 ppm. TWA 8 hours: 50 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 50 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 50 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 50 ppm. TWAEV 8 hours: 152 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 50 ppm. OEL 8 hours: 152 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) [Xylene] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA British Columbia Provincial (Canada, 6/2025) [xylene, all isomers] TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA Quebec Provincial (Canada, 2/2024) [Xylene]</p>
Isobutyl alcohol	78-83-1	<p>6/2025) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 200 ppm. STEV 15 minutes: 400 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 15 minutes: 984 mg/m³. OEL 8 hours: 200 ppm. OEL 15 minutes: 400 ppm. OEL 8 hours: 492 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 30 ppm. TWA 8 hours: 20 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 15 ppm. C: 30 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 20 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 60 mg/m³. OEL 8 hours: 20 ppm. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 60 ppm. TWA 8 hours: 50 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 50 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 50 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 50 ppm. TWAEV 8 hours: 152 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 50 ppm. OEL 8 hours: 152 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) [Xylene] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA British Columbia Provincial (Canada, 6/2025) [xylene, all isomers] TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA Quebec Provincial (Canada, 2/2024) [Xylene]</p>
Xylene	1330-20-7	<p>6/2025) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 200 ppm. STEV 15 minutes: 400 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 15 minutes: 984 mg/m³. OEL 8 hours: 200 ppm. OEL 15 minutes: 400 ppm. OEL 8 hours: 492 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 30 ppm. TWA 8 hours: 20 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 15 ppm. C: 30 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 20 ppm. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 60 mg/m³. OEL 8 hours: 20 ppm. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 60 ppm. TWA 8 hours: 50 ppm. CA British Columbia Provincial (Canada, 6/2025) TWA 8 hours: 50 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 50 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 50 ppm. TWAEV 8 hours: 152 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 50 ppm. OEL 8 hours: 152 mg/m³. CA Saskatchewan Provincial (Canada, 4/2021) [Xylene] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA British Columbia Provincial (Canada, 6/2025) [xylene, all isomers] TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA Quebec Provincial (Canada, 2/2024) [Xylene]</p>

Section 8. Exposure controls/personal protection

Ethylbenzene	100-41-4	<p>TWAEV 8 hours: 100 ppm. TWAEV 8 hours: 434 mg/m³. STEV 15 minutes: 150 ppm. STEV 15 minutes: 651 mg/m³.</p> <p>CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene] OEL 8 hours: 100 ppm. OEL 15 minutes: 651 mg/m³. OEL 15 minutes: 150 ppm. OEL 8 hours: 434 mg/m³.</p> <p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm.</p> <p>CA British Columbia Provincial (Canada, 6/2025) Carc 2B. TWA 8 hours: 20 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) C3. TWAEV 8 hours: 20 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 100 ppm. OEL 8 hours: 434 mg/m³. OEL 15 minutes: 543 mg/m³. OEL 15 minutes: 125 ppm.</p>
--------------	----------	--

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
n-Butyl Acetate	123-86-4	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm.
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 500 ppm. STEL 15 minutes: 750 ppm.
Ethanol	64-17-5	NOM-010-STPS-2014 (Mexico, 4/2016) A3. STEL 15 minutes: 1000 ppm.
2-Propanol	67-63-0	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm.
Ethyl Acetate	141-78-6	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 400 ppm.
1-Butanol	71-36-3	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 20 ppm.
2-Methyl-1-propanol	78-83-1	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 50 ppm.

Biological exposure indices (United States)

Section 8. Exposure controls/personal protection

Ingredient name	Exposure indices
Acetone	ACGIH BEI (United States, 1/2025) BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
2-Propanol	ACGIH BEI (United States, 1/2025) BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.
Xylene, mixed isomers	ACGIH BEI (United States, 1/2025) [xylenes (technical or commercial grades)] BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
Ethylbenzene	ACGIH BEI (United States, 1/2025) BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Acetone	Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift.
2-Propanol	Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 40 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the shift at the end of the work week.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 8. Exposure controls/personal protection

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Black.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : 55°C (131°F)
- Flash point** : Closed cup: -7°C (19.4°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability** : Flammable liquid.
- Lower and upper explosion limit/flammability limit** : Lower: 1.2%
Upper: 19%
- Vapor pressure** : 24 kPa (180 mm Hg)
- Relative vapor density** : 1.5 [Air = 1]

Section 9. Physical and chemical properties

Relative density : 1.16
Density : 1.15 g/cm³
Solubility(ies) :

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water : Not applicable.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight : Not applicable.
Particle characteristics
Median particle size : Not applicable.
Heat of combustion : 15.362 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : The product is stable.
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Result

n-Butyl Acetate

Rat - Oral - LD50

10768 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes

Rabbit - Dermal - LD50

>17600 mg/kg

Acetone

Rat - Oral - LD50

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in

Section 11. Toxicological information

Ethanol	righting reflex) Behavioral - Tremor Rat - Oral - LD50 7 g/kg Rat - Inhalation - LC50 Vapor 124700 mg/m ³ [4 hours]
2-Propanol	Rabbit - Dermal - LD50 12800 mg/kg Rat - Oral - LD50 5000 mg/kg <u>Toxic effects:</u> Behavioral - General anesthetic Rat - Oral - LD50 5620 mg/kg
Ethyl Acetate	Rat - Oral - LD50 5620 mg/kg
Cellulose Nitrate	Rat - Oral - LD50 >5 g/kg
1-Butanol	Rat - Oral - LD50 790 mg/kg <u>Toxic effects:</u> Liver - Fatty liver degeneration Kidney, Ureter, and Bladder - Other changes Blood - Other changes Rabbit - Dermal - LD50 3400 mg/kg Rat - Inhalation - LC50 Vapor 24000 mg/m ³ [4 hours]
Dialkyl (C9-C11) Phthalates	Rabbit - Dermal - LD50 16000 mg/kg Rat - Oral - LD50 >60000 mg/kg
Cellulose Nitrate	Rat - Oral - LD50 >5 g/kg
2-methoxy-1-methylethyl acetate	Rat - Oral - LD50 8532 mg/kg Rabbit - Dermal - LD50 >5 g/kg
Isobutylated Urea-Formaldehyde Polymer	Rat - Oral - LD50 >5 g/kg <u>Toxic effects:</u> Olfaction - Other changes Behavioral - Somnolence (general depressed activity) Behavioral - Food intake (animal) Rabbit - Dermal - LD50 >5 g/kg <u>Toxic effects:</u> Skin After systemic exposure - Dermatitis, other
2-Methyl-1-propanol	Rat - Oral - LD50 2460 mg/kg Rabbit - Dermal - LD50 3400 mg/kg Rat - Inhalation - LC50 Vapor 19200 mg/m ³ [4 hours]
Xylene, mixed isomers	Rat - Oral - LD50 4300 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes Rat - Inhalation - LC50 Gas. 6700 ppm [4 hours] <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)
Light Aromatic Hydrocarbons	Rat - Oral - LD50 8400 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other

Section 11. Toxicological information

trimethylbenzene	changes Rat - Oral - LD50 8970 mg/kg
Ethylbenzene	Rat - Oral - LD50 3500 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes Rabbit - Dermal - LD50 >5000 mg/kg
Hydrotreated Heavy Petroleum Naphtha	Rat - Oral - LD50 >6 g/kg Rat - Inhalation - LC50 Vapor 8500 mg/m ³ [4 hours] <u>Toxic effects:</u> Lung, Thorax, or Respiration - Other changes

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Product/ingredient name

Result

n-Butyl Acetate	Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
Talc	Human - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 72 hours <u>Amount/concentration applied:</u> 300 ug l
Acetone	Rabbit - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
Ethanol	Rabbit - Skin - Mild irritant <u>Amount/concentration applied:</u> 395 mg Rabbit - Skin - Mild irritant <u>Amount/concentration applied:</u> 400 mg
2-Propanol	Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 20 mg
Titanium Dioxide	Rabbit - Skin - Mild irritant <u>Amount/concentration applied:</u> 500 mg Human - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 72 hours <u>Amount/concentration applied:</u> 300 ug l
1-Butanol	Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 20 mg
Xylene, mixed isomers	Rat - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 8 hours <u>Amount/concentration applied:</u> 60 uL Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
trimethylbenzene	Rabbit - Skin - Moderate irritant <u>Amount/concentration applied:</u> 100 % Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
Ethylbenzene	Rabbit - Skin - Mild irritant

Section 11. Toxicological information

Duration of treatment/exposure: 24 hours
Amount/concentration applied: 15 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Result

n-Butyl Acetate

Rabbit - Eyes - Moderate irritant
Amount/concentration applied: 100 mg

Acetone

Human - Eyes - Mild irritant
Amount/concentration applied: 186300 ppm

Rabbit - Eyes - Mild irritant
Amount/concentration applied: 10 uL

Rabbit - Eyes - Moderate irritant
Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg

Ethanol

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 0.066666667 minutes

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 1 hours

Amount/concentration applied: 50 pph

2-Propanol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 10 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

1-Butanol

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 2 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 0.005 MI

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 1.62 mg

Dialkyl (C9-C11) Phthalates

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 0.1 MI

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Xylene, mixed isomers

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Section 11. Toxicological information

Light Aromatic Hydrocarbons

Rabbit - Eyes - Mild irritant
Duration of treatment/exposure: 24 hours
Amount/concentration applied: 100 uL

trimethylbenzene

Rabbit - Eyes - Mild irritant
Duration of treatment/exposure: 24 hours
Amount/concentration applied: 500 mg

Ethylbenzene

Rabbit - Eyes - Severe irritant
Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc	-	2A	-
Ethanol	-	1	-
2-Propanol	-	3	-
Titanium Dioxide	-	2B	-
Xylene, mixed isomers	-	3	-
Ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
n-Butyl Acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Calcium Carbonate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Acetone	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Ethanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-Propanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Ethyl Acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
1-Butanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-methoxy-1-methylethyl acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-Methyl-1-propanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Xylene, mixed isomers	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Light Aromatic Hydrocarbons	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Heavy Aliphatic Solvent	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Hydrotreated Heavy Petroleum Naphtha	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Talc	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1
Xylene, mixed isomers	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Heavy Aliphatic Solvent	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1
Ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Aspiration hazard

Product/ingredient name	Result
--------------------------------	---------------

Section 11. Toxicological information

Xylene, mixed isomers	ASPIRATION HAZARD - Category 1
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1
Heavy Aliphatic Solvent	ASPIRATION HAZARD - Category 1
trimethylbenzene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1
Hydrotreated Heavy Petroleum Naphtha	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure


Not available.


Potential acute health effects


- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following: 
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following: 
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following: 
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Section 11. Toxicological information

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

- General** : Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
MagnaClaw™ Pre-Cat Primer/Undercoater	31552.6	53911.7	N/A	N/A	N/A
n-Butyl Acetate	10768	N/A	N/A	N/A	N/A
Acetone	5800	N/A	N/A	N/A	N/A
Ethanol	7000	N/A	N/A	124.7	N/A
2-Propanol	5000	12800	N/A	N/A	N/A
Ethyl Acetate	5620	N/A	N/A	N/A	N/A
1-Butanol	2500	3400	N/A	24	N/A
Dialkyl (C9-C11) Phthalates	N/A	16000	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
2-Methyl-1-propanol	2460	3400	N/A	N/A	N/A
Xylene, mixed isomers	4300	2500	N/A	N/A	N/A
Light Aromatic Hydrocarbons	8400	N/A	N/A	N/A	N/A
trimethylbenzene	500	N/A	N/A	11	N/A
Ethylbenzene	3500	N/A	N/A	11	N/A
Hydrotreated Heavy Petroleum Naphtha	N/A	N/A	N/A	8.5	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name

Result

n-Butyl Acetate

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g
 18 mg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*
 32 mg/l [48 hours]
Effect: Mortality

Acetone

Acute - EC50 - Fresh water

Algae - Green algae - *Selenastrum sp.*
 7200 mg/l [96 hours]
Effect: Population

Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*
 4.95 mg/l [96 hours]

Section 12. Ecological information

Effect: Reproduction
Chronic - NOEC - Fresh water
 Crustaceans - Daphnia - *Daphniidae*
 0.016 ml/l [21 days]
Effect: Population
Chronic - NOEC - Marine water
 Fish - Threespine stickleback - *Gasterosteus aculeatus* - Larvae
Age: 7 days
 5 µg/l [42 days]
Effect: Population
Acute - LC50 - Marine water
 ISO
 Crustaceans - Calanoid copepod - *Acartia tonsa* - Copepodid
 4.42589 ml/l [48 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Guppy - *Poecilia reticulata*
Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g
 5600 ppm [96 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
 42 mg/l [4 days]
Effect: Mortality
Acute - EC50 - Marine water
 Algae - Green algae - *Ulva pertusa*
 17.921 mg/l [96 hours]
Effect: Reproduction
Chronic - NOEC - Marine water
 Algae - Green algae - *Ulva pertusa*
 4.995 mg/l [96 hours]
Effect: Reproduction
Chronic - NOEC - Fresh water
 Daphnia - Water flea - *Daphnia magna* - Neonate
Age: <24 hours
 100 µl/l [21 days]
Effect: Mortality
Chronic - NOEC - Fresh water
 Fish - Eastern mosquitofish - *Gambusia holbrooki* - Larvae
Age: 3 days
 0.375 µl/l [12 weeks]
Effect: Morphology
Acute - EC50 - Fresh water
 Daphnia - Water flea - *Daphnia magna*
 2 mg/l [48 hours]
Effect: Intoxication
Acute - LC50 - Marine water
 Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*
 1400 mg/l [48 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Harlequinfish, red rasbora - *Rasbora heteromorpha*
Size: 1 to 3 cm
 4200 mg/l [96 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Daphnia - Water flea - *Daphnia cucullata*

Ethanol

2-Propanol

Ethyl Acetate

Section 12. Ecological information

Age: 11 days
 154 mg/l [48 hours]
Effect: Mortality
Acute - LC50 - Fresh water
 Fish - Indian catfish - *Heteropneustes fossilis*
Size: 14.16 cm; Weight: 25.54 g
 212.5 mg/l [96 hours]
Effect: Mortality
Acute - EC50 - Fresh water
 Algae - Green algae - *Selenastrum sp.*
 2500 mg/l [96 hours]
Effect: Population
Chronic - NOEC - Fresh water
 Fish - Fathead minnow - *Pimephales promelas* - Embryo
Age: <24 hours
 75.6 mg/l [32 days]
Effect: Mortality
Chronic - NOEC - Fresh water
 Daphnia - Water flea - *Daphnia magna*
Age: ≤24 hours
 2.4 mg/l [21 days]
Effect: Mortality
Acute - LC50 - Marine water
 Fish - Mummichog - *Fundulus heteroclitus*
 >1000 mg/l [96 hours]
Effect: Mortality
Acute - EC50 - Fresh water
 Algae - Green algae - *Raphidocelis subcapitata*
 579 mg/l [96 hours]
Effect: Biochemistry
Acute - LC50 - Fresh water
 Fish - Fathead minnow - *Pimephales promelas*
Age: 33 days; Size: 20.6 mm; Weight: 0.119 g
 1730 mg/l [96 hours]
Effect: Mortality
Acute - EC50 - Fresh water
 Daphnia - Water flea - *Daphnia magna*
Age: 6 to 24 hours
 1983 mg/l [48 hours]
Effect: Intoxication
Acute - EC50 - Fresh water
 Algae - Green algae - *Raphidocelis subcapitata*
 579 mg/l [96 hours]
Effect: Biochemistry
Acute - LC50 - Fresh water
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*
Weight: 1.67 g
 1330 mg/l [96 hours]
Effect: Mortality
Acute - LC50 - Marine water
 Crustaceans - Brine shrimp - *Artemia salina*
 600 mg/l [48 hours]
Effect: Mortality
Chronic - NOEC - Fresh water
 Daphnia - Water flea - *Daphnia magna*
Age: ≤24 hours
 4 mg/l [21 days]

Titanium Dioxide

Cellulose Nitrate

1-Butanol

Cellulose Nitrate

2-Methyl-1-propanol

Section 12. Ecological information

Xylene, mixed isomers	<p><u>Effect</u>: Reproduction Acute - LC50 - Marine water Crustaceans - Daggerblade grass shrimp - <i>Palaemon pugio</i> 8500 µg/l [48 hours] <u>Effect</u>: Mortality Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 31 days; <u>Size</u>: 18.4 mm; <u>Weight</u>: 0.077 g 13.4 mg/l [96 hours] <u>Effect</u>: Mortality</p>
trimethylbenzene	<p>Acute - LC50 - Marine water Crustaceans - Daggerblade grass shrimp - <i>Palaemon pugio</i> 5600 µg/l [48 hours] <u>Effect</u>: Mortality</p>
Ethylbenzene	<p>Acute - LC50 - Fresh water Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i> 4200 µg/l [96 hours] <u>Effect</u>: Mortality Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> - Neonate <u>Age</u>: ≤24 hours 2.93 mg/l [48 hours] <u>Effect</u>: Intoxication Acute - EC50 - Fresh water Algae - Green algae - <i>Raphidocelis subcapitata</i> 3600 µg/l [96 hours] <u>Effect</u>: Population</p>

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Product/ingredient name	Result
Isobutylated Urea-Formaldehyde Polymer	OECD 7% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-Butyl Acetate	-	-	Readily
Acetone	-	-	Readily
Ethanol	-	-	Readily
2-Propanol	-	-	Readily
Ethyl Acetate	-	-	Readily
1-Butanol	-	-	Readily
Isobutylated Urea-Formaldehyde Polymer	-	-	Not readily
2-Methyl-1-propanol	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Light Aromatic Hydrocarbons	-	-	Readily
Ethylbenzene	-	-	Readily

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Ethyl Acetate	-	30	Low
Dialkyl (C9-C11) Phthalates	-	0.1	Low
Xylene, mixed isomers	-	8.1 to 25.9	Low
Light Aromatic Hydrocarbons	-	10 to 2500	High
Heavy Aliphatic Solvent	-	10 to 2500	High
Hydrotreated Heavy Petroleum Naphtha	-	10 to 2500	High

Mobility in soil

Soil/Water partition coefficient : Not available.






Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.

Section 14. Transport information

Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	-	-	Emergency schedules F-E, S-E
	ERG No. 128	ERG No. 128	ERG No. 128		

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

U.S. Federal regulations :
[SARA 313](#)

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production. Reporting of chemicals in this section does not necessarily indicate their presence in the final formulated product.

Ingredient name	% by weight	CAS number
Lead (as Pb)	0.00001	
1-Butanol	4	71-36-3
Ethylbenzene	0.1	100-41-4

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Section 15. Regulatory information

Not listed.

International lists

- : **Australia inventory (AIIIC):** Not determined.
- : **China inventory (IECSC):** Not determined.
- : **Japan inventory (CSCL):** Not determined.
- : **Japan inventory (ISHL):** Not determined.
- : **Korea inventory (KECI):** Not determined.
- : **New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- : **Philippines inventory (PICCS):** Not determined.
- : **Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- : **Thailand inventory:** Not determined.
- : **Turkey inventory:** Not determined.
- : **Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		3
Physical hazards		4

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
CARCINOGENICITY - Category 1B	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of printing : 5/3/2026

Date of issue/Date of revision : 5/3/2026

Date of previous issue : 7/29/2025

Version : 38

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

Section 16. Other information

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

✔ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.