SAFETY DATA SHEET

3876

Section 1. Identification

Product name	: SUPERLUX by PARA Interior Flat Ceiling Latex White
Product code	: 3876
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of the	ne substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	 Manufactured for: PARA PAINTS By: GENERAL PAINT CORP. 950 Raymur Ave. Vancouver, BC V6A 3L5
Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-855-330-4753
Transportation Emergency	: (800) 424-9300

Section 2. Hazards identification

Telephone Number

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	None known.

Data of issu	e/Date of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version : 15.02	1/11
3876		ARA Interior Flat Ce	···· • • • • • • • • • • • • • • • • •	. 3/23/2024	SHW-85-NA-GHS-CA	1/11
3070	White	ARA IIIlenoi Fial Ce	anny Latex		300-03-NA-003-CA	

Section 2. Hazards identification

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	10.47	13463-67-7
Heavy Paraffinic Oil	0.32	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/e	effects, acute and delayed

Potential acute health effe		
Eye contact	No known significant effects or critical hazards.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	No known significant effects or critical hazards.	
Ingestion	No known significant effects or critical hazards.	
Over-exposure signs/sym	<u>ns</u>	
Eye contact	No specific data.	

Date of issue/Date	of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version	:15.02	2/11
3876	SUPERLUX by PARA Ir White	nterior Flat Ceili	ng Latex		SHW-85-	NA-GHS-CA	

Section 4. First aid measures

: No specific data.
: No specific data.
: No specific data.
dical attention and special treatment needed, if necessary
 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
: No specific treatment.
: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Date of issue/Date of revision	n : 6/10/2024	Date of previous issue	: 5/29/2024	Version : 15.02	3/11
3876 SUPERL White	JX by PARA Interior Flat Ce	eiling Latex		SHW-85-NA-GHS-CA	

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient	name		CAS #		Exposure limits		
Titanium Die	oxide		13463-	67-7	ACGIH TLV (United	hours. Form: Total c I States, 7/2023). hours. Form: respira	
Heavy Paraffinic Oil		64742-	65-0	ACGIH TLV (United States, 7/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). [OIL			
Date of issue/Da	te of revision	: 6/10/2024	Date of previous issu	ie	: 5/29/2024	Version : 15.02	4/11
3876	SUPERLUX by P White	ARA Interior Flat Ce	iling Latex			SHW-85-NA-GHS-CA	

Section 8. Exposure controls/personal protection

	MIST MINERAL] TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
--	---

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		
Occupational exposure limits (Mexico)		

Ingredient name	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls
 If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
 Environmental exposure controls
 Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date	of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version	:15.02	5/11
3876	SUPERLUX by PARA In White	nterior Flat Ceili	ng Latex		SHW-85-	NA-GHS-CA	

Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Liqu	uid.			
Color	:	Whi	White.			
Odor	:	Not	Not available.			
Odor threshold	:	Not	available.			
рН	:	9				
Melting point/freezing point	:	Not	Not available.			
Boiling point, initial boiling point, and boiling range	:	100	100°C (212°F)			
Flash point	:	Clos	sed cup: Not applicable.			
Evaporation rate	:	0.09	∂ (butyl acetate = 1)			
Flammability	:	Not	available.			
Lower and upper explosion limit/flammability limit	:	Not	Not available.			
Vapor pressure	:	2.3 kPa (17.5 mm Hg)				
Relative vapor density	:	1 [Air = 1]				
Relative density	:	1.41				
Solubility(ies)	:	:				
Media			Result			
cold water			Partially soluble			
Partition coefficient: n- octanol/water	:	Not	Not applicable.			
Auto-ignition temperature	:	Not available.				
Decomposition temperature	:	: Not available.				
Viscosity	:	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight	:	Not	t applicable.			
Heat of combustion	:	0.47	78 kJ/g			

Section 10. Stability and reactivity

 Reactivity
 : No specific test data related to reactivity available for this product or its ingredients.

 Chemical stability
 : The product is stable.

 Possibility of hazardous reactions
 : Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date	of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version	:15.02	6/1
3876	SUPERLUX by PARA In White	nterior Flat Ceili	ng Latex		SHW-85-	NA-GHS-CA	

Section 10. Stability and reactivity				
Conditions to avoid	: No specific data.			
Incompatible materials	: No specific data.			
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely : Not available.

routes of exposure

Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version	: 15.02	7/1
3876	SUPERLUX by PARA In White	iterior Flat Ceilii	ng Latex		SHW-85-	NA-GHS-CA	

Section 11. Toxicological information

Inhalation	: No known significant effects or critical hazards.			
Skin contact	: No known significant effects or critical hazards.			
Ingestion	: No known significant effects or critical hazards.			
Symptoms related to the p	physical, chemical and toxicological characteristics			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No specific data.			
Delayed and immediate ef	fects and also chronic effects from short and long term exposure			
<u>Short term exposure</u>				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
<u>Long term exposure</u>				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health e	ffects			
Not available.				
General	: No known significant effects or critical hazards.			
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.			
Mutagenicity	: No known significant effects or critical hazards.			
Teratogenicity	: No known significant effects or critical hazards.			
Developmental effects	: No known significant effects or critical hazards.			
Fertility effects	: No known significant effects or critical hazards.			

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Date of issue/Date of	of revision	: 6/10/2024	Date of previous issue	: 5/29/2024	Version : 15.02	8/11
	SUPERLUX by PARA White	Interior Flat Ceil	ing Latex		SHW-85-NA-GHS-CA	

Section 12. Ecological information

Mobility in soil

3876

Soil/water partition	
coefficient (Koc)	

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

SUPERLUX by PARA Interior Flat Ceiling Latex

White

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG		
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.		
UN proper shipping name	-	-	-	-	-		
Transport hazard class(es)	-	-	-	-	-		
Packing group	-	-	-	-	-		
Environmental hazards	No.	No.	No.	No.	No.		
Additional information	-	-	-	-	-		
Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.							

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

Section 15. Regulatory information

International regulations **Montreal Protocol** Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification
CARCINOGENICITY - (Category 2	Calculation method
History		
Date of printing	: 6/10/2024	

Date of printing	. 0/10/2024
Date of issue/Date of	: 6/10/2024
revision	
Date of previous issue	: 5/29/2024
Version	: 15.02

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.