

Product Data Sheet



PRATT & LAMBERT
PAINTS
Never compromise

Pro-Hide[®] Gold Interior Alkyd

S8800 – Semi-Gloss

Pro-Hide[®] Gold Interior Alkyd Semi-Gloss Enamel is a high quality, high hiding finish formulated for excellent flow and leveling, and extreme durability and washability.

- Enamel finish for a long-lasting, hard, washable coating
- Excellent hide
- Outstanding durability
- Excellent flow and leveling
- Great for cabinets, doors & trim

Recommended Uses

Recommended for interior drywall, masonry, plaster, wood, cabinets, doors, trim and previously painted surfaces.

Recommended Systems

Drywall

1 coat Pro-Hide[®] Gold Interior/Exterior Waterborne Primer
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Masonry (cured 30+ days)

1 coat Pro-Hide[®] Gold Interior/Exterior Waterborne Primer
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Concrete Block

For a filled effect use 1 coat Pro-Hide[®] Silver Latex Block Filler
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Plaster (cured 30+ days)

1 coat Pro-Hide[®] Gold Interior/Exterior Waterborne Primer
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Wood

1 coat Pratt & Lambert[®] Multi-Surface Oil Base Primer OR
Pro-Hide[®] Gold Interior/Exterior Waterborne Primer
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Metal

1 coat Pro-Hide[®] Gold Interior/Exterior Waterborne Primer
1 or 2 coats Pro-Hide[®] Gold Interior Alkyd

Previously Painted Surfaces

No primer necessary
2 coats Pro-Hide[®] Gold Interior Alkyd

Technical Data

Vehicle: Alkyd
Finish: 35-45 units @ 60°
Flash Point: 106°F, PMCC
Volume Solids*: 52 ± 2%
Weight Solids*: 73 ± 2%
Weight/Gallon*: 11.3 lbs.

VOC (less exempt solvents): VOC: 371 g/L – 3.10 lb/gal as per 40 CFR 59.406

Spread Rate: 450 sq. ft. per gallon, porosity and texture dependent

Film Thickness*: @ 4.0 mils wet; 2.1 mils dry

* Product data calculated on Base 1

Drying Time (@ 77°F, 50% R.H.):

Note: Drying times are temperature, humidity and film thickness dependant.

To Touch: 4 hours
To Recoat: 16 hours

Reduction: Mineral Spirits

Tinting: Pratt & Lambert or BAC Universal colorants

Bases Per Sheen:	S/G
Super One-Coat White	✓
Base 1	✓
Base 2	✓
Base 3	✓

Sizes: Gallons, 5 Gallons

As of 4/11/13, complies with:

OTC
ETC
SCAQMD
CARB
LADCO

S8800 is not
compliant in any
VOC area.

Product Data Sheet

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

To ensure proper adhesion, the surface to be painted must be free of dirt, dust, oil, grease, wax, rust, and any other surface contaminants. Clean surface using an appropriate cleaner to remove dust and dirt. Rinse thoroughly and allow to dry. Sand or scrape surface lightly to remove any loose paint and to smooth old surfaces. Dull glossy surfaces by using 150 grit sandpaper. Fill cracks and holes with spackling paste to smooth uneven areas. When dry, sand and clean before spot priming.

Drywall: Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks & holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete Block: All new surfaces must be cured according to the supplier's recommendations—usually at least 30 days – and have a pH between 7 and 10. Remove all form release and curing agents, efflorescence, salts, laitance, and other foreign matter. Patch cracks and holes with an appropriate filler. Rough surfaces may be filled to provide a smooth surface.

Plaster: All new surfaces must be hard and cured according to the supplier's recommendations—usually at least 30 days. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry.

Wood, Pre-Primed Fiberboard, Hardboard, Plywood: Sand any exposed wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

Aluminum & Galvanized Metal: Wash with appropriate cleaner to remove any oil, grease, or other surface contamination using a water-based cleaner-degreaser. Remove all corrosion with sandpaper, steel wool, or other abrading method.

Caulking: Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

Mildew: Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

Pro-Hide Gold® Interior Alkyd S8800 Series – Semi-Gloss

Application

Temperature (air, surface and material):
Apply at temperatures above 50°F

No reduction necessary

Airless Spray:

Pressure.....	2000 psi
Tip.....	.015" - .019"
Reduction.....	Not recommended

Conventional Spray:

Air Pressure.....	40-60 psi
Fluid Pressure.....	10-20 psi
Tip.....	704/E
Reduction.....	Up to 1 pint of mineral spirits

Brush:

Brush.....	Natural bristle
Reduction.....	Not recommended

Roller:

Cover.....	1/4"-3/4" lambs wool
Reduction.....	Not recommended

Tips to Improve Performance

- Clean the surface thoroughly
- Prepare the substrate to create a uniform surface
- Patch cracks, crevices, and through-wall openings using proper sealant or patch
- Fill voids and openings around windows and doors using proper sealant or patch
- Caulk as needed using quality latex or paintable siliconized latex caulk or sealant

Cautions

- Prevent from freezing
- For Interior use only
- Not for use on horizontal surfaces or where water will collect

Clean Up

Clean spills, spatters, and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.