

Product Data Sheet



PRATT & LAMBERT
PAINTS
Never compromise



Skylight® Waterborne Ceiling Paint

Z1251 - Soft White
Z1253 - Ultra White

Skylight® Waterborne Ceiling Paint provides a luxurious, uniform matte flat finish that softly reflects light and hides minor surface imperfections. It is formulated for easy, spatter-resistant application, dries quickly, and provides excellent hiding.

- Excellent coverage and hide
- Reflects light and hides minor imperfections
- Spatter-resistant application
- Fast dry

Recommended Uses

Recommended for use on properly prepared interior ceilings, drywall, plaster, masonry, wood, metal and previously painted surfaces

Recommended Systems

Drywall

No primer necessary OR 1 coat Pratt & Lambert® Drywall Primer
1-2 coats Skylight® Waterborne Ceiling Paint

Plaster, Masonry (cured 30+ days)

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer
1-2 coats Skylight® Waterborne Ceiling Paint

Plaster, Masonry (cured 60+ days)

No primer necessary
1-2 coats Skylight® Waterborne Ceiling Paint

Wood

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer OR
1 coat Pratt & Lambert® Multi-Surface Oil Base Primer
1-2 coats Skylight® Waterborne Ceiling Paint

Metal

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer
1-2 coats Skylight® Waterborne Ceiling Paint

Previously Painted Surfaces

No primer necessary
1-2 coats Skylight® Waterborne Ceiling Paint

Technical Data

Vehicle: Vinyl Acrylic

Finish: Flat: 0-5 units @ 85°

Flash Point: N/A

Volume Solids: 54 ± 2%

Weight Solids: 35± 2%

Weight/Gallon: 11.7 lb/gal

VOC (less exempt solvents): VOC < 50g/L – 0.42 lb/gal as per 40 CFR 59.406

Spread Rate: 400 sq. ft. per gallon

Film Thickness: **Soft** @ 4 mils wet; 1.3 mils dry
Ultra @ 4 mils wet; 1.3 mils dry

Drying Time (@ 77°F, 50% R.H.):

Note: Drying times are temperature, humidity and film thickness dependant.

To Touch: 30 minutes
To Recoat: 2 hours

Colors: Soft White, Ultra White

Tinting: Do not tint

Sizes: Gallon, 5 Gallon

As of 2/25/13, complies with:

OTC	✓
ETC	✓
SCAQMD	✓
CARB	✓
LADCO	✓

Product Data Sheet

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

To ensure proper adhesion, the surface to be painted must be free of dirt, dust, oil, grease, wax, rust, and any other surface contaminants. Clean surface using an appropriate cleaner to remove dust and dirt. Rinse thoroughly and allow to dry. Sand or scrape surface lightly to remove any loose paint and to smooth old surfaces. Dull glossy surfaces by using 150 grit sandpaper. Fill cracks and holes with spackling paste to smooth uneven areas. When dry, sand and clean before spot priming.

Drywall: Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks and holes with spackling compound and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry: Allow to cure at least 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow surface to dry 7 days and prime with Pro-Hide® Gold Exterior Acrylic Cement and Stucco Primer. No primer necessary if cured 60 days.

Plaster: Allow to cure at least 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry. No primer necessary if cured 60 days.

Wood: Sand wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

Aluminum & Galvanized Metal: Wash with appropriate cleaner to remove any oil, grease, or other surface contamination using a water-based cleaner-degreaser. Remove all corrosion with sandpaper, steel wool, or other abrading method.

Caulking: Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface

Mildew: Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.

Skylight® Waterborne Ceiling Paint Z1251-Soft White Z1253- Ultra White

Application

Temperature (air, surface and material):
Apply at temperatures above 50°F

No reduction necessary

Airless Spray:

Pressure.....	2000 psi
Tip.....	.015-.019
Reduction.....	Not recommended

Brush:

Brush.....	Nylon/polyester
Reduction.....	Not recommended

Roller:

Cover.....	3/8" - 3/4" synthetic
Reduction.....	No recommended

Tips to Improve Performance

- Clean the surface thoroughly
- Prepare the substrate to create a uniform surface
- Patch cracks, crevices, and through-wall openings using proper sealant or patch
- Fill voids and openings around windows and doors using proper sealant or patch
- Caulk as needed using quality latex or paintable siliconized latex caulk or sealant

Cautions

- **Protect from freezing**
- **For interior use only**

Clean Up

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.