

# Product Data Sheet



## Accolade® Exterior Premium Paint & Primer

- Z4400 Series – Flat
- Z4500 Series – Eggshell
- Z4900 Series – Semi-Gloss

Accolade® Exterior Premium Paint & Primer is a 100% acrylic house and trim paint designed to withstand harsh winter and summer weather extremes. This highly durable paint features exceptional adhesion and is specially designed to resist blistering, chipping, peeling and chalking, while also providing a mildew resistant coating that may be applied in temperatures as low as 35°F. It is recommended for properly prepared exterior siding, wood, masonry, metal, vinyl and previously painted surfaces. Accolade® Premium lifetime warranty.

- Our finest exterior paint
- Long lasting durability
- Exceptional adhesion
- Ultra moisture-resistant – safe from moisture after just 60 minutes\*
- Can be applied in temperatures as low as 35°F
- Superb hide
- Provides a mildew resistant coating

\*at 77°F, 50% Relative humidity. Temperature and humidity dependent.

### Recommended Uses

Recommended for properly prepared exterior siding, wood, masonry, metal, vinyl and previously painted surfaces.

### Recommended Systems

#### Vinyl, Aluminum, Galvanized Metal, Previously Painted Surfaces:

No primer necessary  
1 or 2 coats Accolade® Exterior Premium

#### Masonry (cured 7+ days):

1 coat Pro-Hide® Gold Exterior Cement & Stucco Primer  
1 or 2 coats Accolade® Exterior Premium

#### Masonry (cured 30+ days):

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer  
1 or 2 coats Accolade® Exterior Premium

#### Concrete Block:

1 coat Pro-Hide® Silver Latex Block Filler  
1 or 2 coats Accolade® Exterior Premium

#### Wood, Hardboard:

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer OR  
Pratt & Lambert® Multi-Surface Oil Base Primer  
1 or 2 coats Accolade® Exterior Premium

#### Cedar, Redwood:

Pratt & Lambert® Multi-Surface Oil Base Primer  
1 or 2 coats Accolade® Exterior Premium

#### Steel:

1 coat Pratt & Lambert® Multi-Purpose Waterborne Primer  
1 or 2 coats Accolade® Exterior Premium

12/16

## Technical Data

**Vehicle:** 100% Acrylic

**Finish:** **Flat** 0-12 units @ 85°  
**Eggshell** 0-15 units @ 65° / 10-20 units @ 60°  
**Semi-Gloss** 40-50 units @ 60°

**Flash Point:** 499°F

**Volume Solids\*:** **Flat** 42 ± 2%  
**Eggshell** 41 ± 2%  
**Semi-Gloss** 42 ± 2%

**Weight Solids\*:** **Flat** 60 ± 2%  
**Eggshell** 55 ± 2%  
**Semi-Gloss** 54 ± 2%

**Weight/Gallon\*:** **Flat** 11.91 lbs.  
**Eggshell** 10.92 lbs.  
**Semi-Gloss** 10.57 lbs.

**VOC:** VOC < 50 g/L – 0.21 lb/gal as per 40 CFR 59.406

**Spread Rate:** 400 sq. ft. per gallon

**Film Thickness:** **Flat** @ 4 mils wet; 1.3 mils dry  
**Satin** @ 4 mils wet; 1.3 mils dry  
**Semi-Gloss** @ 4 mils wet; 1.3 mils dry

\* Product data calculated on Bright White / Base

**Drying Time (@ 77°F, 50% R.H.):**

**Note: Drying times are temperature, humidity, and film thickness dependent.**

**To Touch:** 1 hour  
**To Recoat:** 2-4 hours

**Reduction:** Thinning not required

**Tinting:** Universal colorants

Bases Per Finish:	Fl	Eq	S-G
Bright White / Base	✓	✓	✓
Deep Base	✓	✓	✓
Neutral Base	✓	✓	✓

**Sizes:** Quart, Gallon, 5 Gallon

	As of 1/17, complies with:		
	Fl	Sa	S-G
OTC	✓	✓	✓
EC	✓	✓	✓
SCAQMD	✓	✓	✓
CARB	✓	✓	✓
LADCO	✓	✓	✓

# Product Data Sheet

## Surface Preparation

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

To ensure proper adhesion, the surface to be painted must be free of dirt, dust, oil, grease, wax, rust, and any other surface contaminants. Clean surface using an appropriate cleaner. Rinse thoroughly and allow to dry. Sand or scrape surface to remove any loose paint and to smooth old surfaces. Dull glossy surfaces by using 150 grit sandpaper. Fill cracks and holes with spackling paste to smooth uneven areas. When dry, sand and remove sanding dust.

**Vinyl and Aluminum Siding:** Clean the surface thoroughly with warm, soapy water. Rinse thoroughly.

**Masonry, Concrete, Cement, Block, Brick:** All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Pro-Hide® Gold Exterior Acrylic Cement and Stucco Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.

**Stucco:** Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Pro-Hide® Gold Exterior Acrylic Cement and Stucco Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

**Wood, Pre-Primed Fiberboard, Hardboard, Cedar, Redwood, Plywood:** Sand wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

**Aluminum and Galvanized Metal:** Wash with appropriate cleaner to remove any oil, grease, or other surface contamination. Remove all corrosion with sandpaper, steel wool, or other abrading method.

**Caulking:** Fill gaps between windows, doors, trim, and other through-wall openings with latex or siliconized latex caulk after priming the surface.

**Mildew:** Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

## Accolade® Exterior Premium Paint & Primer Z4400 Series – Flat Z4500 Series – Eggshell Z4900 Series – Semi-Gloss

## Application

**Temperature (air, surface and material):**  
Apply at temperatures above 35°F

More than one coat of paint may be necessary for new and uncoated surfaces, dramatic color changes, or when using dark/vibrant colors for optimal appearance and hide.

### Airless Spray:

Pressure.....	2000 psi
Tip.....	.015" - .019"
Reduction.....	Not necessary

### Brush:

Brush.....	Nylon/polyester
Reduction.....	Not recommended

### Roller:

Cover.....	3/8" - 3/4" synthetic
Reduction.....	Not recommended

## Tips to Improve Performance

- Clean the surface thoroughly
- Prepare the substrate to create a uniform surface
- Patch cracks, crevices, and through-wall openings using proper sealant or patch
- Fill voids and openings around windows and doors using proper sealant or patch
- Caulk as needed using quality latex or paintable siliconized latex caulk or sealant

## Cautions

- **Protect from freezing**
- **For exterior use only**
- **Non-photochemically reactive**

## Clean Up

Clean spills and splatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Pratt & Lambert Paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Pratt & Lambert dealer or representative to obtain the most recent Product Data Sheet.