

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation  
Apr 18, 2026

08 00 [1805]

**PRODUCT NUMBER**

TZ267000D

**PRODUCT NAME**

Pigmented White Polyurethane Topcoat, 70 Sheen

**MANUFACTURER'S NAME**

SAYERLACK, A BRAND OF SHERWIN-WILLIAMS  
1 Sherwin Way  
Cleveland, OH 44113

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

**Hazard Category (for SARA 311.312)**

TZ267000D = | Acute | Chronic | Fire |

**Product Weight**

11.17 lb/gal

**Specific Gravity**

1.34

**FLASH POINT**

73 °F PMCC

**Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Y	4	6
Xylene 1330-20-7	N	Y	Y	Y	22	34
n-Butyl Acetate 123-86-4	N	Y	N	N	3	4
Isobutyl Acetate 110-19-0	N	Y	N	N	4	6

**Regulated Compounds**

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Y	N	0.0000005	
Lead (as Pb)	N	N	Y	N	0.0000003	

### Volatile Organic Compounds - U.S. EPA / Canada

	TZ267000D	
	LB/Gal	g/L
Coating Density	11.17	1338
	By wt	By vol
Total Volatiles	33.4%	50.8%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	33.4%	50.8%
Percent Non-Volatile	66.6%	49.2%
VOC Content	LB/Gal	g/L
Total	3.73	447
Less exempt solvents	3.73	447
Of solids	7.58	909
Of solids	0.50 lb/lb	0.50 kg/kg
	By wt	
By wt LVP-VOC	33.4%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.87**

### Volatile Organic Compounds - California

	TZ267000D	
	LB/Gal	g/L
Coating Density	11.17	1338
	By wt	By vol
Total Volatiles	33.4%	50.8%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	33.4%	50.8%
Percent Non-Volatile	66.6%	49.2%
VOC Content	LB/Gal	g/L
Total	3.73	447
Less exempt solvents	3.73	447
Of solids	7.58	909
Of solids	0.50 lb/lb	0.50 kg/kg
	By wt	
By wt LVP-VOC	33.4%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.88**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	TZ267000D	
	LB/Gal	g/L
Coating Density	11.17	1338
	By wt	By vol
Total Volatiles	33.4%	50.8%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	33.4%	50.8%
Percent Non-Volatile	66.6%	49.2%
VOC Content	LB/Gal	g/L
Total	3.73	447
Less exempt solvents	3.73	447
Of solids	7.58	909
Of solids	0.50 lb/lb	0.50 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	TZ267000D	
	By wt	By vol
Total Volatiles	33.5%	50.8%
VOC Content	LB/Gal	g/L
Total	3.73	448

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	TZ267000D	
	By wt	By vol
Total Volatiles	33.4%	50.8%
VOC Content	LB/Gal	g/L
Total	3.73	447

**Volatile Organic Compounds - Mexico**

	TZ267000D	
	LB/Gal	g/L
Coating Density	11.17	1338
	By wt	By vol
Total Volatiles	33.4%	50.8%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	33.4%	50.8%
Percent Non-Volatile	66.6%	49.2%
VOC Content	LB/Gal	g/L
Total	3.73	447
Less exempt solvents	3.73	447
Of solids	7.59	909
Of solids	0.50 lb/lb	0.50 kg/kg

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	TZ267000D	
	LB/Gal	kg/L
Volatile HAPS	2.95	0.353
Of solids	5.99	0.718
Of solids	0.39 lb/lb	0.39 kg/kg

### Air Quality Data

#### Density of Organic Solvent Blend

7.36 lb/gal

#### Photochemically Reactive

Yes

### Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.