ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

08 00 [1805]

Jun 29, 2025

PRODUCT NUMBER

TZ267000D

PRODUCT NAME

Pigmented White Polyurethane Topcoat, 70 Sheen

MANUFACTURER'S NAME

SAYERLACK, A BRAND OF SHERWIN-WILLIAMS 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

TZ267000D = | Acute | Chronic | Fire |

 Product Weight
 Specific Gravity
 FLASH POINT

 11.19 lb/gal
 1.35
 73 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Toluene 108-88-3	N	Υ	Υ	Υ	1	2
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	4	6
Xylene 1330-20-7	N	Υ	Υ	Υ	22	33
n-Butyl Acetate 123-86-4	N	Υ	N	N	3	4
Isobutyl Acetate 110-19-0	N	Υ	N	N	3	5

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Υ	N	0.0000005	
Lead (as Pb)	N	N	Υ	N	0.000003	

Volatile Organic Compounds - U.S. EPA / Canada

	TZ267000D		
	LB/Gal	g/L	
Coating Density	11.19	1340	
	By wt	By vol	
Total Volatiles	32.8%	49.8%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	32.8%	49.8%	
Percent Non-Volatile	67.2%	50.2%	
VOC Content	LB/Gal	g/L	
Total	3.66	439	
Less exempt solvents	3.66	439	
Of solids	7.30	875	
Of solids	0.48 lb/lb	0.48 kg/kg	
	By wt		
By wt LVP-VOC	32.8%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.87

Volatile Organic Compounds - California

	TZ267000D		
	LB/Gal	g/L	
Coating Density	11.19	1340	
	By wt	By vol	
Total Volatiles	32.8%	49.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	32.8%	49.8%	
Percent Non-Volatile	67.2%	50.2%	
VOC Content	LB/Gal	g/L	
Total	3.66	439	
Less exempt solvents	3.66	439	
Of solids	7.30	875	
Of solids	0.48 lb/lb	0.48 kg/kg	
	By wt		
By wt LVP-VOC	32.8%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.87

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	TZ267000D		
	LB/Gal	g/L	
Coating Density	11.19	1340	
	By wt	By vol	
Total Volatiles	32.8%	49.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	32.8%	49.8%	
Percent Non-Volatile	67.2%	50.2%	
VOC Content	LB/Gal	g/L	
Total	3.66	439	
Less exempt solvents	3.66	439	
Of solids	7.30	875	
Of solids	0.48 lb/lb	0.48 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	TZ267000D		
	By wt	By vol	
Total Volatiles	32.8%	49.8%	
VOC Content	LB/Gal	g/L	
Total	3.66	439	

Volatile Organic Compounds - EU Directive 2010/75/EU

	TZ267000D	
	By wt	By vol
Total Volatiles	32.8%	49.8%
VOC Content	LB/Gal	g/L
Total	3.66	439

Volatile Organic Compounds - Mexico

	TZ267000D		
	LB/Gal	g/L	
Coating Density	11.19	1340	
	By wt	By vol	
Total Volatiles	32.8%	49.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	32.8%	49.8%	
Percent Non-Volatile	67.2%	50.2%	
VOC Content	LB/Gal	g/L	
Total	3.66	439	
Less exempt solvents	3.66	439	
Of solids	7.30	875	
Of solids	0.48 lb/lb	0.48 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	TZ267000D		
	LB/Gal	kg/L	
Volatile HAPS	3.01	0.361	
Of solids	6.01	0.720	
Of solids	0.40 lb/lb	0.40 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.36 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.