ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jun 28, 2025

16 00 [1795]

PRODUCT NUMBER

TZ9935NND

PRODUCT NAME

Solvent-Based Polyurethane Neutral Tint-Base (NN), 35 Sheen

MANUFACTURER'S NAME

SAYERLACK, A BRAND OF SHERWIN-WILLIAMS 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

TZ9935NND = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT8.29 lb/gal1.0059 °F PMCC

Volatile Ingredients

- Olamo inglocation to						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene	N	Υ	Υ	Υ	5	5
100-41-4						
Xylene 1330-20-7	N	Y	Υ	Y	25	29
Diacetone Alcohol 123-42-2	N	N	N	N	2	2
n-Butyl Acetate 123-86-4	N	Υ	N	N	2	2
Isobutyl Acetate 110-19-0	N	Υ	N	N	19	22

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lead (as Pb)	N	N	Υ	N	0.00003	

Volatile Organic Compounds - U.S. EPA / Canada

	TZ9935NND		
	LB/Gal	g/L	
Coating Density	8.29	993	
	By wt	By vol	
Total Volatiles	53.6%	61.4%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	53.6%	61.4%	
Percent Non-Volatile	46.4%	38.6%	
VOC Content	LB/Gal	g/L	
Total	4.44	532	
Less exempt solvents	4.44	532	
Of solids	11.50	1378	
Of solids	1.15 lb/lb	1.15 kg/kg	
	By wt		
By wt LVP-VOC	53.6%	· · · · · · · · · · · · · · · · · · ·	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 2.23

Volatile Organic Compounds - California

	TZ9935NND		
	LB/Gal	g/L	
Coating Density	8.29	993	
	By wt	By vol	
Total Volatiles	53.6%	61.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	53.6%	61.4%	
Percent Non-Volatile	46.4%	38.6%	
VOC Content	LB/Gal	g/L	
Total	4.44	532	
Less exempt solvents	4.44	532	
Of solids	11.50	1378	
Of solids	1.15 lb/lb	1.15 kg/kg	
	By wt		
By wt LVP-VOC	53.6%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 2.23

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	TZ9935NND		
	LB/Gal	g/L	
Coating Density	8.29	993	
	By wt	By vol	
Total Volatiles	53.6%	61.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	53.6%	61.4%	
Percent Non-Volatile	46.4%	38.6%	
VOC Content	LB/Gal	g/L	
Total	4.44	532	
Less exempt solvents	4.44	532	
Of solids	11.50	1378	
Of solids	1.15 lb/lb	1.15 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	TZ9935NND	
	By wt	By vol
Total Volatiles	53.6%	61.4%
VOC Content	LB/Gal	g/L
Total	4.44	532

Volatile Organic Compounds - EU Directive 2010/75/EU

	TZ993	35NND
	By wt	By vol
Total Volatiles	53.6%	61.4%
VOC Content	LB/Gal	g/L
Total	4.44	532

Volatile Organic Compounds - Mexico

	TZ9935NND		
	LB/Gal	g/L	
Coating Density	8.29	993	
	By wt	By vol	
Total Volatiles	53.6%	61.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	53.6%	61.4%	
Percent Non-Volatile	46.4%	38.6%	
VOC Content	LB/Gal	g/L	
Total	4.44	532	
Less exempt solvents	4.44	532	
Of solids	11.50	1378	
Of solids	1.15 lb/lb	1.15 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	TZ9935NND		
	LB/Gal	kg/L	
Volatile HAPS	2.48	0.297	
Of solids	6.43	0.771	
Of solids	0.64 lb/lb	0.64 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.24 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.