ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

25 00 [1795]

PRODUCT NUMBER

TZ9960BBD

PRODUCT NAME

Solvent-Based Polyurethane White Tint-Base (BB), 60 Sheen

MANUFACTURER'S NAME

SAYERLACK, A BRAND OF SHERWIN-WILLIAMS

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

TZ9960BBD = | Acute | Chronic | Fire |

Product Weight 10.79 lb/gal	Specific 1.30	Gravity			H POINT °F PMCC	
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Y	3	4
Xylene 1330-20-7	N	Y	Y	Y	16	23
Methyl Ethyl Ketone 78-93-3	N	Y	N	N	1	2
Isobutyl Acetate 110-19-0	N	Y	N	Ν	13	19
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	Ν	2	2

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lead (as Pb)	Ν	Ν	Y	Ν	0.00001	

Date of Preparation Jun 28, 2025

Volatile Organic Compounds - U.S. EPA / Canada

	TZ9960BBD		
	LB/Gal	g/L	
Coating Density	10.79	1292	
	By wt	By vol	
Total Volatiles	36.1%	53.7%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	36.1%	53.7%	
Percent Non-Volatile	63.9%	46.3%	
VOC Content	LB/Gal	g/L	
Total	3.88	466	
Less exempt solvents	3.88	466	
Of solids	8.39	1006	
Of solids	0.56 lb/lb	0.56 kg/kg	
	By wt		
By wt LVP-VOC	36.1%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.43

Volatile Organic Compounds - California

	TZ9960BBD		
	LB/Gal	g/L	
Coating Density	10.79	1292	
	By wt	By vol	
Total Volatiles	36.1%	53.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	36.1%	53.7%	
Percent Non-Volatile	63.9%	46.3%	
VOC Content	LB/Gal	g/L	
Total	3.88	466	
Less exempt solvents	3.88	466	
Of solids	8.39	1006	
Of solids	0.56 lb/lb	0.56 kg/kg	
	By wt		
By wt LVP-VOC	36.1%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.43

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	TZ9960BBD		
	LB/Gal	g/L	
Coating Density	10.79	1292	
	By wt	By vol	
Total Volatiles	36.1%	53.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	36.1%	53.7%	
Percent Non-Volatile	63.9%	46.3%	
VOC Content	LB/Gal	g/L	
Total	3.88	466	
Less exempt solvents	3.88	466	
Of solids	8.39	1006	
Of solids	0.56 lb/lb	0.56 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	TZ9960BBD		
	By wt	By vol	
Total Volatiles	36.2%	53.9%	
VOC Content	LB/Gal	g/L	
Total	3.90	468	

Volatile Organic Compounds - EU Directive 2010/75/EU

	TZ9960BBD		
	By wt	By vol	
Total Volatiles	36.1%	53.7%	
VOC Content	LB/Gal	g/L	
Total	3.88	466	

Volatile Organic Compounds - Mexico

	TZ9960BBD		
	LB/Gal	g/L	
Coating Density	10.79	1292	
	By wt	By vol	
Total Volatiles	36.1%	53.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	36.1%	53.7%	
Percent Non-Volatile	63.9%	46.3%	
VOC Content	LB/Gal	g/L	
Total	3.88	466	
Less exempt solvents	3.88	466	
Of solids	8.39	1006	
Of solids	0.56 lb/lb	0.56 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	TZ9960BBD		
	LB/Gal	kg/L	
Volatile HAPS	1.98	0.237	
Of solids	4.28	0.513	
Of solids	0.28 lb/lb	0.28 kg/kg	

Air Quality Data

Density of Organic Solvent Blend 7.25 lb/gal Photochemically Reactive Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.