

# SAFETY DATA SHEET

According to the Canadian Hazardous Products Regulations (HPR)  
TZ7015A00

## Section 1. Identification

**Product name** : Clear Acrylic Polyurethane Topcoat  
15 Sheen

**Product code** : TZ7015A00

**Other means of identification** : Not available.

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Paint or paint related material.

**Manufacturer** : SAYERLACK, a brand of Sherwin-Williams  
101 W. Prospect Avenue  
Cleveland, OH 44115

**National contact** : Sherwin-Williams Canada Inc.  
180 Brunel Road  
Mississauga, Ontario L4Z 1T5 Canada

**Emergency telephone number of the company** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

**Product Information Telephone Number** : US / Canada: 1-800-524-5979  
Mexico: Not Available

**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 2.7% (dermal), 10.3% (inhalation)

### GHS label elements

**Hazard pictograms** :



**Signal word** : Danger

**Date of issue/Date of revision** : 5/2/2026  
TZ7015A00 Clear Acrylic Polyurethane Topcoat  
15 Sheen

**Date of previous issue** : 10/3/2025

**Version** : 21  
SHW-85-NA-GHS-CA

1/26

## Section 2. Hazards identification

**Hazard statements** : Highly flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

**Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

**Hazards not otherwise classified** : None known.

**Hazards identified when used** : No known significant effects or critical hazards.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

**Other means of identification** : Not available.

**CAS number/other identifiers**

## Section 3. Composition/information on ingredients

| Ingredient name       | % by weight | Identifiers |
|-----------------------|-------------|-------------|
| Xylene, mixed isomers | 19.92       | 1330-20-7   |
| n-Butyl Acetate       | 17.55       | 123-86-4    |
| Methyl Ethyl Ketone   | 11.49       | 78-93-3     |
| Isobutyl Acetate      | 7.6         | 110-19-0    |
| Cyclohexanone         | 5           | 108-94-1    |
| Ethylbenzene          | 3.54        | 100-41-4    |
| 2-Methyl-1-propanol   | 3.03        | 78-83-1     |
| Ethyl Acetate         | 2.7         | 141-78-6    |
| Methyl Methacrylate   | 0.36        | 80-62-6     |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

## Section 4. First aid measures

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

## Section 5. Fire-fighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Remark** : Flammable liquid.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : **This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).**
- Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Section 7. Handling and storage

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits (OSHA United States)

| Ingredient name       | CAS #     | Exposure limits  |
|-----------------------|-----------|--|
| Xylene, mixed isomers | 1330-20-7 | <b>ACGIH TLV (United States, 1/2025) [p-xylene and mixtures containing p-xylene]</b><br>A4. Ototoxicant.<br>TWA 8 hours: 20 ppm.   |
| n-Butyl Acetate       | 123-86-4  | <b>OSHA PEL (United States, 5/2018) [Xylenes]</b><br>TWA 8 hours: 100 ppm.<br>TWA 8 hours: 435 mg/m <sup>3</sup> .<br><b>ACGIH TLV (United States, 1/2025) [Butyl acetates]</b><br>STEL 15 minutes: 150 ppm.<br>TWA 8 hours: 50 ppm.   |
| Methyl Ethyl Ketone   | 78-93-3   | <b>NIOSH REL (United States, 10/2020)</b><br>TWA 10 hours: 150 ppm.<br>TWA 10 hours: 710 mg/m <sup>3</sup> .<br>STEL 15 minutes: 200 ppm.<br>STEL 15 minutes: 950 mg/m <sup>3</sup> .<br><b>OSHA PEL (United States, 5/2018)</b><br>TWA 8 hours: 150 ppm.<br>TWA 8 hours: 710 mg/m <sup>3</sup> .  |
| Isobutyl Acetate      | 110-19-0  | <b>ACGIH TLV (United States, 1/2025)</b><br>Absorbed through skin.<br>TWA 8 hours: 75 ppm.<br>STEL 15 minutes: 150 ppm.<br><b>NIOSH REL (United States, 10/2020)</b><br>TWA 10 hours: 200 ppm.<br>TWA 10 hours: 590 mg/m <sup>3</sup> .<br>STEL 15 minutes: 300 ppm.<br>STEL 15 minutes: 885 mg/m <sup>3</sup> .<br><b>OSHA PEL (United States, 5/2018)</b><br>TWA 8 hours: 200 ppm.<br>TWA 8 hours: 590 mg/m <sup>3</sup> .<br><b>ACGIH TLV (United States, 1/2025) [Butyl acetates]</b><br>STEL 15 minutes: 150 ppm.<br>TWA 8 hours: 50 ppm. |

## Section 8. Exposure controls/personal protection

|                     |          |   |
|---------------------|----------|---|
| Cyclohexanone       | 108-94-1 | <p><b>NIOSH REL (United States, 10/2020)</b><br/>TWA 10 hours: 150 ppm.<br/>TWA 10 hours: 700 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 150 ppm.<br/>TWA 8 hours: 700 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 1/2025) A3.</b><br/>Absorbed through skin.<br/>TWA 8 hours: 20 ppm.<br/>STEL 15 minutes: 50 ppm.</p> <p><b>NIOSH REL (United States, 10/2020)</b><br/>Absorbed through skin.<br/>TWA 10 hours: 25 ppm.<br/>TWA 10 hours: 100 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 50 ppm.<br/>TWA 8 hours: 200 mg/m<sup>3</sup>.</p> |
| Ethylbenzene        | 100-41-4 | <p><b>ACGIH TLV (United States, 1/2025) A3.</b><br/>Ototoxicant.<br/>TWA 8 hours: 20 ppm.</p> <p><b>NIOSH REL (United States, 10/2020)</b><br/>TWA 10 hours: 100 ppm.<br/>TWA 10 hours: 435 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 125 ppm.<br/>STEL 15 minutes: 545 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 100 ppm.<br/>TWA 8 hours: 435 mg/m<sup>3</sup>.</p>  |
| 2-Methyl-1-propanol | 78-83-1  | <p><b>ACGIH TLV (United States, 1/2025)</b><br/>TWA 8 hours: 50 ppm.<br/>TWA 8 hours: 152 mg/m<sup>3</sup>.</p> <p><b>NIOSH REL (United States, 10/2020)</b><br/>TWA 10 hours: 50 ppm.<br/>TWA 10 hours: 150 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 100 ppm.<br/>TWA 8 hours: 300 mg/m<sup>3</sup>.</p>  |
| Ethyl Acetate       | 141-78-6 | <p><b>ACGIH TLV (United States, 1/2025)</b><br/>TWA 8 hours: 400 ppm.<br/>TWA 8 hours: 1440 mg/m<sup>3</sup>.</p> <p><b>NIOSH REL (United States, 10/2020)</b><br/>TWA 10 hours: 400 ppm.<br/>TWA 10 hours: 1400 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 400 ppm.<br/>TWA 8 hours: 1400 mg/m<sup>3</sup>.</p>   |
| Methyl Methacrylate | 80-62-6  | <p><b>ACGIH TLV (United States, 1/2025) A4.</b><br/>Skin sensitizer.<br/>TWA 8 hours: 50 ppm.<br/>STEL 15 minutes: 100 ppm.</p> <p><b>NIOSH REL (United States, 10/2020)</b><br/>TWA 10 hours: 100 ppm.<br/>TWA 10 hours: 410 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL (United States, 5/2018)</b><br/>TWA 8 hours: 100 ppm.<br/>TWA 8 hours: 410 mg/m<sup>3</sup>.</p>   |

# Section 8. Exposure controls/personal protection

## Occupational exposure limits (Canada)

| Ingredient name     | CAS #     | Exposure limits  |
|---------------------|-----------|--|
| Xylene              | 1330-20-7 | <p><b>CA Saskatchewan Provincial (Canada, 4/2021) [Xylene]</b><br/>                     STEL 15 minutes: 150 ppm.<br/>                     TWA 8 hours: 100 ppm.</p> <p><b>CA British Columbia Provincial (Canada, 6/2025) [xylene, all isomers]</b><br/>                     TWA 8 hours: 20 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)]</b><br/>                     STEL 15 minutes: 150 ppm.<br/>                     TWA 8 hours: 100 ppm.</p> <p><b>CA Quebec Provincial (Canada, 2/2024) [Xylene]</b><br/>                     TWAEV 8 hours: 100 ppm.<br/>                     TWAEV 8 hours: 434 mg/m<sup>3</sup>.<br/>                     STEV 15 minutes: 150 ppm.<br/>                     STEV 15 minutes: 651 mg/m<sup>3</sup>.</p> <p><b>CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene]</b><br/>                     OEL 8 hours: 100 ppm.<br/>                     OEL 15 minutes: 651 mg/m<sup>3</sup>.<br/>                     OEL 15 minutes: 150 ppm.<br/>                     OEL 8 hours: 434 mg/m<sup>3</sup>.</p> |
| n-butyl acetate     | 123-86-4  | <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b><br/>                     STEL 15 minutes: 200 ppm.<br/>                     TWA 8 hours: 150 ppm.</p> <p><b>CA British Columbia Provincial (Canada, 6/2025) [butyl acetate, all isomers]</b><br/>                     STEL 15 minutes: 150 ppm.<br/>                     TWA 8 hours: 50 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019) [butyl acetates, all isomers]</b><br/>                     STEL 15 minutes: 150 ppm.<br/>                     TWA 8 hours: 50 ppm.</p> <p><b>CA Quebec Provincial (Canada, 2/2024) [butyl acetates]</b><br/>                     STEV 15 minutes: 150 ppm.<br/>                     TWAEV 8 hours: 50 ppm.</p> <p><b>CA Alberta Provincial (Canada, 3/2023)</b><br/>                     OEL 15 minutes: 200 ppm.<br/>                     OEL 15 minutes: 950 mg/m<sup>3</sup>.<br/>                     OEL 8 hours: 150 ppm.<br/>                     OEL 8 hours: 713 mg/m<sup>3</sup>.</p>   |
| Methyl ethyl ketone | 78-93-3   | <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b><br/>                     STEL 15 minutes: 300 ppm.<br/>                     TWA 8 hours: 200 ppm.</p> <p><b>CA British Columbia Provincial (Canada, 6/2025) Repr. Absorbed through skin.</b><br/>                     TWA 8 hours: 50 ppm.<br/>                     STEL 15 minutes: 100 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019)</b><br/>                     TWA 8 hours: 200 ppm.</p>  |

## Section 8. Exposure controls/personal protection

|                  |          |  |
|------------------|----------|--|
| Isobutyl acetate | 110-19-0 | <p>STEL 15 minutes: 300 ppm.<br/> <b>CA Quebec Provincial (Canada, 2/2024)</b><br/>           TWAEV 8 hours: 50 ppm.<br/>           TWAEV 8 hours: 150 mg/m<sup>3</sup>.<br/>           STEV 15 minutes: 100 ppm.<br/>           STEV 15 minutes: 300 mg/m<sup>3</sup>.<br/> <b>CA Alberta Provincial (Canada, 3/2023)</b><br/>           OEL 15 minutes: 300 ppm.<br/>           OEL 8 hours: 200 ppm.<br/>           OEL 8 hours: 590 mg/m<sup>3</sup>.<br/>           OEL 15 minutes: 885 mg/m<sup>3</sup>.</p> <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b><br/>           STEL 15 minutes: 188 ppm.<br/>           TWA 8 hours: 150 ppm.<br/> <b>CA British Columbia Provincial (Canada, 6/2025) [butyl acetate, all isomers]</b><br/>           STEL 15 minutes: 150 ppm.<br/>           TWA 8 hours: 50 ppm.<br/> <b>CA Ontario Provincial (Canada, 6/2019) [butyl acetates, all isomers]</b><br/>           STEL 15 minutes: 150 ppm.<br/>           TWA 8 hours: 50 ppm.<br/> <b>CA Quebec Provincial (Canada, 2/2024) [butyl acetates]</b><br/>           STEV 15 minutes: 150 ppm.<br/>           TWAEV 8 hours: 50 ppm.<br/> <b>CA Alberta Provincial (Canada, 3/2023)</b><br/>           OEL 8 hours: 150 ppm.<br/>           OEL 8 hours: 713 mg/m<sup>3</sup>.</p> |
| Cyclohexanone    | 108-94-1 | <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b> Absorbed through skin.<br/>           STEL 15 minutes: 50 ppm.<br/>           TWA 8 hours: 20 ppm.<br/> <b>CA British Columbia Provincial (Canada, 6/2025)</b> Absorbed through skin.<br/>           TWA 8 hours: 20 ppm.<br/>           STEL 15 minutes: 50 ppm.<br/> <b>CA Ontario Provincial (Canada, 6/2019)</b><br/>           Absorbed through skin.<br/>           TWA 8 hours: 20 ppm.<br/>           STEL 15 minutes: 50 ppm.<br/> <b>CA Quebec Provincial (Canada, 2/2024)</b><br/>           C3. Absorbed through skin.<br/>           TWAEV 8 hours: 20 ppm.<br/>           STEV 15 minutes: 50 ppm.<br/> <b>CA Alberta Provincial (Canada, 3/2023)</b><br/>           Absorbed through skin.<br/>           OEL 8 hours: 20 ppm.<br/>           OEL 8 hours: 80 mg/m<sup>3</sup>.<br/>           OEL 15 minutes: 200 mg/m<sup>3</sup>.<br/>           OEL 15 minutes: 50 ppm.</p>   |
| Ethylbenzene     | 100-41-4 | <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b><br/>           STEL 15 minutes: 125 ppm.<br/>           TWA 8 hours: 100 ppm.</p>  |

## Section 8. Exposure controls/personal protection

|                     |         |   |
|---------------------|---------|---|
| Isobutyl alcohol    | 78-83-1 | <p><b>CA British Columbia Provincial (Canada, 6/2025)</b> Carc 2B.<br/>TWA 8 hours: 20 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019)</b><br/>TWA 8 hours: 20 ppm.</p> <p><b>CA Quebec Provincial (Canada, 2/2024)</b> C3.<br/>TWAEV 8 hours: 20 ppm.</p> <p><b>CA Alberta Provincial (Canada, 3/2023)</b><br/>OEL 8 hours: 100 ppm.<br/>OEL 8 hours: 434 mg/m<sup>3</sup>.<br/>OEL 15 minutes: 543 mg/m<sup>3</sup>.<br/>OEL 15 minutes: 125 ppm.</p> <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b><br/>STEL 15 minutes: 60 ppm.<br/>TWA 8 hours: 50 ppm.</p> <p><b>CA British Columbia Provincial (Canada, 6/2025)</b><br/>TWA 8 hours: 50 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019)</b><br/>TWA 8 hours: 50 ppm.</p> <p><b>CA Quebec Provincial (Canada, 2/2024)</b><br/>TWAEV 8 hours: 50 ppm.<br/>TWAEV 8 hours: 152 mg/m<sup>3</sup>.</p> <p><b>CA Alberta Provincial (Canada, 3/2023)</b><br/>OEL 8 hours: 50 ppm.<br/>OEL 8 hours: 152 mg/m<sup>3</sup>.</p> |
| methyl methacrylate | 80-62-6 | <p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b> Sensitizer.<br/>STEL 15 minutes: 100 ppm.<br/>TWA 8 hours: 50 ppm.</p> <p><b>CA British Columbia Provincial (Canada, 6/2025)</b> Skin sensitizer.<br/>TWA 8 hours: 50 ppm.<br/>STEL 15 minutes: 100 ppm.</p> <p><b>CA Ontario Provincial (Canada, 6/2019)</b><br/>TWA 8 hours: 50 ppm.<br/>STEL 15 minutes: 100 ppm.</p> <p><b>CA Quebec Provincial (Canada, 2/2024)</b> Skin sensitizer.<br/>TWAEV 8 hours: 50 ppm.<br/>STEV 15 minutes: 100 ppm.</p> <p><b>CA Alberta Provincial (Canada, 3/2023)</b><br/>OEL 8 hours: 205 mg/m<sup>3</sup>.<br/>OEL 8 hours: 50 ppm.<br/>OEL 15 minutes: 410 mg/m<sup>3</sup>.<br/>OEL 15 minutes: 100 ppm.</p>  |

[Occupational exposure limits \(Mexico\)](#)

## Section 8. Exposure controls/personal protection

| Ingredient name       | CAS #     | Exposure limits   |
|-----------------------|-----------|---|
| Xylene, mixed isomers | 1330-20-7 | <b>NOM-010-STPS-2014 (Mexico, 4/2016) [Xileno, mezcla] A4.</b><br>STEL 15 minutes: 150 ppm.<br>TWA 8 hours: 100 ppm.        |
| n-Butyl Acetate       | 123-86-4  | <b>NOM-010-STPS-2014 (Mexico, 4/2016)</b><br>TWA 8 hours: 150 ppm.<br>STEL 15 minutes: 200 ppm.                             |
| Methyl Ethyl Ketone   | 78-93-3   | <b>NOM-010-STPS-2014 (Mexico, 4/2016)</b><br>TWA 8 hours: 200 ppm.<br>STEL 15 minutes: 300 ppm.                             |
| Isobutyl Acetate      | 110-19-0  | <b>NOM-010-STPS-2014 (Mexico, 4/2016)</b><br>TWA 8 hours: 150 ppm.  |
| Cyclohexanone         | 108-94-1  | <b>NOM-010-STPS-2014 (Mexico, 4/2016) A3.</b><br>Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>STEL 15 minutes: 50 ppm. |
| Ethylbenzene          | 100-41-4  | <b>NOM-010-STPS-2014 (Mexico, 4/2016) A3.</b><br>TWA 8 hours: 20 ppm.   |
| 2-Methyl-1-propanol   | 78-83-1   | <b>NOM-010-STPS-2014 (Mexico, 4/2016)</b><br>TWA 8 hours: 50 ppm.   |
| Ethyl Acetate         | 141-78-6  | <b>NOM-010-STPS-2014 (Mexico, 4/2016)</b><br>TWA 8 hours: 400 ppm.  |

### Biological exposure indices (United States)

| Ingredient name       | Exposure indices  |
|-----------------------|---|
| Xylene, mixed isomers | <b>ACGIH BEI (United States, 1/2025) [xylenes (technical or commercial grades)]</b><br>BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.   |
| Methyl Ethyl Ketone   | <b>ACGIH BEI (United States, 1/2025)</b><br>BEI: 2 mg/l, methyl ethyl ketone [in urine].<br>Sampling time: end of shift.  |
| Cyclohexanone         | <b>ACGIH BEI (United States, 1/2025)</b><br>BEI: 80 mg/l [Semi-quantitative: The determinant is an indicator of exposure to the chemical, but the quantitative interpretation of the measurement is ambiguous. These determinants should be used as a screening test if a quantitative test is not practical or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], 1,2-cyclohexanediol [in urine].<br>Sampling time: end of shift at end of workweek.<br>BEI: 8 mg/l [Semi-quantitative: The determinant is an indicator of exposure to the chemical, but the quantitative interpretation of the measurement is ambiguous. These determinants should be used as a screening test if a quantitative test is not practical or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], cyclohexanol [in urine].<br>Sampling time: end of shift. |

## Section 8. Exposure controls/personal protection

|              |   |
|--------------|---|
| Ethylbenzene | <b>ACGIH BEI (United States, 1/2025)</b><br>BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine].<br>Sampling time: end of shift. |
|--------------|---|

**Biological exposure indices (Canada)**

No exposure indices known.

**Biological exposure indices (Mexico)**

| <b>Ingredient name</b> | <b>Exposure indices</b>   |
|------------------------|---|
| Xylene, mixed isomers  | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) [xilenos (grado técnico o comercial)]</b><br>BEI: 1.5 g/g creatinine, methyl hippuric acids [in urine]. Sampling time: at the end of the work shift.   |
| Methyl Ethyl Ketone    | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b><br>BEI: 2 mg/L, MEK [in urine]. Sampling time: at the end of the work shift.   |
| Cyclohexanone          | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b><br>BEI: 8 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.; semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], cyclohexanol [in urine]. Sampling time: at the end of the work shift.<br>BEI: 80 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.; semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], 1,2-cyclohexanediol [in urine]. Sampling time: at the end of the shift at the end of the work |

## Section 8. Exposure controls/personal protection

|              |   |
|--------------|---|
| Ethylbenzene | <p>week.</p> <p><b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b></p> <p>BEI: 0.7 g/g creatinine [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.; semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], Sum of mandelic acid and acid phenylglyoxylic [in urine]. Sampling time: at the end of the shift at the end of the work week.</p> <p>BEI: semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible., ethylbenzene [in exhaled air]. Sampling time: uncritical.</p> |
|--------------|---|

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : **This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).**  
Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

**Skin protection**

## Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : Colorless.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : 70°C (158°F)
- Flash point** : Closed cup: 6°C (42.8°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability** : Flammable liquid.
- Lower and upper explosion limit/flammability limit** : Lower: 1%  
Upper: 10.9%
- Vapor pressure** : 12.1 kPa (90.6 mm Hg)
- Relative vapor density** : 2.48 [Air = 1]
- Relative density** : 0.93
- Density** : 0.93 g/cm<sup>3</sup>
- Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.

## Section 9. Physical and chemical properties

- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C (104°F)): >20.5 mm<sup>2</sup>/s (>20.5 cSt)
- Molecular weight** : Not applicable.
- Particle characteristics**
- Median particle size** : Not applicable.
- Heat of combustion** : 20.674 kJ/g

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

##### Product/ingredient name

##### Result

Xylene, mixed isomers

##### Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

##### Rat - Inhalation - LC50 Gas.

6700 ppm [4 hours]

Toxic effects: Behavioral - Somnolence (general depressed activity)

n-Butyl Acetate

##### Rat - Oral - LD50

10768 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes

##### Rabbit - Dermal - LD50

>17600 mg/kg

##### Rabbit - Dermal - LD50

6480 mg/kg

##### Rat - Oral - LD50

2737 mg/kg

Methyl Ethyl Ketone

##### Rat - Oral - LD50

13400 mg/kg

Isobutyl Acetate

# Section 11. Toxicological information

|                     |   |
|---------------------|---|
| Cyclohexanone       | <p><b>Rabbit - Dermal - LD50</b><br/>&gt;17400 mg/kg</p> <p><b>Rat - Oral - LD50</b><br/>1800 mg/kg</p> <p><b>Rat - Inhalation - LC50 Gas.</b><br/>8000 ppm [4 hours]</p>   |
| Ethylbenzene        | <p><b>Rat - Oral - LD50</b><br/>3500 mg/kg</p> <p><u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes</p> <p><b>Rabbit - Dermal - LD50</b><br/>&gt;5000 mg/kg</p> <p><b>Rat - Oral - LD50</b><br/>2460 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b><br/>3400 mg/kg</p> <p><b>Rat - Inhalation - LC50 Vapor</b><br/>19200 mg/m<sup>3</sup> [4 hours]</p> |
| 2-Methyl-1-propanol | <p><b>Rat - Oral - LD50</b><br/>5620 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b><br/>&gt;5 g/kg</p> <p><u>Toxic effects:</u> Skin After systemic exposure - Dermatitis, other</p>  |
| Ethyl Acetate       | <p><b>Rat - Oral - LD50</b><br/>7872 mg/kg</p> <p><u>Toxic effects:</u> Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression</p>  |
| Methyl Methacrylate | <p><b>Rat - Inhalation - LC50 Vapor</b><br/>78000 mg/m<sup>3</sup> [4 hours]</p>  |

**Conclusion/Summary [Product]** : Not available.

**Skin corrosion/irritation**

**Product/ingredient name**

**Result**

Xylene, mixed isomers

**Rat - Skin - Mild irritant**  
Duration of treatment/exposure: 8 hours  
Amount/concentration applied: 60 uL

**Rabbit - Skin - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg

**Rabbit - Skin - Moderate irritant**  
Amount/concentration applied: 100 %

**Rabbit - Skin - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg

**Rabbit - Skin - Mild irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 14 mg

**Rabbit - Skin - Mild irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 402 mg

**Rabbit - Skin - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg

**Rabbit - Skin - Mild irritant**

n-Butyl Acetate

Methyl Ethyl Ketone

Isobutyl Acetate

# Section 11. Toxicological information

Cyclohexanone  
Amount/concentration applied: 500 mg  
**Rabbit - Skin - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg  
**Human - Skin - Mild irritant**  
Duration of treatment/exposure: 48 hours  
Amount/concentration applied: 50 %  
**Rabbit - Skin - Mild irritant**

Ethylbenzene  
Amount/concentration applied: 500 mg  
**Rabbit - Skin - Mild irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 15 mg

**Conclusion/Summary [Product]** : Not available.

## Serious eye damage/eye irritation

### **Product/ingredient name**

### **Result**

Xylene, mixed isomers  
**Rabbit - Eyes - Mild irritant**  
Amount/concentration applied: 87 mg  
**Rabbit - Eyes - Severe irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 5 mg  
**Rabbit - Eyes - Moderate irritant**  
Amount/concentration applied: 100 mg  
**Rabbit - Eyes - Moderate irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 500 mg  
**Rabbit - Eyes - Severe irritant**  
Duration of treatment/exposure: 24 hours  
Amount/concentration applied: 250 ug  
**Rabbit - Eyes - Severe irritant**  
Amount/concentration applied: 20 mg  
**Rabbit - Eyes - Severe irritant**  
Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]** : Not available.

## Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

## Respiratory or skin sensitization

Not available.

## **Skin**

**Conclusion/Summary [Product]** : Not available.

## **Respiratory**

**Conclusion/Summary [Product]** : Not available.

# Section 11. Toxicological information

## Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

## Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

## Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Xylene, mixed isomers   | -    | 3    | -   |
| Cyclohexanone           | -    | 3    | -   |
| Ethylbenzene            | -    | 2B   | -   |
| Methyl Methacrylate     | -    | 3    | -   |

## Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

## Specific target organ toxicity (single exposure)

### Product/ingredient name

### Result

|                       |  |
|-----------------------|--|
| Xylene, mixed isomers | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |
| n-Butyl Acetate       | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| Methyl Ethyl Ketone   | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| Isobutyl Acetate      | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| Cyclohexanone         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |
| Ethylbenzene          | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| 2-Methyl-1-propanol   | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |
| Ethyl Acetate         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| Methyl Methacrylate   | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |

## Specific target organ toxicity (repeated exposure)

### Product/ingredient name

### Result

# Section 11. Toxicological information

|                       |   |
|-----------------------|---|
| Xylene, mixed isomers | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| Ethylbenzene          | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |

## Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| Xylene, mixed isomers   | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene            | ASPIRATION HAZARD - Category 1 |

## Information on the likely routes of exposure

Not available.

## Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

## Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
  - pain
  - watering
  - redness
- Inhalation** : Adverse symptoms may include the following:
  - respiratory tract irritation
  - coughing
  - nausea or vomiting
  - headache
  - drowsiness/fatigue
  - dizziness/vertigo
  - unconsciousness
- Skin contact** : Adverse symptoms may include the following:
  - pain or irritation
  - redness
  - blistering may occur
- Ingestion** : Adverse symptoms may include the following:
  - stomach pains

## Delayed and immediate effects and also chronic effects from short and long term exposure

### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

## Potential chronic health effects

Not available.

# Section 11. Toxicological information

**Conclusion/Summary [Product]** : Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

**Numerical measures of toxicity**

**Acute toxicity estimates**

| Product/ingredient name            | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Clear Acrylic Polyurethane Topcoat | 7219.0       | 7460.9         | 143520                   | 278.5                      | N/A                                 |
| Xylene, mixed isomers              | 4300         | 2500           | N/A                      | N/A                        | N/A                                 |
| n-Butyl Acetate                    | 10768        | N/A            | N/A                      | N/A                        | N/A                                 |
| Methyl Ethyl Ketone                | 2737         | 6480           | N/A                      | N/A                        | N/A                                 |
| Isobutyl Acetate                   | 13400        | N/A            | N/A                      | N/A                        | N/A                                 |
| Cyclohexanone                      | 1800         | 1100           | 8000                     | N/A                        | N/A                                 |
| Ethylbenzene                       | 3500         | N/A            | N/A                      | 11                         | N/A                                 |
| 2-Methyl-1-propanol                | 2460         | 3400           | N/A                      | N/A                        | N/A                                 |
| Ethyl Acetate                      | 5620         | N/A            | N/A                      | N/A                        | N/A                                 |
| Methyl Methacrylate                | 7872         | N/A            | N/A                      | 78                         | N/A                                 |

# Section 12. Ecological information

**Toxicity**

**Product/ingredient name**

**Result**

Xylene, mixed isomers

**Acute - LC50 - Marine water**  
 Crustaceans - Daggerblade grass shrimp - *Palaemon pugio*  
 8500 µg/l [48 hours]  
Effect: Mortality

**Acute - LC50 - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 days; Size: 18.4 mm; Weight: 0.077 g  
 13.4 mg/l [96 hours]  
Effect: Mortality

n-Butyl Acetate

**Acute - LC50 - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g  
 18 mg/l [96 hours]  
Effect: Mortality

**Acute - LC50 - Marine water**  
 Crustaceans - Brine shrimp - *Artemia salina*  
 32 mg/l [48 hours]  
Effect: Mortality

Methyl Ethyl Ketone

**Acute - EC50 - Fresh water**  
 Daphnia - Water flea - *Daphnia magna* - Larvae  
Age: <24 hours

## Section 12. Ecological information

5091 mg/l [48 hours]  
Effect: Intoxication  
**Acute - LC50 - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 days; Size: 22 mm; Weight: 0.167 g  
 3220 mg/l [96 hours]  
Effect: Mortality

**Acute - EC50 - Marine water**  
 Algae - Diatom - *Skeletonema costatum*  
 >500 mg/l [96 hours]  
Effect: Population

Cyclohexanone

**Acute - LC50 - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas*  
Age: 30 days; Size: 20.2 mm; Weight: 0.127 g  
 527 mg/l [96 hours]  
Effect: Mortality

**Chronic - EC10**  
 Algae - Green algae - *Chlamydomonas reinhardtii* - Exponential growth phase  
Age: 7 days  
 3.56 mg/l [72 hours]  
Effect: Population

**Acute - EC50**  
 Algae - Green algae - *Chlamydomonas reinhardtii* - Exponential growth phase  
Age: 7 days  
 32.9 mg/l [72 hours]  
Effect: Population

Ethylbenzene

**Acute - LC50 - Fresh water**  
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*  
 4200 µg/l [96 hours]  
Effect: Mortality

**Acute - EC50 - Fresh water**  
 Daphnia - Water flea - *Daphnia magna* - Neonate  
Age: ≤24 hours  
 2.93 mg/l [48 hours]  
Effect: Intoxication

**Acute - EC50 - Fresh water**  
 Algae - Green algae - *Raphidocelis subcapitata*  
 3600 µg/l [96 hours]  
Effect: Population

2-Methyl-1-propanol

**Acute - LC50 - Fresh water**  
 Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*  
Weight: 1.67 g  
 1330 mg/l [96 hours]  
Effect: Mortality

**Acute - LC50 - Marine water**  
 Crustaceans - Brine shrimp - *Artemia salina*  
 600 mg/l [48 hours]  
Effect: Mortality

**Chronic - NOEC - Fresh water**  
 Daphnia - Water flea - *Daphnia magna*  
Age: ≤24 hours  
 4 mg/l [21 days]  
Effect: Reproduction

Ethyl Acetate

**Acute - LC50 - Fresh water**  
 Daphnia - Water flea - *Daphnia cucullata*

# Section 12. Ecological information

Age: 11 days  
 154 mg/l [48 hours]  
Effect: Mortality  
**Acute - LC50 - Fresh water**  
 Fish - Indian catfish - *Heteropneustes fossilis*  
Size: 14.16 cm; Weight: 25.54 g  
 212.5 mg/l [96 hours]  
Effect: Mortality  
**Acute - EC50 - Fresh water**  
 Algae - Green algae - *Selenastrum sp.*  
 2500 mg/l [96 hours]  
Effect: Population  
**Chronic - NOEC - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas* - Embryo  
Age: <24 hours  
 75.6 mg/l [32 days]  
Effect: Mortality  
**Chronic - NOEC - Fresh water**  
 Daphnia - Water flea - *Daphnia magna*  
Age: ≤24 hours  
 2.4 mg/l [21 days]  
Effect: Mortality  
**Acute - LC50 - Fresh water**  
 Fish - Fathead minnow - *Pimephales promelas* - Adult  
 130 mg/l [96 hours]  
Effect: Mortality

Methyl Methacrylate

**Conclusion/Summary [Product]** : Not available.

**Persistence and degradability**

Not available.

**Conclusion/Summary [Product]** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Xylene, mixed isomers   | -                 | -          | Readily          |
| n-Butyl Acetate         | -                 | -          | Readily          |
| Methyl Ethyl Ketone     | -                 | -          | Readily          |
| Ethylbenzene            | -                 | -          | Readily          |
| 2-Methyl-1-propanol     | -                 | -          | Readily          |
| Ethyl Acetate           | -                 | -          | Readily          |

**Bioaccumulative potential**

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| Xylene, mixed isomers   | -                  | 8.1 to 25.9 | Low       |
| Ethyl Acetate           | -                  | 30          | Low       |

**Mobility in soil**

**Soil/Water partition coefficient** : Not available.

**Other adverse effects**

## Section 12. Ecological information






No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                   | DOT<br>Classification  | TDG<br>Classification  | Mexico<br>Classification   | IATA   | IMDG   |
|-----------------------------------|--|--|--|--|--|
| <b>UN number</b>                  | UN1263   | UN1263   | UN1263   | UN1263   | UN1263   |
| <b>UN proper shipping name</b>    | PAINT  | PAINT  | PAINT  | PAINT  | PAINT  |
| <b>Transport hazard class(es)</b> | 3<br> | 3<br>   | 3<br> | 3<br> | 3<br> |
| <b>Packing group</b>              | II   | II   | II   | II   | II   |
| <b>Environmental hazards</b>      | No.  | No.  | No.  | No.  | No.  |
| <b>Additional information</b>     | -<br><br><b>ERG No.</b><br>128   | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).<br><br><b>ERG No.</b><br>128 | -<br><br><b>ERG No.</b><br>128   | -  | <b>Emergency schedules</b> F-E, S-E  |

## Section 14. Transport information

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to IMO instruments** : Not available.

**Proper shipping name** : Not available.

## Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### International lists

**Australia inventory (AIC)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Korea inventory (KECI)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
**Philippines inventory (PICCS)**: Not determined.  
**Taiwan Chemical Substances Inventory (TCSI)**: Not determined.  
**Thailand inventory**: Not determined.  
**Turkey inventory**: Not determined.  
**Vietnam inventory**: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 3 |
| Flammability     |   | 3 |
| Physical hazards |   | 0 |
|                  |   |   |

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

# Section 16. Other information

| Classification   | Justification         |
|--|-----------------------|
| FLAMMABLE LIQUIDS - Category 2   | On basis of test data |
| SKIN CORROSION/IRRITATION - Category 2   | Calculation method    |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  | Calculation method    |
| SKIN SENSITIZATION - Category 1  | Calculation method    |
| CARCINOGENICITY - Category 2   | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2                              | Calculation method    |

**History**

- Date of printing** : 5/2/2026
- Date of issue/Date of revision** : 5/2/2026
- Date of previous issue** : 10/3/2025
- Version** : 21
- Key to abbreviations** :
  - ATE = Acute Toxicity Estimate
  - BCF = Bioconcentration Factor
  - GHS = Globally Harmonized System of Classification and Labelling of Chemicals
  - IATA = International Air Transport Association
  - IBC = Intermediate Bulk Container
  - IMDG = International Maritime Dangerous Goods
  - LogPow = logarithm of the octanol/water partition coefficient
  - MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
  - N/A = Not available
  - SGG = Segregation Group
  - UN = United Nations

📌 Indicates information that has changed from previously issued version.

**Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

