### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Feb 24, 2024

08 00 [0554]

### **PRODUCT NUMBER**

SC0206000

#### PRODUCT NAME

LU™206 All-Purpose Silicone Lubricant Aerosol

#### **MANUFACTURER'S NAME**

SPRAYON PRODUCTS SPRAYON PRODUCTS GROUP 101 W. Prospect Avenue, Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

SC0206000 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT5.42 lb/gal0.65-20 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Propane 74-98-6	N	N	N	N	15	19
Hexane 110-54-3	N	Υ	Υ	Υ	41	40
2-Methylpentane 107-83-5	N	N	N	N	19	19
3-Methylpentane 96-14-0	N	N	N	N	7	7
2,3-Dimethylbutane 79-29-8	N	N	N	N	6	6
2,2-Dimethylbutane 75-83-2	N	N	N	N	2	2
Cyclohexane 110-82-7	N	Υ	Υ	N	2	2

# Volatile Organic Compounds - U.S. EPA / Canada

	SC0206000	
	LB/Gal	g/L
Coating Density	5.42	649
	By wt	By vol
Total Volatiles	94.1%	95.7%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	94.1%	95.7%
Percent Non-Volatile	5.9%	4.3%
VOC Content	LB/Gal	g/L
Total	5.10	611
Less exempt solvents	5.10	611
Of solids	> 99.99	> 11,983
Of solids	15.94 lb/lb	15.94 kg/kg
	By wt	
By wt LVP-VOC	94.1%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.18

## **Volatile Organic Compounds - California**

	SC0206000		
	LB/Gal	g/L	
Coating Density	5.42	649	
	By wt	By vol	
Total Volatiles	94.1%	95.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	94.1%	95.7%	
Percent Non-Volatile	5.9%	4.3%	
VOC Content	LB/Gal	g/L	
Total	5.10	611	
Less exempt solvents	5.10	611	
Of solids	> 99.99	> 11,983	
Of solids	15.94 lb/lb	15.94 kg/kg	
	By wt		
By wt LVP-VOC	94.1%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.07

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	SC0206000		
	LB/Gal	g/L	
Coating Density	5.42	649	
	By wt	By vol	
Total Volatiles	94.1%	95.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	94.1%	95.7%	
Percent Non-Volatile	5.9%	4.3%	
VOC Content	LB/Gal	g/L	
Total	5.10	611	
Less exempt solvents	5.10	611	
Of solids	> 99.99	> 11,983	
Of solids	15.94 lb/lb	15.94 kg/kg	

## Volatile Organic Compounds - EU Directive 2004/42/EC

	SC0206000	
	By wt	By vol
Total Volatiles	94.1%	95.7%
VOC Content	LB/Gal	g/L
Total	5.10	611

# Volatile Organic Compounds - EU Directive 2010/75/EU

	SC0206000	
	By wt	By vol
Total Volatiles	94.1%	95.7%
VOC Content	LB/Gal	g/L
Total	5.10	611

# **Volatile Organic Compounds - Mexico**

	SC0206000		
	LB/Gal	g/L	
Coating Density	5.42	649	
	By wt	By vol	
Total Volatiles	94.1%	95.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	94.1%	95.7%	
Percent Non-Volatile	5.9%	4.3%	
VOC Content	LB/Gal	g/L	
Total	5.10	611	
Less exempt solvents	5.10	611	
Of solids	> 99.99	> 11,983	
Of solids	15.94 lb/lb	15.94 ka/ka	

# Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	SC0206000	
	LB/Gal	kg/L
Volatile HAPS	2.24	0.269
Of solids	52.84	6.331
Of solids	7.02 lb/lb	7.02 kg/kg

### **Air Quality Data**

**Density of Organic Solvent Blend** 

5.33 lb/gal

**Photochemically Reactive** 

Yes

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.