

CUTTING OIL



LU™ 208




Light Pressure Lubricant



Cutting and tapping fluids on all metals



Dielectric strength value: 10,000 Volts



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 500 °F (260 °C)



NSF® Registered; H1 Rated (Lubricants with incidental contact) (Registration # 115088)



HMIS Hazard Rating: Health (1) • Flammability (4) • Reactivity (0)

- Works on ferrous and soft metals
- Clings to surfaces
- Aerosol jet-spray for pin-point accuracy
- Reduces friction and wear



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 208 Cutting Oil is an excellent lubricant specifically formulated for all ferrous and non-ferrous machining operations. Extends tool life, reducing tool sharpening and downtime. Recommended for all metals including stainless steel and soft metals such as aluminum, brass and copper. It utilizes a unique combination of friction reducing triglycerides. It yields a high degree of fluid film protection resulting in excellent extreme pressure characteristics preventing metal-to-metal seizure.

LUBRICANTS

USES

- Drilling
- Cutting
- Threading
- Sawing
- Reaming and broaching
- Grinding

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

DIELECTRIC STRENGTH: 10,000 volts

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -20°F **HIGH:** 500°F

LOAD CAPACITY: Light

- NSF Registration Number 115088; P1 Rated
- Penetrant
- Rust Inhibitor
- Effective on all metals
- Prevents galling and scuffing of dies
- Extends die life and provides better part appearance
- Unique formulation insures proper wetting of metal surfaces
- High viscosity gives effective lubricity through progressive draws

PROPERTIES

APPEARANCE: Light amber

ODOR: Petroleum

PROPELLANT: Hydrocarbon

WT./GAL.: 7.13

SPECIFIC GRAVITY: 0.86

PAINTABLE: No

H.A.P.S. (Hazardous Air Pollutants): No

SARA 313 Chemicals: No

% VOC AEROSOL: 10.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: - <0°F

HAZARD RATING: 1,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00208

UPC Code: 0-75577-90208-8

Fill Wt.: 12 oz.

Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



LU208



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU208