

FOOD GRADE SILICONE LUBRICANT



LUTM212

- 

NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145277)
- 

LIGHT PRESSURE

For use in low pressure applications
- 

450 232
°F ↔ °C
-40 -40

Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 450 °F (232 °C)
- 

5% SILICONE

5% Silicone
- 

WIDE DELIVERY SPRAY

Wide delivery spray covers a wide surface area in a short amount of time
- 

H 2
F 4
R 0

HMS Hazard Rating:
Health (2) • Flammability (4) • Reactivity (0)

- Meets FDA requirements
- Resists corrosion and chemical attack
- Wide delivery spray covers a wide surface area in a short amount of time



PRESERVE. PROTECT. PREVENT.®

Sprayon® LUTM212 Food Grade Silicone Lubricant is a 5% low-viscosity silicone formula compatible with most surfaces. Meets FDA regulation described in Title 21 paragraph 178.3570, when no more than 1 ppm is imparted. NSF® H1 Registered for use in federally inspected meat and poultry plants. Effective from -40°F to +450°F. Repels water and is non-corrosive to metals. An excellent lubricant on plastic, fiber gears, extruded parts, wood-to-wood sliding applications and on rubber.

LUBRICANTS

FOR USE ON

- Slides • Guides • Knives
- Food & Drug Processing Equipment
- Food Racks • Slicers
- Heat Sealing Equipment
- Saws • Overhead Drives
- Grinders • Belts • Mixers
- Bottling Machines
- Conveyors • Chutes

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU212

APPLICATION

Shake well before using. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

- PLASTIC SAFE: Yes
- TEMPERATURE RANGE:
 - HIGH: 450 °F
 - LOW: -40 °F
- LOAD CAPACITY: Light
 - Penetrant
 - Water-Displacer
 - Rust Inhibitor
 - Equipped with SPRAY ANYWAY™ Nozzle

PACKAGING

- STOCK #: S00212000
- UPC CODE: 0-75577-00622-9
- FILL WT.: 13.25 oz.
- PER CASE: 12
- CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

- MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
- CUSTOMER SERVICE: 800-777-2966
- TECHNICAL INFORMATION: 800-251-2486

PROPERTIES

- APPEARANCE: Clear
- BASE: Silicone
- FILM TYPE: Wet Fluid Film
- ODOR: Low
- CONTAINS P.T.F.E: No
- PROPELLANT: Hydrocarbon Blend
- WT./GAL.: 5.42
- SPECIFIC GRAVITY: 0.65
- % VOC AEROSOL: 95
- V.O.C. COMPLIANT CALIFORNIA: Yes (For use in manufacturing process only)
- V.O.C. COMPLIANT OTC STATES: Yes
- SARA 313: None
- HAPS: None
- FLAMMABLE: Yes
- FLASH POINT: <0 °F
- HAZARD RATING: 2, 4, 0
- SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145277



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966

310-PDS-LU212