




# FOOD GRADE HIGH TEMP LUBRICANT





## LU™ 213


- 


NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145281)
- 

For use in high pressure applications
- 

Minimum - Maximum operational temperature range: Low 12 °F (-11 °C) • High 635 °F (335 °C)
- 

Meets (OECD) 301B Standards - Rapidly Biodegradable after 301B Standard
- 

Free of heavy metals such as Barium & Cadmium
- 

Contains P.T.F.E. (polytetrafluoroethylene)
- 

HMIS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- High Temperature Performance
- Fortified With Extreme Pressure and Anti-Wear Additives
- Foaming Action For Excellent Cling and Penetration



**PRESERVE. PROTECT. PREVENT.™**

Sprayon® LU™213 Food Grade High Temp Lubricant is a blend of the finest quality renewable resource oils available, treated with the most effective anti-oxidants, extreme pressure, anti-wear, and corrosion protecting additives. PTFE is added to further enhance load capacity, and reduce friction. LU™213 Food Grade High Temp Lubricant offers excellent extreme pressure lubricity, water resistance and high temperature (12 °F to 635 °F) performance on chains and much more. Foaming action allows for pin-point application and penetration.

# LUBRICANTS

## FOR USE ON

- Ovens • Dryers
- Gears • Conveyors
- Wire Ropes • Hoists
- Rollers • Cams
- Slide Bearings
- Anything Requiring Extreme Temperature Performance

## FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU213

## APPLICATION

Shake well before using. For best results use at room temperature 70° F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth. Use extension tube for hard to reach areas

## PERFORMANCE

**PLASTIC & RUBBER SAFE:** Yes  
(Always test before using)  
**TEMPERATURE RANGE:**  
**HIGH:** 635°F  
**LOW:** 12°F  
**LOAD CAPACITY:** Extreme  
**DIELECTRIC STRENGTH:** 46.5 kV  
**FALEX LOAD (ASTM D-3233A):** 3,750 lbs.  
**4-BALL WEAR SCAR (ASTM D-2266):** 0.44mm  
**RAPIDLY BIODEGRADABLE (OECD-301):** Yes  
**DELIVERY:** SPRAY ANYWAY™

## PACKAGING

**STOCK #:** S00213000  
**UPC CODE:** 0-75577-00623-6  
**FILL WT.:** 15 oz.  
**PER CASE:** 12  
**CARTON DIMENSIONS:**  
L 11.13" x W 8.44" x H 9.94"

## SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

## RESOURCES

**MSDS/EDS/PRODUCT DATA SHEETS:** Sprayon.com  
**CUSTOMER SERVICE:** 800-777-2966  
**TECHNICAL INFORMATION:** 800-251-2486

## PROPERTIES

**APPEARANCE:** Light Straw Color  
**BASE:** Bio-based (Vegetable)  
**FILM TYPE:** Wet  
**CONTAINS P.T.F.E.:** Yes  
**ODOR:** Low  
**PROPELLANT:** Hydrocarbon Blend  
**WT./GAL.:** 6.86  
**SPECIFIC GRAVITY:** 0.83  
**% VOC AEROSOL:** 15  
**V.O.C. COMPLIANT CALIFORNIA:** Yes  
**V.O.C. COMPLIANT OTC STATES:** Yes  
**HEAVY METALS:** No  
**FLAMMABLE:** Yes  
**FLASH POINT:** <0 °F  
**SARA 313:** None  
**PROP 65:** None  
**HAPS:** None  
**HAZARD RATING:** 2, 4, 0  
**SHELF LIFE:** 3 years from date of manufacture

## NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145281



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

© 2012 Sprayon® Products Made in U.S.A.

Distributed by:



**Sprayon® Products**  
101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
800-777-2966

310-PDS-LU213