

MOLD RELEASE

# MOLD CLEANER



## MR<sup>TM</sup> 351



HMIS Hazard Rating:  
Health (2) • Flammability (2) • Reactivity (0)



Protectant Longevity: Light 3 months



Non-abrasive. Will not abrade surfaces



Features Spray Anyway<sup>TM</sup> Nozzle

- Non-abrasive
- Displaces moisture
- Neutralizes fingerprints
- Equipped with SPRAY ANYWAY<sup>TM</sup> Valve
- Removes resin residual, oils and grease deposits



PRESERVE. PROTECT. PREVENT.<sup>TM</sup>

Sprayon<sup>®</sup> MR<sup>TM</sup> 351 Mold Cleaner is a non-abrasive cleaner for all types of metal molds that also leaves a fine, microscopic inhibitor for short-term protection against corrosion. Surface moisture, dirt, oils, release agent residues and other contaminants are quickly eliminated without the necessity of removing the mold from the machine.



## USES

- Metal molds
- Machinery
- Electrical and electronic equipment
- Pins
- Mechanical equipment



MR351

© 2010 Sprayon® Products Made in U.S.A.

## MOLD RELEASE

### APPLICATION

Product should be sprayed in a well ventilated area. Sprays best at room temperature (70°F). Shake can well before using. Hold can 8" to 10" from surface to be cleaned. Beginning at the top of the mold, use spray pressure to thoroughly wet surface. Wipe surface with a clean cloth to remove contaminants. Repeat application if needed. To use entire contents, hold sprayhead, then rotate can until material sprays. To provide extended protection against acid, humidity rust and contamination during indoor or outdoor storage, use Sprayon® MR™361 Mold Protectant.

### PERFORMANCE

- No CFS's, HFC's
- SPRAY ANYWAY™ valve
- Extension tube is included for ease in flushing deep cavities

### PACKAGING

STOCK #: S00351  
UPC CODE: 0-75577-90351-1  
FILL WT.: 16 oz.  
PER CASE: 12  
CARTON DIMENSIONS:  
L 11.13" x W 8.44" x H 9.94"

### SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

### PROPERTIES

APPEARANCE: Clear volatile liquid  
ODOR: Fresh linen  
PROPELLANT: CO<sub>2</sub>  
WT./GAL.: 11.96  
SPECIFIC GRAVITY: 1.44  
% VOC: 71.62%  
V.O.C. COMPLIANT CALIFORNIA: Yes  
V.O.C. COMPLIANT OTC STATES: Yes  
FLAMMABLE: No  
FLASH POINT: None  
HAZARD RATING: 2,2,0  
SHELF LIFE: 3 years from date of manufacture

### RESOURCES

MSDS/EDS/PRODUCT  
DATA SHEETS: [sprayon.com](http://sprayon.com)  
CUSTOMER SERVICE: 1-800-777-2966  
TECHNICAL INFORMATION: 1-800-251-2486



Distributed by:

PRESERVE. PROTECT. PREVENT.



**Sprayon® Products**  
101 Prospect Ave. NW  
Cleveland, OH 44115  
[Sprayon.com](http://Sprayon.com)  
1-800-777-2966

310-PDS-MR351