

FOOD GRADE BELT DRESSING



SPTM 608



NSF® Nonfood Compounds Program Listed
H1 Rated (Registration # 145285)



Asphalt & Rosin Free



Features SPRAY ANYWAY™ Nozzle



HMIS Hazard Rating:
Health (2) • Flammability (4) • Reactivity (0)

- Colorless & Water Resistant
- Rosin & Asphalt Free
- Increases Pulling Power



PRESERVE. PROTECT. PREVENT.®

Sprayon® SPTM 608 Food Grade Belt Dressing is ideal for industrial, automotive and food processing applications. Highly processed ingredients ensure increased RPM & horsepower, while reducing slippage. Will not glaze, collect dirt or dust. SPTM 608 Food Grade Belt Dressing is effective in the prevention of dry/air rot. This formulation conditions belts while increasing pulling power.

SPECIALTY PRODUCTS

FOR USE ON

- Appliance Drive Belts
- Bearings • Flat Belts
- Polishing Belts • V-Belts
- Sanding Belts
- Toothed Belts
- Round Belts
- Rubber • Leather
- Fabric Materials

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



SP608

APPLICATION

Shake well before using. Clean belt of foreign matter. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Spray with back and forth motion 12 inches from belt surface. Only use necessary amount to achieve desired results. Do not over saturate. NOTE: Not recommended this product be applied to moving belts or machinery in operation. Use extension tube for hard to reach areas.

PERFORMANCE

- Reduces slippage, increases pulling power, RPM & belt lift
- Regular use adds life and increased efficiency
- Equiped with SPRAY ANYWAY™ Nozzle

PACKAGING

STOCK #: S00608000

UPC CODE: 0-75577-00624-3

FILL WT.: 13.25 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: Sprayon.com

CUSTOMER SERVICE:

800-777-2966

TECHNICAL INFORMATION:

800-251-2486

PROPERTIES

APPEARANCE: Clear

FILM TYPE: Tacky Semi-Solid

ODOR: Mild Solvent

PROPELLANT: Hydrocarbon Blend

WT./GAL.: 5.42

SPECIFIC GRAVITY: 0.65

H.A.P.S. (Hazardous Air Pollutants): None

SARA 313 Chemicals: None

% VOC AEROSOL: 80%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0 °F

HAZARD RATING: 2, 4, 0

SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145285



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.

Scan this code with your mobile phone to download the NSF® Registration Letter for this product

