

NON-CHLORINATED ELECTRICAL CLEANER



EL™ 2846



For use on Energized Equipment



NSF® Registered; K2 Rated (Solvents for cleaning electronic instruments) (Registration# 138487)




Dielectric strength value: 15,000 volts



Non-flammable



Evaporation rate: Very Fast



KB Solvency Strength (higher value, stronger the solvent): 129



HMIS Hazard Rating
Health (2) • Flammability (0) • Reactivity (0)

- Non-flammable, non-chlorinated
- Fast evaporating
- Dielectric strength: 15,000 volts
- No hazardous air pollutants



PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 2846 Non-Chlorinated Electrical Degreaser is a non-flammable, fast-evaporating cleaner that penetrates instantly to remove dirt, oil, grease and wax. Increases the life of electrical components by removing foreign materials that can cause costly downtime. Degreases more thoroughly and several times faster than alkaline cleaners. Excellent for cleaning sheet and strip steel prior to galvanizing. Equipped with a high-delivery valve for cleaning efficiency and an extension tube for hard-to-reach areas.

ELECTRICAL & ELECTRONIC

USES

- Electric motors
- Generators
- Air tools
- Brakes
- Clutches
- Chains
- Sprockets
- Wire rope
- Dies
- Molds
- Relays
- Locks
- Radar equipment
- Material handling equipment
- Air conditioners

APPLICATION

Product should be sprayed in a well-ventilated area. Shake well before using. Sprays best at room temperature (70°F). Hold can in upright position for best spray pattern. NOTE: May harm certain plastics, elastomers and air-dry painted surfaces. Test product on nonessential similar material prior to application.

PERFORMANCE

EVAPORATION RATE: Very Fast
KB VALUE (Cleaning Power): 129
DIELECTRIC STRENGTH: 15,000 volts
PLASTIC SAFE: No

- NSF Registration Number 138487; K2 Rated
- Non-chlorinated
- Non-ozone depleting
- No residue
- High delivery valve
- Fast evaporation
- Safe on all ferrous and non-ferrous metals
- Safe on lexan, ABS and noryl plastics
- Equipped with an extension tube for hard to reach areas

PROPERTIES

APPEARANCE: Clear Volatile Liquid
ODOR: Strong
PROPELLANT: CO₂
WT./GAL.: 10.74
SPECIFIC GRAVITY: 1.29
H.A.P.S. (HAZARDOUS AIR POLLUTANTS): No
SARA 313 CHEMICALS: No
PROP 65 CHEMICALS: No
% VOC AEROSOL: 94%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: No
FLASH POINT: N/A
HAZARD RATING: 2, 0, 0
SHELF LIFE: 3 years from date of manufacture

PACKAGING

STOCK #: S02084600
UPC CODE: 0-75577-20846-3
FILL WT: 18 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA
SHEETS: sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



EL2846



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-EL2846