

NON-FLAMMABLE SYNTHETIC LUBRICANT



LU™ 728

	For use in extreme pressure applications
	Contains P.T.F.E. (polytetrafluoroethylene)
	Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 475 °F (246 °C)
	Dielectric strength value: 39,000 Volts
	Non-Flammable
	Features Spray Anyway® Nozzle
	HMIS Hazard Rating: Health (1) • Flammability (0) • Reactivity (0)

- H1 rated
- Non-flammable
- Low HMIS rating
- Low odor & colorless
- Extreme pressure performance
- Formulated with P.T.F.E.



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 728 Non-Flammable Synthetic Lubricant has been specifically developed to meet the demands for a safe, low HMIS rating, non-flammable lubricant that has all the performance characteristics of a premium, high load capable, synthetic lubricant. Modified with P.T.F.E. to enhance its lubricity, you can count on LU™ 728 Non-Flammable Synthetic Lubricant as the worker's choice lubricant for safety and performance.

LUBRICANTS

USES

- Hinges
- Nuts & bolts
- Conveyors
- Chains
- Cables
- Linkages
- Food processing equipment

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

DIELECTRIC STRENGTH: 39,000 volts

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 475°F

LOAD CAPACITY: Extreme Pressure

FALEX LUBRICITY TEST: Exceeds

22 lb. max

EP PRESSURE (ASTM D3233A): 3,000 lbs

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Equipped with SPRAY ANYWAY™ valve and extension tube

PROPERTIES

APPEARANCE: Clear liquid

ODOR: Low

PROPELLANT: CO₂

WT./GAL.: 6.8

SPECIFIC GRAVITY: 0.82

H.A.P.S. (HAZARDOUS AIR POLLUTANTS): No

SARA 313 CHEMICALS: No

PROP 65: No

% VOC AEROSOL: 0.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: No

FLASH POINT: 320°F

HAZARD RATING: 1,0,0

SHELF LIFE: 3 years from date of manufacture



LU728

PACKAGING

Stock #: S00728000

UPC Code: 0-75577-00728-8

Fill Wt.: 8.75 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU728