

DRY WELD SPATTER PROTECTANT



WLTM 941

H 2TM
F 2
R 0

HMIS Hazard Rating:
Health (2) • Flammability (2) • Reactivity (0)



Product is FREE of Methylene Chloride

TALC
BASE

Product base - Talc

QUICK
DRY
5 MIN.

Dry to touch time: 5 minutes

EASY
REMOVAL

Product can be easily removed

- Formulated without Methylene Chloride
- Talc based
- Brushes off easily
- Does not contain silicone
- Prevents base metal spatter



PRESERVE. PROTECT. PREVENT.TM

Sprayon® WLTM 941 Dry Weld Spatter Protectant is a powder formula that dries to a white film. Prevents spatter from sticking to metal surfaces during welding. Just brush or wipe off residue after welding. Does not contain silicone. Surface may be painted after use.

USES

- All types of welding processes
- Maintenance
- Production
- Construction
- Body Shops

WELDING

SURFACE PREPARATION

NOTE: Allow material to air dry before welding. Surface must be free of grease, rust, dirt and wax. Product should be sprayed in a well-ventilated area. Use at room temperature (70°F). Shake well before using. Spray 8" to 10" from surface. Move can with short "dusting" strokes. After completing job, clean valve by holding can upside down and spray until no more paint comes out.

PERFORMANCE

- Will not interfere with painting
- Easy removal

DRYING TIME @ 70°F @ 50%R.H.

TO TOUCH: 5 minutes

CLEAN UP: Brush or cloth

PACKAGING

STOCK #: S00941000

UPC CODE: 0-75577-75937-8

FILL WT.: 15.5 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 8.38"

PROPERTIES

BASE: Talc

SOLVENT: Chlorinated

APPEARANCE: Dry Translucent White

PROPELLANT: Hydrocarbon

WT./GAL.: 8.22

SPECIFIC GRAVITY: 0.99

% VOC: 27.24%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,2,0

COVERAGE PER AEROSOL (THEORETICAL):

10-15 sq. ft. per can

SHELF LIFE: 3 years from date of manufacture

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: sprayon.com

CUSTOMER SERVICE: 1-800-777-2966

TECHNICAL INFORMATION: 1-800-251-2486



WL941



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-WL941