# **SAFETY DATA SHEET**

B66W1251

### **Section 1. Identification**

Product name	: PRO INDUSTRIAL™ DTM Acrylic Eg-Shel Extra White
Product code	: B66W1251
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

Classification of the	: SKIN SENSITIZATION - Category 1
substance or mixture	CARCINOGENICITY - Category 1A

: Danger

**GHS label elements** 

Hazard pictograms

Signal word **Hazard statements** 

: May cause an allergic skin reaction. May cause cancer.

**Precautionary statements** 

**Prevention** 

Response

of the workplace. : IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out

Date of issue/Date	of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	: 25	1/13
B66W1251	PRO INDUSTRIAL™ D Extra White	TM Acrylic Eg-S	Shel		SHW-85-I	NA-GHS-CA	



# Section 2. Hazards identification

Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

### CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	16.34	13463-67-7
Polypropylene glycol alkyl phenyl ether	0.74	9064-13-5
Benzophenone	0.14	119-61-9
Cristobalite, respirable powder	0.11	14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date	of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	: 25	2/13
B66W1251	PRO INDUSTRIAL™ D Extra White	TM Acrylic Eg-S	Shel		SHW-85-I	NA-GHS-CA	

# Section 4. First aid measures

Section 4. Flist a				
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.			
Most important symptoms/	effects, acute and delayed			
Potential acute health effe	octs			
Eye contact	: No known significant effects or critical hazards.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: May cause an allergic skin reaction.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/sym	<u>ptoms</u>			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>			
Specific treatments	: No specific treatment.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

Date of issue/Date	of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	: 25
B66W1251	PRO INDUSTRIAL™ E Extra White	OTM Acrylic Eg-S	Shel		SHW-85-	NA-GHS-CA

3/13

# Section 5. Fire-fighting measures

Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	<u>ont</u>	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date	of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	: 25	4/13
B66W1251	PRO INDUSTRIAL™ D Extra White	TM Acrylic Eg-S	Shel		SHW-85-	NA-GHS-CA	

# Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from				
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials				
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed				
	and sealed until ready for use. Containers that have been opened must be carefully				
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.				
	Use appropriate containment to avoid environmental contamination. See Section 10 for				
	incompatible materials before handling or use.				

# Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 7/2023). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles
Polypropylene glycol alkyl phenyl ether	9064-13-5	None.
Benzophenone	119-61-9	OARS WEEL (United States, 4/2022). TWA: 0.5 mg/m <sup>3</sup> 8 hours.
Cristobalite, respirable powder	14464-46-1	<ul> <li>OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO<sub>2</sub>+5) 8 hours.</li> <li>Form: Respirable TWA: 10 mg/m<sup>3</sup> / 2 x (%SiO<sub>2</sub>+2) 8 hours.</li> <li>Form: Respirable TWA: 30 mg/m<sup>3</sup> / 2 x (%SiO<sub>2</sub>+2) 8 hours.</li> <li>Form: Total dust</li> <li>OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>ACGIH TLV (United States, 7/2023). [Silica, crystalline] TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> <li>NIOSH REL (United States, 10/2020).</li> <li>[SILICA, CRYSTALLINE] TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</li> </ul>

### Occupational exposure limits (Canada)

Ingredien	t name		CAS #	Exposure limit	ts			
Benzophe	enone		119-61-9	•	/EEL (United States, 4/2022).			
' Cristobalite		14464-46-1	CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite] TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2023). TWAEV: 0.05 mg/m <sup>3</sup> 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 3/2023). OEL: 0.025 mg/m <sup>3</sup> 8 hours. Form:					
ate of issue/L	Date of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version : 25	5/13		
66W1251 PRO INDUSTRIAL™ DTM Acrylic Eg-Shel Extra White		-Shel		SHW-85-NA-GHS-CA	<b>x</b>			

# Section 8. Exposure controls/personal protection

Respirable particulate <b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Respirable particulate matter. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: respirable
TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
None.		

### **Biological exposure indices (United States)**

No exposure indices known.

#### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mis local exhaust ventilation or other engineering controls to k airborne contaminants below any recommended or statute	keep worker exposure to
Environmental exposure controls	This product contains a component that is either sub condition or an existing/proposed SNAC (Significant	
	Emissions from ventilation or work process equipment sh they comply with the requirements of environmental prote cases, fume scrubbers, filters or engineering modification will be necessary to reduce emissions to acceptable level	ction legislation. In some s to the process equipment
Individual protection measure	<u>ires</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling eating, smoking and using the lavatory and at the end of t Appropriate techniques should be used to remove potenti Contaminated work clothing should not be allowed out of contaminated clothing before reusing. Ensure that eyewa showers are close to the workstation location.	he working period. ally contaminated clothing. the workplace. Wash
Eye/face protection	: Safety eyewear complying with an approved standard sho assessment indicates this is necessary to avoid exposure gases or dusts. If contact is possible, the following protec the assessment indicates a higher degree of protection: s shields.	e to liquid splashes, mists, ction should be worn, unless
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an worn at all times when handling chemical products if a risk necessary. Considering the parameters specified by the during use that the gloves are still retaining their protective noted that the time to breakthrough for any glove material glove manufacturers. In the case of mixtures, consisting protection time of the gloves cannot be accurately estimat	k assessment indicates this is glove manufacturer, check e properties. It should be I may be different for different of several substances, the
Body protection	<ul> <li>Personal protective equipment for the body should be sele performed and the risks involved and should be approved handling this product.</li> </ul>	
Date of issue/Date of revision	: 5/16/2024 Date of previous issue : 4/25/2024	Version : 25 6/13
B66W1251 PRO INDUSTRI/ Extra White	AL™ DTM Acrylic Eg-Shel	SHW-85-NA-GHS-CA

# Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### Appearance

Physical state	:	Liqui	d.			
Color	:	Whit	e.			
Odor	:	Not a	available.			
Odor threshold	:	Not a	available.			
рН	:	9				
Melting point/freezing point	:	Not a	available.			
Boiling point, initial boiling point, and boiling range	:	100°	C (212°F)			
Flash point	:	Clos	ed cup: Not applicable.			
Evaporation rate	:	0.09	(butyl acetate = 1)			
Flammability	:	Not a	Not available.			
Lower and upper explosion limit/flammability limit	1	Lower: 0.6% Upper: 4.2%				
Vapor pressure	:	2.3 kPa (17.5 mm Hg)				
Relative vapor density	:	1 [Air = 1]				
Relative density	:	1.28				
Solubility(ies)	1					
Media			Result			
cold water			Partially soluble			
Partition coefficient: n- octanol/water	:	Not a	applicable.			
Auto-ignition temperature	:	Not available.				
Decomposition temperature	:	Not available.				
Viscosity	:	Kine	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	:	Not	applicable.			
Heat of combustion	:	1.11	1 kJ/g			

## Section 10. Stability and reactivity

 Reactivity
 : No specific test data related to reactivity available for this product or its ingredients.

 Chemical stability
 : The product is stable.

 Possibility of hazardous reactions
 : Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date	of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	: 25	7/13
B66W1251	PRO INDUSTRIAL™ D Extra White	TM Acrylic Eg-S	Shel		SHW-85-N	IA-GHS-CA	

Section 10. Stability and reactivity				
Conditions to avoid	: No specific data.			
Incompatible materials	: No specific data.			
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzophenone	LD50 Dermal LD50 Oral		3535 mg/kg >10 g/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

### Sensitization

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Benzophenone Cristobalite, respirable powder	- - +	2B 2B 1	- - Known to be a human carcinogen.

### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

### Aspiration hazard

Not available.

Date of is	sue/Date of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version : 25	8/13
B66W125	PRO INDUSTRIAL	™ DTM Acrylic Eg	-Shel		SHW-85-NA-GHS-CA	

# Section 11. Toxicological information

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>icts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following:
	irritation
Ingestion	redness : No specific data.
ingestion	
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ifects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

: 4/25/2024

# Section 12. Ecological information

т	oxi	ci	tv
-	0.74		-

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide Benzophenone	Acute LC50 >1000000 μg/l Marine water Acute LC50 10.89 mg/l Fresh water	Fish - <i>Fundulus heteroclitus</i> Fish - <i>Pimephales promelas</i> - Larvae	96 hours 96 hours
	Chronic NOEC 1.03 mg/l Fresh water	Fish - <i>Pimephales promelas</i> - Embryo	32 days

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Benzophenone	-	12.02	Low

### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods: This product contains a component that is either subject to a CEPA ministerial<br/>condition or an existing/proposed SNAC (Significant New Activity).<br/>The generation of waste should be avoided or minimized wherever possible. Disposal<br/>of this product, solutions and any by-products should at all times comply with the<br/>requirements of environmental protection and waste disposal legislation and any<br/>regional local authority requirements. Dispose of surplus and non-recyclable products<br/>via a licensed waste disposal contractor. Waste should not be disposed of untreated to<br/>the sewer unless fully compliant with the requirements of all authorities with jurisdiction.<br/>Waste packaging should be recycled. Incineration or landfill should only be considered<br/>when recycling is not feasible. This material and its container must be disposed of in a<br/>safe way. Care should be taken when handling emptied containers that have not been<br/>cleaned or rinsed out. Empty containers or liners may retain some product residues.<br/>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains<br/>and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Date of issue/Date of rev	vision : 5/16/20.	24 Date of previous i	ssue : 4/25/2024	4 Versi	on : 25 10/1:
B66W1251 PRO INDUSTRIAL™ DTM Acrylic Eg-Shel SHW-85-NA-GHS-CA Extra White					

Section 14.	Transp	ort info	ormation			
Packing group	-		-	-	-	-
Environmental hazards	No.		No.	No.	No.	No.
Additional information Special precaution	- s for user	conside	r container sizes. T	- iptions are provided the presence of a shi	pping description for	a particular
		suitably to shipn of the p dangero	for that mode of tra- nent, and complian erson offering the p ous goods must be	, etc.), does not indic ansport. All packaging ce with the applicable product for transport. trained on all of the r of emergency situatio	g must be reviewed e regulations is the s People loading and isks deriving from th	for suitability prior ole responsibility unloading
Transport in bulk a to IMO instruments	ccording	Not avail	able.			
		Proper s	hipping name	: Not available.		
Section 15. Regulatory information						

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

International regulations


Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

# Section 16. Other information



Date of issue/Date	e of revision	: 5/16/2024	Date of previous issue	: 4/25/2024	Version	:25	11/13
B66W1251 PRO INDUSTRIAL™ DTM Acrylic Eg-Shel Extra White				SHW-85-	NA-GHS-CA	L .	

# Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

	Justification		
SKIN SENSITIZATION - C CARCINOGENICITY - Cat	Calculation method Calculation method		
<u>History</u>			
Date of printing	: 5/16/2024		
Date of issue/Date of revision	: 5/16/2024		
Date of previous issue	: 4/25/2024		
Version	: 25		
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations		

**V** Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 4/25/2024