SAFETY DATA SHEET

A6T354

Section 1. Identification

Product name	: A-100® Exterior Latex Flat Ultradeep Base
Product code	: A6T354
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: The Sherwin-Williams Company 418 North Service Road East Oakville, Ontario L6H 5R2 Canada
Emergency telephone	: US / Canada: (800) 424-9300
number of the company	Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 1-800-474-3794 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

ARCINOGENICITY - Category 1A PECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
the second s
ercentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1.1% ral), 1.1% (dermal), 1.1% (inhalation)
▲
anger
ay cause cancer.
auses damage to organs through prolonged or repeated exposure. (respiratory tract)
ead label before use. Keep out of reach of children. If medical advice is needed, have oduct container or label at hand.

Date of issue	/Date of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	1/12
A6T354	A-100® Exterior L Ultradeep Base	atex Flat			SHW-85-NA-GHS-CA	

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Cristobalite, respirable powder	1.07	14464-46-1
Hydroxyethylcellulose	1.03	9004-62-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary f	<u>irst aid measures</u>
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Date of issue/Date of revision	: 5/9/2024 Date of previous issue : 4/10/2024 Version : 4 2/12

Date of Issue/Date	of revision	5/9/2024	Date of previous issue	: 4/10/2024	version :4	2/
A6T354	A-100® Exterior Latex F Ultradeep Base	Flat			SHW-85-NA-GHS-CA	

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/e	effects, acute and delayed
Potential acute health effect	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Date of issue/Date of revision	: 5/9/2024 Date of previous issue : 4/10/2024 Version : 4 3/12
A6T354 A-100® Exterior I Ultradeep Base	atex Flat SHW-85-NA-GHS-CA

Section 5. Fire-fighting measures

Special protective : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/L	Date of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	4/12
A6T354	A-100® Exterior La	atex Flat			SHW-85-NA-GHS-CA	
	Ultradeep Base					

Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination. See Section 10 for
	incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Cristobalite, respirable powder	14464-46-1	 OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO₂+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 7/2023). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust
Hydroxyethylcellulose	9004-62-0	None.

Occupational exposure limits (Canada)

ngredient name	CAS #	Exposure limits
Cristobalite	14464-46-1	 CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2023). TWAEV: 0.05 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 3/2023). OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 0.05 mg/m³ 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction

Section 8. Exposure controls/personal protection

Ingredient name		CAS #	Exposure limits		
Cristobalite, respirable powo	ler	14464-46-1	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction		
Biological exposure indice	<u>s (United States)</u>				
No exposure indices known					
Biological exposure indice	s (Canada)				
No exposure indices known					
Biological exposure indice	s (Mexico)				
No exposure indices known					
··· ·· · · · · · · · · · · · · · · · ·					
Appropriate engineering controls Environmental exposure	local exhaust ventila airborne contaminar : This product conta	tion or other engi nts below any reco iins a componen	es, gas, vapor or mist, use process enclosures, neering controls to keep worker exposure to ommended or statutory limits. It that is either subject to a CEPA ministerial		
controls	Emissions from vent they comply with the cases, fume scrubbe	tilation or work pro requirements of ers, filters or engin	SNAC (Significant New Activity). Docess equipment should be checked to ensure environmental protection legislation. In some neering modifications to the process equipment is to acceptable levels.		
ndividual protection measure	<u>ures</u>				
Hygiene measures	eating, smoking and Appropriate techniqu	using the lavator ues should be use clothing before re	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. eusing. Ensure that eyewash stations and safety location.		
Eye/face protection	assessment indicate gases or dusts. If co	: Safety eyewear complying with an approved standard should be u assessment indicates this is necessary to avoid exposure to liquid gases or dusts. If contact is possible, the following protection sho the assessment indicates a higher degree of protection: safety glasses are approximately approx			
Skin protection					
Hand protection	worn at all times whe necessary. Conside during use that the g noted that the time to glove manufacturers	en handling chem ring the paramete loves are still reta o breakthrough fo s. In the case of r	s complying with an approved standard should be nical products if a risk assessment indicates this ers specified by the glove manufacturer, check aining their protective properties. It should be or any glove material may be different for differen nixtures, consisting of several substances, the be accurately estimated.		
Body protection		isks involved and	body should be selected based on the task beir should be approved by a specialist before		
Other skin protection		eing performed ar	nal skin protection measures should be selected nd the risks involved and should be approved by t.		
Respiratory protection	appropriate standard	d or certification.	exposure, select a respirator that meets the Respirators must be used according to a ure proper fitting, training, and other important		

Date of issue/Dat	te of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	6/12
A6T354	A-100® Exterior La Ultradeep Base	atex Flat			SHW-85-NA-GHS-CA	x

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Clear.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
	••••••
Flammability	: Not available.
· · · · · · · · · · · · · · · · · · ·	
Flammability Lower and upper explosion	: Not available.
Flammability Lower and upper explosion limit/flammability limit	Not available.Not available.
Flammability Lower and upper explosion limit/flammability limit Vapor pressure	Not available.Not available.2.3 kPa (17.5 mm Hg)

Media		Result
cold water		Partially soluble
Partition coefficient: n- : Not octanol/water		applicable.
Auto-ignition temperature : Not		available.
Decomposition temperature : Not		available.
Viscosity	: Kin	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not	applicable.
Heat of combustion	: 0.47	7 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date	of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	7/12
A6T354	A-100® Exterior Latex Ultradeep Base	Flat			SHW-85-NA-GHS-CA	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Cristobalite, respirable powder	+	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effectsEye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related	to the physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Date of issue	/Date of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	8/12
A6T354	A-100® Exterior L Ultradeep Base	atex Flat			SHW-85-NA-0	GHS-CA

Section 11. Toxicological information

	5
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	<u>ffects</u>
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical management of ta	

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Date of issue/Date of revision		: 5/9/2024
A6T354	A-100® Exterior La	itex Flat
	Ultradeep Base	

Date of previous issue

: 4/10/2024

Section 13. Disposal considerations

Disposal methods

: This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	•				
	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Multi-modal shipping descriptions are provided for informational purposes and do not Special precautions for user : consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

Date of issue/Date	of revision	: 5/9/2024	Date of previous issue	: 4/10/2024	Version : 4	10/12
A6T354	A-100® Exterior Latex Ultradeep Base	Flat			SHW-85-NA-GHS-CA	

Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
	Calculation method Calculation method

: 5/9/2024
: 5/9/2024
: 4/10/2024
: 4

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.