SAFETY DATA SHEET

151-8331

Section 1. Identification

Product name	: 950A Siliconized Acrylic Latex Caulk Clear	
Product code	: 151-8331	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of t	he substance or mixture and uses advised against	
Paint or paint related material.		
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115	
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada	
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	
Product Information Telephone Number	: US / Canada: 1-800-474-3794 Mexico: Not Available	
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	

Section 2. Hazards identification

Classification of the substance or mixture	: Not classified.		
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 5.1% (dermal), 5.1% (inhalation)		
GHS label elements			
Signal word	: No signal word.		
Hazard statements	: No known significant effects or critical hazards.		
Precautionary statements			
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.		
Prevention	: Not applicable.		
Response	: Not applicable.		
Storage	: Not applicable.		
Disposal	: Not applicable.		
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.		
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.		
Date of issue/Date of revision	: 2/5/2024 Date of previous issue : 9/13/2023 Version : 18 1/11		

151-8331 950A Siliconized Acrylic Latex Caulk Clear	IW-85-NA-GHS-CA	

Section 2. Hazards identification

Hazards not otherwise : None known. classified

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.
Identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Paraffinic Mineral Oil	5.05	8042-47-5
Fumed Amorphous Silica	2.36	112945-52-5
Hydroxyethylcellulose	1.1	9004-62-0
Light Aliphatic Hydrocarbon	0.44	64742-47-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Clear

Description of necess	<u>ary mst alu measures</u>
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms	/effects, acute and delayed		
Potential acute health eff	<u>ects</u>		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
<u>Over-exposure signs/syn</u>	<u>nptoms</u>		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Indication of immediate m	edical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist quantities have been ingested or inhaled. 	immediately if large	
Specific treatments	: No specific treatment.		
Date of issue/Date of revision	: 2/5/2024 Date of previous issue : 9/13/2023	Version : 18	2/11
151-8331 950A Siliconiz	ed Acrylic Latex Caulk	SHW-85-NA-GHS-CA	

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.		
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for co	ntainment and cleaning up		
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/13/2023	Version : 18	3/11
151-8331	950A Siliconized Acryli	c Latex Caulk			SHW-85-NA-GHS-CA	
	Clear					

Section 7. Handling and storage

Precautions for safe handling	L		
Protective measures : Put on appropriate personal protective equipment (see Section 8).			
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.		
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.		

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Paraffinic Mineral Oil	8042-47-5	OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Fumed Amorphous Silica	112945-52-5	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m ³ 10 hours.
Hydroxyethylcellulose Light Aliphatic Hydrocarbon	9004-62-0 64742-47-8	None. ACGIH TLV (United States, 1/2023). [Kerosene as total hydrocarbon vapor] Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.

Occupational exposure limits (Canada)

Ingredient name		CAS #	Exposure limits				
Paraffinic	Mineral Oil		8042-47-5	6/2022). [Oil m refined] TWA: 1 mg/m CA Alberta Pro [Oil mist, mine 8 hrs OEL: 5 r	ovincial (Canad	a, 6/2018 -orm: Mis	3).
Date of issue/L	Date of revision	: 2/5/2024	Date of previous issue	: 9/13/2023	Version	:18	4/11
51-8331	950A Siliconized Clear	Acrylic Latex Caulk			SHW-85-	NA-GHS-C	A

Section 8. Exposure controls/personal protection

· · ·	•	
Petroleum refining, hydrotreated light distillate	64742-47-8	CA British Columbia Provincial (Canada, 6/2022). [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures. TWA: 200 mg/m ³ , (as total hydrocarbon vapour) 8 hours. CA Alberta Provincial (Canada, 6/2018). [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin. 8 hrs OEL: 200 mg/m ³ , (as total hydrocarbon vapour) 8 hours. CA Ontario Provincial (Canada, 6/2019). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapour) 8 hours.

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Paraffinic Mineral Oil	8042-47-5	NOM-010-STPS-2014 (Mexico, 4/2016). [Highly refined mineral oils, mist, with the exception of cutting fluids] TWA: 5 mg/m ³ 8 hours. Form: mist

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering : controls Environmental exposure : controls	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

Date of issue/Date of revision : 2/5/2024 Date of previous issue : 9/13/2023 Version : 18 5/11 151-8331 950A Siliconized Acrylic Latex Caulk Clear SHW-85-NA-GHS-CA SHW-85-NA-GHS-CA

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>						
Physical state	: Liq	uid.				
Color	: Cle	ar.				
Odor	: No	t available.				
Odor threshold	: No	t available.				
рН	8.3					
Melting point/freezing point	: No	: Not available.				
Boiling point, initial boiling point, and boiling range	: 100	0°C (212°F)				
Flash point	: Clo	sed cup: Not applicable.				
Evaporation rate	: 0.0	9 (butyl acetate = 1)				
Flammability	: No	t available.				
Lower and upper explosion limit/flammability limit						
Vapor pressure	re : 2.3 kPa (17.5 mm Hg)					
Relative vapor density	: 1[/	[Air = 1]				
Relative density	: 1.0	: 1.04				
Solubility(ies)	:					
Media		Result				
cold water		Partially soluble				
Partition coefficient: n- : Not applicable. octanol/water						
Auto-ignition temperature : Not available.						
Decomposition temperature : Not available.						
Viscosity	: Ki	nematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight	: No	ot applicable.				
Heat of combustion	: 0.8	28 kJ/g				

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
I I	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Paraffinic Mineral Oil Fumed Amorphous Silica	LD50 Oral LD50 Oral		>5000 mg/kg 3160 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Fumed Amorphous Silica	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
Light Aliphatic Hydrocarbon	Category 3		Respiratory tract 🥄 irritation
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/13/2023	Version : 18	7/11
151-8331	950A Siliconized Acryli Clear	ic Latex Caulk			SHW-85-NA-GHS-CA	

Section 11. Toxicological information

Name		Route of exposure	Target organs
Light Aliphatic Hydrocarbon	Category 2	-	-

Aspiration hazard

Name	Result
	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate eff	ects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
Light Aliphatic Hydrocarbon	Acute LC50 2200 μg/l Fresh water	Fish - Lepomis macrochirus	4 days 🥄

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Date of issue/Date of rev	vision : 2/5/2024	4 Date of previous i	ssue : 9/13/202	3 Versio	on :18 9/11
151-8331 950A Clear	Siliconized Acrylic Latex Ca	ulk		SHW	85-NA-GHS-CA

Section 14. Transp	port information			
Special precautions for user	: Multi-modal shipping descri consider container sizes. Th mode of transport (sea, air, suitably for that mode of tran to shipment, and complianc of the person offering the pr dangerous goods must be to and on all actions in case of	e presence of a ship etc.), does not indica nsport. All packaging e with the applicable oduct for transport. F rained on all of the ris	pping description for ate that the product i must be reviewed f regulations is the so People loading and u sks deriving from the	a particular s packaged or suitability prior ole responsibility ınloading
Transport in bulk according to IMO instruments	: Not available.			
	Proper shipping name	: Not available.		

Section 15. Regulatory information

International	regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/13/2023	Version : 18	10/11
151-8331	950A Siliconized Acryli Clear	ic Latex Caulk			SHW-85-NA-GHS-CA	

Section 16. Other information

	Classification	Justification
Not classified.		
History		
Date of printing	: 2/5/2024	
Date of issue/Date of revision	: 2/5/2024	
Date of previous issue	: 9/13/2023	
Version	: 18	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification ar IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffic MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	cient of Pollution From Ships, 1973

✓ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of previous issue