ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Feb 19, 2024

59 00 [0364]

B25W25

PRODUCT NAME

PRODUCT NUMBER

PrepRite® Interior/Exterior Latex Block Filler, White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

B25W25 = | Acute | Chronic |

Product WeightSpecific GravityFLASH POINT13.48 lb/gal1.62N.A.

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Water 7732-18-5	N	N	N	N	31	50

Volatile Organic Compounds - U.S. EPA / Canada

,			
	B25W25		
	LB/Gal	g/L	
Coating Density	13.48	1615	
	By wt	By vol	
Total Volatiles	32.1%	52.4%	
Federally exempt solvents			
Water	30.6%	50.0%	
Organic Volatiles	1.5%	2.3%	
Percent Non-Volatile	67.9%	47.6%	
VOC Content	LB/Gal	g/L	
Total	0.20	24	
Less exempt solvents	0.40	48	
Of solids	0.42	51	
Of solids	0.02 lb/lb	0.02 kg/kg	
	By wt		
By wt LVP-VOC	0.0%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.03

Volatile Organic Compounds - California

	B25W25	
	LB/Gal	g/L
Coating Density	13.48	1615
	By wt	By vol
Total Volatiles	32.1%	52.4%
Exempt solvents		
Water	30.6%	50.0%
Organic Volatiles	1.5%	2.3%
Percent Non-Volatile	67.9%	47.6%
VOC Content	LB/Gal	g/L
Total	0.20	24
Less exempt solvents	0.40	48
Of solids	0.42	51
Of solids	0.02 lb/lb	0.02 kg/kg
	By wt	
By wt LVP-VOC	0.0%	·

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.03

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	B25W25	
	LB/Gal	g/L
Coating Density	13.48	1615
	By wt	By vol
Total Volatiles	32.1%	52.4%
Exempt solvents		
Water	30.6%	50.0%
Organic Volatiles	1.5%	2.3%
Percent Non-Volatile	67.9%	47.6%
VOC Content	LB/Gal	g/L
Total	0.20	24
Less exempt solvents	0.40	48
Of solids	0.42	51
Of solids	0.02 lb/lb	0.02 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	B25W25	
	By wt	By vol
Total Volatiles	31.7%	51.6%
VOC Content	LB/Gal	g/L
Total	0.14	17

Volatile Organic Compounds - EU Directive 2010/75/EU

	B25W25	
	By wt	By vol
Total Volatiles	31.7%	51.6%
VOC Content	LB/Gal	g/L
Total	0.14	17

Volatile Organic Compounds - Mexico

	B25W25	
	LB/Gal	g/L
Coating Density	13.48	1615
	By wt	By vol
Total Volatiles	32.1%	52.4%
Exempt solvents		
Water	30.6%	50.0%
Organic Volatiles	1.5%	2.3%
Percent Non-Volatile	67.9%	47.6%
VOC Content	LB/Gal	g/L
Total	0.20	24
Less exempt solvents	0.40	48
Of solids	0.42	51
Of solids	0.02 lb/lb	0.02 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	B25W25		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

8.71 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.