

SuperDeck® Deck Wash

640359915


**SHERWIN
WILLIAMS®**

CHARACTERISTICS

SuperDeck® Deck Wash is specifically designed for use on exterior wood and deck surfaces to help remove the discoloration that makes uncoated, weathered surfaces unsightly; and to prepare your deck for application of SuperDeck Stains. With Deck Wash, you can renew weathered surfaces by removing stains caused by mold, mildew, dirt, nails and other pollutants.

Where to use:

Use on decks and outdoor furniture made of pressure treated wood, cedar, pine, and most other woods.

Not recommended for use on previously painted surfaces.

This product is not recommended for redwood or teak.

This product is intended for exterior use only.

Coverage: 250 sq. ft. per gallon
Depending upon the condition and porosity of the wood.

pH: 11.7
Solvent: Water
Size: 1 gallon

6403-59915

V.O.C. (less exempt solvents):

less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 2.6 ± 2%
Weight Solids: 5.1 ± 2%
Weight per Gallon: 8.53 lbs
Flash Point: N.A.
Type: Sodium Hypochlorite

COMPLIANCE

As of 07/16/2020, Complies with:

| | |
|----------------------------|-----|
| OTC | Yes |
| OTC Phase II | Yes |
| SCAQMD | Yes |
| CARB | Yes |
| CARB SCM 2007 | Yes |
| Canada | Yes |
| LEED® v4 & v4.1 Emissions | No |
| LEED® v4 & v4.1 VOC | Yes |
| EPD-NSF® Certified | No |
| MIR-Manufacturer Inventory | No |
| MPI® | No |

APPLICATION

Use at full strength in a well ventilated area. **DO NOT MIX WITH ANY OTHER PRODUCT.**

Apply to the surface with a sprayer or plastic sprinkling can. After applying, let the product sit on the surface for 10 minutes (do not allow Deck Wash to remain on the surface for more than 15 minutes, as an uneven appearance may result). During this time, the product is working to remove the dirt and contamination embedded in the pores of the wood. For stubborn stains, it may be advantageous to scrub with a stiff brush or broom for best results. After 10 minutes, rinse the surface thoroughly with clean water. **Repeat the rinsing 2 or 3 times.** Thoroughly rinse the surface with fresh water from a hose, removing all residue. Any residue left on the surface may interfere with the drying or adhesion of topcoats. If topcoating is desired, wait at least 24 hours until the surface is completely dry before applying a product from the SuperDeck Deck Care Family.

APPLICATION TIPS

Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.

Thoroughly read and understand all the label cautions prior to using any cleaner.

Be sure that the cleaner is appropriate for the dirt-contamination.

Do not mix together any cleaning compounds containing bleach and ammonia.

Abrasive cleansers may damage a paint film, use very carefully.

Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions would be advised.

Before applying overall, test a sample area, rinse, and let dry to ensure that the results are to your satisfaction. Make sure the surface is completely dry prior to and during application. If the wood is previously damaged due to pressure washing or significant weathering has taken place, the surface may appear fuzzy after application.

SuperDeck™

Deck Wash

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Be sure the surface is free of any loose dirt and debris. Thoroughly wet plants and shrubs and cover to protect them from overspray. Uncover promptly after cleaning. Remove all deck furniture and decorative items. Do not allow **SuperDeck Deck Wash** to come into contact with finished or aluminum surfaces. Rinse immediately after use on metal to avoid pitting or discoloration. Do not allow **SuperDeck Deck Wash** to come into prolonged contact with clothing, carpet, or fabric, as damage may occur. For best results apply to dry wood.

Plan the application; for horizontal surfaces, work backwards so that you do not walk on the surface being treated. For vertical surfaces, work from the top down. Treat small areas one at a time.

Using the right cleaner often makes the cleaning easier. Prior to using **SuperDeck Deck Wash**, some general cleaning may be needed. Clean all surfaces completely with the appropriate cleaner based on the conditions. Rinse the surface completely and allow the surface to dry thoroughly.

SuperDeck® Deck Wash

- Mildew stain, Algae stain
- Weathered wood (bleaches wood)
- Gray wood (bleaches wood)

SuperDeck® Revive™

- Tannin Bleed, Nail stain
- Weathered wood (restores color)
- Gray wood (restores color), Mill Glaze

SuperDeck® Stain & Sealer Remover

- Weathered, gray wood
- Old Paint & Stain

SURFACE PREPARATION

Carefully follow all label instructions. Thoroughly rinse the surface to remove all residue and allow to thoroughly dry before coating.

- Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.
- Do not apply over sealed surfaces.
- To determine if the surface is sealed, test the absorbency by sprinkling water on it. If the water penetrates quickly, the surface is ready to finish. If the water beads up or does not penetrate, remove the coating-sealer and allow to dry. Test for absorbency again.
- **Failure to follow application and surface preparation guidelines may result in premature coating failure.**

Mildew: Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

CAUTIONS

This product must be applied outdoors to wood intended for exterior use only.

Not for interior use.

Storage: Protect from freezing. Do not store below 30°F

Wear rubber gloves and eye protection.

Before using, carefully read **CAUTIONS on label**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 07/16/2020 640359915 01 11
FRC,SP

CLEANUP INFORMATION

Rinse equipment and brushes with soap and water immediately after use.