

Product Lens

a materials health assessment

COMPANY AND PRODUCT INFO

Issued to	Sherwin-Williams			
For the Products	PrepRite ProBlock Interior/Exterior Latex Primer/Sealer – B51W600 Series *Assessment is limited to base formulas and does not include tint.			
Description	Assures uniform appearance of topcoats. Seals out solvent sensitive stains - tar, solvent based markers, etc. and minor dried water stains.			
Expiration	October 31, 2024 Assessor			



Qualifications

LEED BPDO Credit: Material Ingredients Option 1 Qualifies for as 1 product LEED BPDO Credit: Material Ingredients Option 2

MATERIALS / INGREDIENTS INFORMATION

Disclosure Level: 100 ppm 🔿 1000 ppm 🟈

The following table represents the top 100% of the material ingredient disclosure and ratings. For the full ingredient disclosure information, please see the table on the reverse side.

Materials	Result				
	Supply Chain/ MFG	Install	Use	End of Use	
Water					
Extender Pigments					
Titanium Dioxide	- I				
Acrylic Polymer					
Additives					
Other Polymers					

Go to https://spot.ul.com/ to view the full, detailed materials ingredient list

Sherwin-Williams

Other Achievements



Exposure Indicator

D = Dermal, Skin				
I = Inhalation, air				
O = Oral, mouth				

<1-(800) 474-3794>

*No Indicator means no potential exposure scenario identified

Color Ratings

-							
		Minimal or no hazard identified and/or potential exposure					
		Low or mild hazard identified and/or potential exposure					
		Moderate hazard identified and/or potential exposure					
		Problematic concern found. The combination of the hazard and potential exposure leads to some caution for some uses and/or applications.					
		Cannot be fully assessed due to either lack of complete formulation, or lack of toxicological information for one or more ingredients.					
		Highly problematic material containing one or more chemicals classified as CMR and having a plausible route of exposure.					





Product Lens a materials health assessment

Material	CAS Number	Role	%					Comment
				MFG	Install	Use	End of Use	
Water	7732-18-5	Solvent	40%-50%					
Extender Pigments	Proprietary	Extender Pigments	10%-25%					Manufacturer has provided evidence of no heavy metal contamination, and has guaranteed proper PPE and other technologies in place to limit worker exposure. Also includes materials with inhilation risks that have been mitigated by the use of proper PPE duing manufacturin.
Titanium Dioxide	13463-67-7	Pigment	10%-20%	1				Inhalation risk is mitigated duirng manufacturing with use of proper PPE
Acrylic Polymer	Proprietary	Resin/Polymer	10%-20%					Monomers are strong skin sensitizers. Manufacturer has guaranteed proper PPE to protect workers from skin contact.
Additives	Proprietary	Additives	0%-5%					Includes substances that are moderately hazardous to aquatic systems, so care should be take during manufacturing and installation to minimize direct exposure to natural environment/bodies of water. Also includes materials with chronic toxicity concerns mitigated by proper PPE during manufacturing.
Other Polymers	Proprietary	Resin/Polymer	0%-2%					Acceptable for use in all product phases

Low or mild hazard identified and/or potential exposure Moderate hazard identified and/or potential exposure

Problematic concern found. The combination of the hazard and potential exposure leads to some caution for some uses and/or applications.

Cannot be fully assessed due to either lack of complete formulation, or lack of toxicological information for one or more ingredients.

Highly problematic material containing one or more chemicals classified as CMR and having a plausible route of exposure.