# **SAFETY DATA SHEET**

B41W2651

# Section 1. Identification

Product name	: PROMAR® 200 Zero VOC Interior Latex Low Gloss Eg-Shel Extra White
Product code	: B41W2651
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	the substance or mixture and uses advised against
Paint or paint related material	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: The Sherwin-Williams Company 418 North Service Road East Oakville, Ontario L6H 5R2 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 1-800-474-3794 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

# Section 2. Hazards identification

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.

Date of issue/Date	e of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	1/11
B41W2651	PROMAR® 200 Z Extra White	ero VOC Interior La	tex Low Gloss Eg-Shel		SHW-85-	NA-GHS-CA	

# Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

# Substance/mixture: MixtureOther means of: Not available.identification

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	12.71	13463-67-7
Calcium Carbonate	6.2	1317-65-3
Heavy Paraffinic Oil	0.19	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary	<u>r first aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms	/effects, acute an	<u>id delayed</u>			
Potential acute health eff	ects				
Eye contact	: No known s	significant effects or critic	al hazards.		
Inhalation	: No known s	significant effects or critic	al hazards.		
Date of issue/Date of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version : 22.01	2/11
B41W2651 PROMAR® 20 Extra White	0 Zero VOC Interior La	tex Low Gloss Eg-Shel		SHW-85-NA-GHS-C	Α

# Section 4. First aid measures

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	No specific data.
Indication of immediate medic	al attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### Environmental precautions :

Date of issue/Date of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version : 22.01	3/11
B41W2651 PROMAR® 200 Z Extra White	ero VOC Interior La	tex Low Gloss Eg-Shel		SHW-85-NA-GHS-CA	

### Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

**Control parameters** 

**Occupational exposure limits (OSHA United States)** 

Ingredient n	ame		CAS #	Exposure lim	its		
Titanium Dio	xide	13463-67-7OSHA PEL (United States, 5/201 TWA: 15 mg/m³ 8 hours. Form: ACGIH TLV (United States, 1/20) TWA: 2.5 mg/m³ 8 hours. Form: fraction, finescale particles			orm: Total <b>1/2023).</b>		
Calcium Carl	oonate		1317-65-3	•	United States, m³ 8 hours. For		able
Date of issue/Dat	e of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	4/11
B41W2651	PROMAR® 200 2 Extra White	Zero VOC Interior La	tex Low Gloss Eg-Shel		SHW-85	-NA-GHS-CA	4

# Section 8. Exposure controls/personal protection

Heavy Paraffinic Oil	64742-65-0	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust <b>NIOSH REL (United States, 10/2020).</b> <b>[calcium carbonate]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total <b>OSHA PEL (United States, 5/2018). [Oil mist, mineral]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 1/2023).</b> <b>[Mineral Oil, pure, highly and severely refined]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction <b>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]</b> TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
----------------------	------------	--

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
None.		

#### **Biological exposure indices (United States)**

No exposure indices known.

#### Biological exposure indices (Canada)

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate e controls Environment controls		local exhau airborne co Emissions they compl cases, fum	rations generate dust, fu ust ventilation or other er ontaminants below any re from ventilation or work y with the requirements of le scrubbers, filters or en essary to reduce emissio	ngineering controls to ecommended or state process equipment s of environmental pro ugineering modification	<ul> <li>keep worker ex utory limits.</li> <li>should be check tection legislatic ons to the proce</li> </ul>	cposure to ed to ensu n. In some	re e
Individual pro	otection measures	2					
Hygiene me	asures :	eating, smo Appropriate Wash cont	ds, forearms and face the oking and using the lava e techniques should be u aminated clothing before re close to the workstatio	tory and at the end o used to remove poter e reusing. Ensure the	f the working pentially contamination	riod. Ited clothin	g.
Eye/face pro	otection	assessmer gases or d	wear complying with an a nt indicates this is necess usts. If contact is possib ment indicates a higher o	sary to avoid exposu le, the following prot	re to liquid splas ection should be	shes, mists worn, unl	,
Date of issue/Dat	e of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	5/11
B41W2651	PROMAR® 200 Zero Extra White	VOC Interior La	tex Low Gloss Eg-Shel		SHW-85-	NA-GHS-CA	

# Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

- top our un ou								
Physical state	:	Liqui	id.					
Color	:	White.						
Odor	:	Not a	Not available.					
Odor threshold	:	Not a	Not available.					
рН	:	9.2						
Melting point/freezing point	:	Not a	available.					
Boiling point, initial boiling point, and boiling range	:	100°	°C (212°F)					
Flash point	:	Clos	ed cup: Not applicable.					
Evaporation rate	:	0.09	(butyl acetate = 1)					
Flammability	:	: Not available.						
Lower and upper explosion limit/flammability limit	:	: Not available.						
Vapor pressure	:	: 2.3 kPa (17.5 mm Hg)						
Relative vapor density	:	: 1 [Air = 1]						
Relative density	:	1.35						
Solubility(ies)	:							
Media			Result					
cold water			Partially soluble					
Partition coefficient: n- octanol/water	:	Not a	applicable.					
Auto-ignition temperature	: Not available.							
Decomposition temperature	• : Not available.							
Viscosity	:	Kine	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)					
Molecular weight	۰.	Not	applicable.					

Date of issue/Date	of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	6/1
B41W2651	PROMAR® 200 Zero V Extra White	OC Interior Late	ex Low Gloss Eg-Shel		SHW-85-	NA-GHS-CA	

# Section 9. Physical and chemical properties

Heat of combustion : 1.219 kJ/g

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

### **Carcinogenicity**

#### Net evelleble

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Date of issue/Date	of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	7/11
B41W2651	PROMAR® 200 Zero \ Extra White	OC Interior Late	ex Low Gloss Eg-Shel		SHW-85-	NA-GHS-CA	

# Section 11. Toxicological information

Name		Route of exposure	Target organs
Calcium Carbonate	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.
Potential acute health effect	<u>:ts</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate eff	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ifects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity Acute toxicity estimates

Date of issue/Date	of revision	: 4/10/2024	Date of previous issue	: 3/26/2024	Version : 22.01	8/11
B41W2651	PROMAR® 200 Zero V Extra White	VOC Interior Lat	ex Low Gloss Eg-Shel		SHW-85-NA-GHS-CA	<b>x</b>

Not available.

# Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Date of issue/Date of rev	l vision : 4/10/20	D24 Date of previous	issue : 3/26/202	Ver	r <mark>sion :</mark> 22.01 9/1
341W2651 PRO	vision : 4/10/20 MAR® 200 Zero VOC Interi White				sion : 22.0 W-85-NA-G

Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precaution		consider container s mode of transport (s suitably for that mod to shipment, and co of the person offerin	izes. The presence ea, air, etc.), does le of transport. All p mpliance with the a g the product for tra ust be trained on al	of a shipping descrip not indicate that the p ackaging must be re pplicable regulations ansport. People loadi I of the risks deriving	product is packaged viewed for suitability prior is the sole responsibility

# Section 15. Regulatory information

#### International regulations

#### Montreal Protocol

Not listed.


#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	<ul> <li>Australia inventory (AIIC): Not determined.</li> <li>China inventory (IECSC): Not determined.</li> <li>Japan inventory (CSCL): Not determined.</li> <li>Japan inventory (ISHL): Not determined.</li> <li>Korea inventory (KECI): Not determined.</li> <li>New Zealand Inventory of Chemicals (NZIoC): Not determined.</li> <li>Philippines inventory (PICCS): Not determined.</li> <li>Taiwan Chemical Substances Inventory (TCSI): Not determined.</li> <li>Thailand inventory: Not determined.</li> </ul>
	Thailand inventory: Not determined.
	Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of issue/Date of revision		: 4/10/2024	Date of previous issue	: 3/26/2024	Version	: 22.01	10/11
B41W2651 PROMAR® 200 Zero VOC Interior Latex Low Gloss Eg-Shel Extra White				SHW-85-NA-GHS-CA			

# Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification			
CARCINOGENICITY - Cat	Calculation method			
History				
Date of printing	: 4/10/2024			
Date of issue/Date of revision	: 4/10/2024			
Date of previous issue	: 3/26/2024			
Version	: 22.01			
Key to abbreviations	IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffi MARPOL = International Convention for the Prevention	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals ATA = International Air Transport Association BC = International Air Transport Association BC = International Maritime Dangerous Goods ogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 Is modified by the Protocol of 1978. ("Marpol" = marine pollution) I/A = Not available GGG = Segregation Group		

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 3/26/2024