# **SAFETY DATA SHEET**

B53T1154

# Section 1. Identification

Product name	: PRO INDUSTRIAL <sup>™</sup> Waterbased Alkyd Urethane Semi-Gloss Ultradeep Base
Product code	: B53T1154
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

# Section 2. Hazards identification

Classification of the substance or mixture	: SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 9.6% (oral), 9.6% (dermal), 9.6% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes damage to organs through prolonged or repeated exposure. (lungs)
Precautionary statements	
Prevention	<ul> <li>Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.</li> </ul>
Response	: Get medical advice or attention if you feel unwell.
Storage	: Not applicable.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version	:14.02	1/11
B53T1154	PRO INDUSTRIAL™ V Ultradeep Base	Vaterbased Alky	yd Urethane Semi-Gloss		SHW-85-	NA-GHS-CA	

# Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

### CAS number/other identifiers

Ingredient name	% by weight	CAS number
Kaolin	9.61	1332-58-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

Description of necessary fir	<u>it aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

# Most important symptoms/effects, acute and delayed Potential acute health effects

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version	:14.02	2/11
B53T1154	PRO INDUSTRIAL™ V Ultradeep Base	Vaterbased Alky	/d Urethane Semi-Gloss		SHW-85-	NA-GHS-CA	

# Section 4. First aid measures

Eye contact	: No known significant effects or critical hazards.				
Inhalation	: No known significant effects or critical hazards.				
Skin contact	: No known significant effects or critical hazards.				
Ingestion	: No known significant effects or critical hazards.				
Over-exposure signs/symp	<u>otoms</u>				
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: No specific data.				
Ingestion	: No specific data.				
Indication of immediate me	dical attention and special treatment needed, if necessary				
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>				
Specific treatments	: No specific treatment.				
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.				

# See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	Personal precautions, protective equipment and emergency procedures						
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.						
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".						

### Environmental precautions :

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version : 14.02	3/11
B53T1154	PRO INDUSTRIAL™ V Ultradeep Base	Vaterbased Alky	/d Urethane Semi-Gloss		SHW-85-NA-GHS-CA	

# Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

# Precautions for safe handling

	•	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

## Occupational exposure limits (OSHA United States)

Ingredient name CAS # Exposure limits				
Kaolin	1332-58-7	ACGIH TLV (United States, 1/2023). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dus		
Date of issue/Date of revision :	19/2024 Date of previous issue	: 2/7/2024 Version : 14.02 4/11		
53T1154 PRO INDUSTRIAL™ Wa Ultradeep Base	rbased Alkyd Urethane Semi-Gloss	SHW-85-NA-GHS-CA		

# Section 8. Exposure controls/personal protection

# Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Kaolin	1332-58-7	<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 4 mg/m<sup>3</sup> 15 minutes. Form: respirable fraction TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> <li>CA British Columbia Provincial (Canada, 6/2022). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica.</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> </ul>
2-Ethylhexanol	104-76-7	ACGIH TLV (United States, 1/2023). TWA: 5 ppm 8 hours.

### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
None.		

## **Biological exposure indices (United States)**

No exposure indices known.

### Biological exposure indices (Canada)

No exposure indices known.

### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version	:14.02	5/11
B53T1154	PRO INDUSTRIAL™ V Ultradeep Base	/aterbased Alky	/d Urethane Semi-Gloss		SHW-85-	NA-GHS-CA	

showers are close to the workstation location.

# Section 8. Exposure controls/personal protection

	• •
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### **Appearance**

<u>nppourunoo</u>				
Physical state	: Liqu	ıid.		
Color	: Clea	ar.		
Odor	: Not	available.		
Odor threshold	: Not	available.		
рН	: 8.5			
Melting point/freezing point	: Not	available.		
Boiling point, initial boiling point, and boiling range	: 100	°C (212°F)		
Flash point	: Clos	sed cup: Not applicable.		
Evaporation rate	: 0.09	9 (butyl acetate = 1)		
Flammability	: Not	available.		
Lower and upper explosion limit/flammability limit	: Not	available.		
Vapor pressure	: 2.3	kPa (17.5 mm Hg)		
Relative vapor density	: 1[A	ir = 1]		
Relative density	: 1.12	2		
Solubility(ies)	:			
Media		Result		1
cold water		Partially soluble		1
Partition coefficient: n- octanol/water	: Not	applicable.		1
Auto-ignition temperature	: Not	available.		
Date of issue/Date of revision	: 4/	19/2024         Date of previous issue         : 2/7/2024	Version : 14.02	6/11
B53T1154 PRO INDUSTRIA Ultradeep Base	L™ Wateı	based Alkyd Urethane Semi-Gloss	SHW-85-NA-GHS-CA	

# Section 9. Physical and chemical properties

Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not applicable.
Heat of combustion	: 0.382 kJ/g

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

Acute toxicity

Not available.

### Irritation/Corrosion

Not available.

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

## **Carcinogenicity**

Not available.

## Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Kaolin	Category 1	inhalation	lungs

### Aspiration hazard

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version : 14.02	7/11
B53T1154	PRO INDUSTRIAL™ \ Ultradeep Base	Vaterbased Alk	yd Urethane Semi-Gloss		SHW-85-NA-GHS-CA	

# Section 11. Toxicological information

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effect	<u>ts</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	÷	No known significant effects or critical hazards.
Skin contact	÷	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics					
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: No specific data.				
Ingestion	: No specific data.				

Delayed and immediate eff	ects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

# Section 12. Ecological information

# **Toxicity**

Not available.

# Persistence and degradability Not available. Bioaccumulative potential Not available. Mobility in soil Soil/water partition : Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport informatio
----------------------------------

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Date of issue/Date of revision       : 4/19/2024       Date of previous issue       : 2/7/2024       Version       : 14.02       9/11         B53T1154       PRO INDUSTRIAL™ Waterbased Alkyd Urethane Semi-Gloss       SHW-85-NA-GHS-CA       9/11         Ultradeep Base       Ultradeep Base       SHW-85-NA-GHS-CA       9/11					

port information		1	
consider container sizes. T mode of transport (sea, air suitably for that mode of tra to shipment, and complian of the person offering the p	he presence of a ship , etc.), does not indica ansport. All packaging ce with the applicable product for transport.	oping description for ate that the product i g must be reviewed f regulations is the so People loading and u	a particular s packaged for suitability prior ble responsibility unloading
: Not available.	of entergency situation	13.	
Proper shipping name	: Not available.		
	<ul> <li>Multi-modal shipping descr consider container sizes. T mode of transport (sea, air suitably for that mode of tra to shipment, and complian of the person offering the p dangerous goods must be and on all actions in case of Not available.</li> </ul>	<ul> <li>Multi-modal shipping descriptions are provided f consider container sizes. The presence of a ship mode of transport (sea, air, etc.), does not indica suitably for that mode of transport. All packaging to shipment, and compliance with the applicable of the person offering the product for transport. If dangerous goods must be trained on all of the ri and on all actions in case of emergency situation</li> <li>Not available.</li> </ul>	<ul> <li>Multi-modal shipping descriptions are provided for informational purple consider container sizes. The presence of a shipping description for mode of transport (sea, air, etc.), does not indicate that the product i suitably for that mode of transport. All packaging must be reviewed f to shipment, and compliance with the applicable regulations is the set of the person offering the product for transport. People loading and u dangerous goods must be trained on all of the risks deriving from the and on all actions in case of emergency situations.</li> <li>Not available.</li> </ul>

# International regulations

Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

# Section 16. Other information

## Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/7/2024	Version	:14.02	10/11
B53T1154	PRO INDUSTRIAL™ W Ultradeep Base	/aterbased Alky	d Urethane Semi-Gloss		SHW-85-I	NA-GHS-CA	

# Section 16. Other information

Classification Justification						
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1         Calculation method						
<u>History</u>						
Date of printing	: 4/19/2024					
Date of issue/Date of revision	: 4/19/2024					
Date of previous issue	: 2/7/2024					
Version	: 14.02					
Key to abbreviations	<ul> <li>14.02</li> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>					

✓ Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.