

All Surface Enamel

Interior-Exterior Latex Satin

A41-1300 Series


**SHERWIN
WILLIAMS.**

CHARACTERISTICS

All Surface Enamel is designed for use on interior and exterior wood, metal, drywall, and other surfaces.

This high quality coating provides excellent resistance to weather and sunlight, maintaining its gloss and color. The exceptional durability allows it to be used on doors, trim, windows, and other hard wear areas.

Interior & Exterior for use on these surfaces:

- Aluminum • Drywall • Steel • Cement • Wood
- Masonry • Concrete • Plaster • Galvanized

Color: Many Colors
To optimize hide and color development, always use the recommended P-Shade primer.

Coverage: 350-400 sq. ft. per gallon
@ 4.0 mils wet 1.7 mils dry

Drying Time, @ 77° F, 50% RH:

Touch: 1 Hour
Recoat: 4 Hours
Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish: 10-20 units @ 60°

Tinting with CCE:

Base:	oz. per gallon:	Strength:
Extra White	0-6	SherColor
Deep Base	6-12	SherColor
Ultradeep Base	10-12	SherColor

Package black available.

White A41W01351

(may vary by color)

V.O.C. (less exempt solvents):

Less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 42 ±2%

Weight Solids: 55 ±2%

Weight per Gallon: 10.61 lbs

Flash Point: N.A.

Vehicle Type: Acrylic

Shelf Life: 36 months, unopened

COMPLIANCE

As of 10/17/2023, Complies with:

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	Yes
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	No

APPLICATION

Apply at temperatures above 50°F.

No reduction necessary.

Brush:

Use a nylon-polyester brush.

Roller:

Use a 1/4-3/4 synthetic nap cover.

For specific brushes and rollers, please refer to our Brush and Roller Guide.

Spray—Airless:

Pressure 1500 p.s.i.
Tip .017-.021 inch

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

SPECIFICATIONS

Aluminum:

2 coats All Surface Latex Enamel

Drywall, interior:

1 coat Premium Wall & Wood Primer
2 coats All Surface Latex Enamel

Galvanized Steel:

2 coats All Surface Latex Enamel

Masonry, Concrete, Cement, Block:

1 coat Conflex Block Filler (optional)
Or Loxon Concrete and Masonry Primer
2 coats All Surface Latex Enamel

Plaster:

1 coat Loxon Concrete and Masonry Primer
2 coats All Surface Latex Enamel

Steel:

1 coat All Surface Enamel Latex Primer
2 coats All Surface Latex Enamel

Wood, interior:

1 coat Premium Wall & Wood Primer
2 coats All Surface Latex Enamel

Wood, exterior:

1 coat Exterior Latex Wood Primer
2 coats All Surface Latex Enamel

The systems listed above are representative of the product's use, other systems may be appropriate.

All Surface Enamel

Interior-Exterior Latex Satin

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Aluminum and Galvanized Steel: Wash to remove any oil, grease, or other surface contamination using a water-based cleaner-degreaser. Remove all corrosion with sandpaper, steel wool, or other abrading method.

Caulking: Exterior gaps between windows, doors, trim, and other through-wall openings; and interior gaps between walls, ceilings, crown moldings, and other trim can be filled with the appropriate caulk after priming the surface.

Drywall: Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block: All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete and Masonry Primer.

SURFACE PREPARATION

Mildew: Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts clean water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with clean water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

Plaster: Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Steel: Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

Wood: Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

CAUTIONS

Protect from freezing.

Not for use on roofs, floors, or decks.

Do not use colorants formulated for interior use only on exterior surfaces.

Before using, carefully read **CAUTIONS** on label.

CRYSTALLINE SILICA Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 10/16/2023 **A41W01351** 27 33
SP

CLEANUP INFORMATION

Clean spills, spatters, hands, and tools immediately after use with soap and clean warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.