SAFETY DATA SHEET

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Section 1. Identification

Product code : K45W1151

GHS product identifier : PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel

Extra White

Product use : Industrial applications, Used by spraying.

Material uses : Paint or paint related material.

Details of the supplier of the safety data sheet

Mfg. in the U.S.A. and exported by: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

Imported by:

Sherwin Williams Asia Pacific

Building 11, Shibei One Center, No1401 Jiangchang

Road

Jing'an District, Shanghai 200436, China

Phone: +86 21 61937965 regulatory.asia@sherwin.com

Supplier Telephone number : (216) 566-2902

e-mail address of person

responsible for this SDS

: MSDS@sherwin.com

Emergency telephone number (with hours of

operation)

: 400-6267911 (24/7)

Hours of operation : Emergency contact available 24 hours a day

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Emergency overview

Liquid.

White.

Causes mild skin irritation.

May cause cancer.

Toxic to aquatic life.

None known. Please refer to the SDS for additional information.

IF exposed or concerned: Get medical advice or attention. If skin irritation occurs:

Get medical advice or attention.

See Section 12 for environmental precautions.

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 1/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 2. Hazards identification

Classification of the : SKIN CORROSION/IRRITATION - Category 3

substance or mixture CARCINOGENICITY - Category 1A

AQUATIC HAZARD (ACUTE) - Category 2

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : Causes mild skin irritation.

May cause cancer. Toxic to aquatic life.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection. Avoid release to the environment.

Response: IF exposed or concerned: Get medical advice or attention. If skin irritation occurs:

Get medical advice or attention.

Storage: Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Physical and chemical

hazards

: No known significant effects or critical hazards.

Health hazards: Causes mild skin irritation. May cause cancer.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 2/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 2. Hazards identification

Environmental hazards: Toxic to aquatic life.

Other hazards which do not result in classification

: None known. Please refer to the SDS for additional information.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Hazardous ingredients

Ingredient name	%	CAS number	EC number	Hazard classification
Titanium Dioxide Cristobalite, respirable powder Ammonium Hydroxide	≥10 - ≤25 <1 ≤0.3	13463-67-7 14464-46-1 1336-21-6	236-675-5 238-455-4 215-647-6	H316, H351 H350, H372 H302, H314, H318, H335, H400, H412
3-Iodo-2-propynyl Butyl Carbamate	<0.1	55406-53-6	259-627-5	H302, H317, H318, H331, H372, H400, H410
Zinc Pyrithione	<0.01	13463-41-7	236-671-3	H301, H310 + H330, H318, H360, H360D, H372, H400, H410

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediatel

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least

10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 3/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.

Skin contact: Causes mild skin irritation.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO₂, powders, water spray or mist.

Unsuitable extinguishing

media

: Do not use water jet.

Date of issue/Date of revision: 2024/04/25.Date of previous issue: 2024/04/10.Version: 2.064/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eq-Shel - Extra White

Section 5. Fire-fighting measures

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: metal oxide/oxides

Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not

Date of issue/Date of revision : 2024/04/10. : 2024/04/25. Date of previous issue Version: 2.06 5/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 7. Handling and storage

Advice on general occupational hygiene reuse container.

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Store above 5°C (42°F) Protect from frost.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium Dioxide	GBZ 2.1 (China, 11/2022).
	PC-TWA: 8 mg/m ³ 8 hours. Form: dust
Cristobalite, respirable powder	ACGIH TLV (United States, 1/2023).
·	[Silica, crystalline]
	TWA: 0.025 mg/m ³ 8 hours. Form:
	Respirable fraction
ammonia (more than 10%)	GBZ 2.1 (China, 11/2022). [Ammonia]
,	PC-TWA: 20 mg/m³ 8 hours.
	PC-STEL: 30 mg/m³ 15 minutes.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

: 2024/04/10.

safety showers are close to the workstation location.

Eye/face protection

Date of issue/Date of revision

Skin protection

: Use safety eyewear designed to protect against splash of liquids.

Hand protection : Wear suitable gloves tested to EN374.

Gloves

: 2024/04/25. Date of previous issue

SHW-A4-AP-GH432-CN

Version : 2.06

6/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 8. Exposure controls/personal protection

Short Term Exposure less than 10 minutes Continuous use Nitrile gloves.

Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time).

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection: Personnel should wear protective clothing.

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.
Color : White.
Odor : Paint

Odor threshold : Not available.

pH : 9.2

Melting point/freezing point : Not available.

Boiling point, initial boiling : 100°C (212°F)

point, and boiling range

Flash point : Closed cup: Not applicable.

Evaporation rate : 0.09 (butyl acetate = 1)

Lower and upper explosion limit/flammability limit

: Not available.

Vapor pressure : 2.3 kPa (17.5 mm Hg)

Relative vapor density : 1 [Air = 1] **Relative density** : 1.27

Solubility(ies) :

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 7/14

K45W1151 PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 9. Physical and chemical properties

 Media
 Result

 cold water
 Partially soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

VOC content : 4 g/L **Heat of combustion** : 1.532 kJ/g

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

: Avoid high temperature.

Incompatible materials: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ammonia (more than 10%)	LD50 Oral	Rat	350 mg/kg	-
3-iodo-2-propynyl	LD50 Oral	Rat	1470 mg/kg	-
butylcarbamate				
Zinc Pyrithione	LC50 Inhalation Vapor	Rat	140 mg/m ³	4 hours
-	LD50 Dermal	Rabbit	100 mg/kg	-
	LD50 Oral	Rat	177 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
ammonia (more than 10%)	Eyes - Severe irritant	Rabbit	-	ug I 0.5 minutes	-
	Eyes - Severe irritant	Rabbit	-	1 mg 250 ug	-

Sensitization

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 8/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 11. Toxicological information

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	IARC
Titanium Dioxide	2B
Cristobalite, respirable powder	1

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	' ' ' ' ' ' '	Route of exposure	Target organs
ammonia (more than 10%)	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract
3-iodo-2-propynyl butylcarbamate	Category 1	-	larynx
Zinc Pyrithione	Category 1	-	-

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Causes mild skin irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 9/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: No known significant effects or critical hazards.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
ammonia (more than 10%)	Acute LC50 37 ppm Fresh water	Fish - <i>Gambusia affinis</i> - Adult	96 hours
3-iodo-2-propynyl butylcarbamate	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
-	Acute LC50 40 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 67 μg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
Zinc Pyrithione	Acute EC50 0.51 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Acute EC50 38 μg/l Fresh water	Crustaceans - Ilyocypris dentifera	48 hours
	Acute EC50 8.25 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 0.36 μg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Chronic NOEC 2.7 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	21 days

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 10/14

SHW-A4-AP-GH432-CN

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 12. Ecological information

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Zinc Pyrithione	-	11	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Do not incinerate closed container. Incinerate in a licensed, high-temperature, hazardous-waste incinerator.

Section 14. Transport information

	China	ADR	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport Hazard Class(es)/Label(s)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards/Marine pollutant	No.	No.	No.	No.

Additional information

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 11/14

PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Incompatible materials : No specific data.

Transport in bulk according: Not available.

to IMO instruments

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Section 15. Regulatory information

National inventory

: Australia inventory (AIIC): Not determined.

Canada inventory: Not determined.

China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory: Not determined.

Mexico inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined. Russian Federation inventory: Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

United States inventory (TSCA 8b): Not determined.

Vietnam inventory: Not determined.

List of Goods banned for Importing

None of the components are listed.

Drug Precursors Requiring an Import/Export License

None of the components are listed.

Inventory of Hazardous Chemicals

None of the components are listed.

List of Explosive Precursors

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 12/14

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

K45W1151 PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 15. Regulatory information

Ingredient name	CAS number	Status	Reference number
	7631-99-4	Listed	2.1
	10377-60-3	Listed	2.4

List of Goods banned for Exporting

None of the components are listed.

List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

Catalogue and classification of drug precursor chemicals

Category	Ingredient name	%	Status
Category 3	sulfuric acid	≤0.1	Listed

Inventory of Highly Toxic Articles

None of the components are listed.

Catalogue of Hazardous Chemicals of Priority Management

Listed

Listed

Listed

China MEE12 Registration number

$D \wedge \alpha$	istratio	n niim	hor
Neu	เธเนสเเน	nı mum	IDEI

T-181529

T-141288

T-141290

T-130576

Section 16. Other information

History

Date of printing : 2024/04/25. **Date of issue/Date of** : 2024/04/25.

revision

Date of previous issue : 2024/04/10.

Version : 2.06

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

Procedure used to derive the classification

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 13/14

K45W1151 PRO INDUSTRIAL™ Pre-Catalyzed Waterbased Epoxy Eg-Shel - Extra White

Section 16. Other information

Classification	Justification
SKIN CORROSION/IRRITATION - Category 3	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
AQUATIC HAZARD (ACUTE) - Category 2	Calculation method

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Full text of classifications

[CLP/GHS]

: SKIN CORROSION/IRRITATION - Category 3

CARCINOGENICITY - Category 1A

AQUATIC HAZARD (ACUTE) - Category 2

Full text of abbreviated H

statements

: H316 - Causes mild skin irritation.

H350 - May cause cancer.

H401 - Toxic to aquatic life.

Precautionary statements

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

P308 + P313 - IF exposed or concerned: Get medical advice or attention. P332 + P313 - If skin irritation occurs: Get medical advice or attention.

P405 - Store locked up.

P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

V Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 2024/04/25. Date of previous issue : 2024/04/10. Version : 2.06 14/14