# **SAFETY DATA SHEET**

B41W1951

## Section 1. Identification

| Product name                                 | : PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel<br>Low Gloss Extra White  |
|--|--|
| Product code                                 | : B41W1951   |
| Other means of<br>identification             | : Not available.   |
| Product type                                 | : Liquid.  |
| Relevant identified uses of t                | he substance or mixture and uses advised against   |
| Paint or paint related material.             |  |
| Manufacture                                  |  |
| Manufacturer                                 | : THE SHERWIN-WILLIAMS COMPANY<br>101 W. Prospect Avenue<br>Cleveland, OH 44115                                    |
| National contact                             | : The Sherwin-Williams Company<br>418 North Service Road East<br>Oakville, Ontario L6H 5R2 Canada                  |
| Emergency telephone                          | : US / Canada: (800) 424-9300  |
| number of the company                        | Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year                                  |
| Product Information<br>Telephone Number      | : US / Canada: 1-800-474-3794<br>Mexico: Not Available   |
| Transportation Emergency<br>Telephone Number | : US / Canada: (800) 424-9300<br>Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year |

## Section 2. Hazards identification

| Classification of the substance or mixture | : CARCINOGENICITY - Category 2  |
|--|---|
| GHS label elements                         |   |
| Hazard pictograms                          | :   |
|  |   |
|  |   |
| Signal word                                | : Warning   |
| Hazard statements                          | : Suspected of causing cancer.  |
| Precautionary statements                   |   |
| General                                    | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.   |
| Prevention                                 | • Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. |
| Response                                   | : IF exposed or concerned: Get medical advice or attention.   |
| Storage                                    | : Store locked up.  |

| Date of issue/Date                               | e of revision | : 4/25/2024 | Date of previous issue | : 4/10/2024 | Version | :16.03    | 1/12 |
|--|---------------|-------------|------------------------|-------------|---------|-----------|------|
| B41W1951 PROMAR® 200 HP 2<br>Low Gloss Extra Whi |               |             | r Acrylic Eg-Shel      |             | SHW-85- | NA-GHS-CA |      |

## Section 2. Hazards identification

| Disposal                         | : Dispose of contents and container in accordance with all local, regional, national and international regulations.                               |
|----------------------------------|---|
| Supplemental label<br>elements   | WARNING: This product contains chemicals known to the State of California to cause<br>cancer and birth defects or other reproductive harm.        |
|                                  | This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). |
|                                  | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.      |
| Hazards not otherwise classified | : None known.   |

## Section 3. Composition/information on ingredients

| Substance/mixture             | : Mixture        |
|-------------------------------|------------------|
| Other means of identification | : Not available. |
| lucilition                    |                  |

### CAS number/other identifiers

| Ingredient name      | % by weight | CAS number |
|----------------------|-------------|------------|
| Titanium Dioxide     | 14.11       | 13463-67-7 |
| Heavy Paraffinic Oil | 0.25        | 64742-65-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

| Description of necessary f   | i <mark>rst</mark> a  | id measures          |   |             |         |        |                       |
|--|---|----------------------|---|-------------|---------|--------|-----------------------|
| Eye contact  | :   | eyelids. Ch          | / flush eyes with plenty c<br>eck for and remove any<br>et medical attention. |             |         |        |                       |
| Inhalation       : Remove victim to fresh air and keep at rest in a position comfortable for breat not breathing, if breathing is irregular or if respiratory arrest occurs, provide a respiration or oxygen by trained personnel. It may be dangerous to the personid to give mouth-to-mouth resuscitation. Get medical attention. If unconscient in recovery position and get medical attention immediately. Maintain an ope Loosen tight clothing such as a collar, tie, belt or waistband. |   |                      |   |             |         |        | al<br>viding<br>blace |
| Skin contact   | : Flush contaminated skin with plenty of water. Remove contaminated clothing shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wa before reuse. Clean shoes thoroughly before reuse. |                      |   |             |         |        |                       |
| Ingestion  |   |                      |   |             |         |        |                       |
| Most important symptoms  | /effec  | <u>cts, acute an</u> | d delayed   |             |         |        |                       |
| Potential acute health eff   | ects  |                      |   |             |         |        |                       |
| Eye contact  | :   | No known s           | ignificant effects or critic  | al hazards. |         |        |                       |
| Date of issue/Date of revision   |   | : 4/25/2024          | Date of previous issue  | : 4/10/2024 | Version | :16.03 | 2/12                  |

| Date of Issue/Date | of revision                                | 4/25/2024 | Date of previous issue | : 4/10/2024 | version | : 16.03   | 2/1 |
|--------------------|--|-----------|------------------------|-------------|---------|-----------|-----|
| B41W1951           | PROMAR® 200 HP Ze<br>Low Gloss Extra White |           | Acrylic Eg-Shel        |             | SHW-85- | NA-GHS-CA |     |
|                    |  |           |                        |             |         |           |     |

## Section 4. First aid measures

| Inhalation                 | : No known significant effects or critical hazards.  |  |  |  |  |  |
|----------------------------|--|--|--|--|--|--|
| Skin contact               | : No known significant effects or critical hazards.  |  |  |  |  |  |
| Ingestion                  | : No known significant effects or critical hazards.  |  |  |  |  |  |
| Over-exposure signs/sym    | <u>ptoms</u>   |  |  |  |  |  |
| Eye contact                | : No specific data.  |  |  |  |  |  |
| Inhalation                 | : No specific data.  |  |  |  |  |  |
| Skin contact               | : No specific data.  |  |  |  |  |  |
| Ingestion                  | lo specific data.  |  |  |  |  |  |
| Indication of immediate me | dical attention and special treatment needed, if necessary   |  |  |  |  |  |
| Notes to physician         | <ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large<br/>quantities have been ingested or inhaled.</li> </ul>                          |  |  |  |  |  |
| Specific treatments        | : No specific treatment.   |  |  |  |  |  |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |  |  |  |  |  |

## See toxicological information (Section 11)

## Section 5. Fire-fighting measures

| Extinguishing media                            |   |
|--|---|
| Suitable extinguishing media                   | : Use an extinguishing agent suitable for the surrounding fire.   |
| Unsuitable extinguishing media                 | : None known.   |
| Specific hazards arising from the chemical     | : In a fire or if heated, a pressure increase will occur and the container may burst.   |
| Hazardous thermal decomposition products       | : Decomposition products may include the following materials:<br>carbon dioxide<br>carbon monoxide<br>metal oxide/oxides  |
| Special protective actions for fire-fighters   | <ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if<br/>there is a fire. No action shall be taken involving any personal risk or without suitable<br/>training.</li> </ul> |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.   |

## Section 6. Accidental release measures

| Personal precautions, protect  | ive equipment and emergency procedures   |
|--------------------------------|--|
| For non-emergency<br>personnel | : No action shall be taken involving any personal risk or without suitable training.<br>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from<br>entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.<br>Provide adequate ventilation. Wear appropriate respirator when ventilation is<br>inadequate. Put on appropriate personal protective equipment. |
| For emergency responders       | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".  |

#### Environmental precautions :

| Date of issue/Date | of revision                                | : 4/25/2024 | Date of previous issue | : 4/10/2024 | Version | :16.03    | 3/12 |
|--------------------|--|-------------|------------------------|-------------|---------|-----------|------|
| B41W1951           | PROMAR® 200 HP Ze<br>Low Gloss Extra White |             | Acrylic Eg-Shel        |             | SHW-85- | NA-GHS-CA |      |

## Section 6. Accidental release measures

## This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Largo spill | <ul> <li>Stop leak if without risk. Move containers from spill area. Approach release from</li> </ul>   |

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

| Precautions for safe handling                                      | 9  |
|--|--|
| Protective measures  | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure -<br>obtain special instructions before use. Do not handle until all safety precautions have<br>been read and understood. Do not get in eyes or on skin or clothing. Do not ingest.<br>Avoid breathing vapor or mist. If during normal use the material presents a respiratory<br>hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the<br>original container or an approved alternative made from a compatible material, kept<br>tightly closed when not in use. Empty containers retain product residue and can be<br>hazardous. Do not reuse container. |
| Advice on general occupational hygiene                             | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.  |
| Conditions for safe storage,<br>including any<br>incompatibilities | : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.  |

## Section 8. Exposure controls/personal protection

<u>Control parameters</u> Occupational exposure limits (OSHA United States)

## Section 8. Exposure controls/personal protection

| Ingredient name      | CAS #      | Exposure limits  |
|----------------------|------------|--|
| Titanium Dioxide     | 13463-67-7 | OSHA PEL (United States, 5/2018).<br>TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust<br>ACGIH TLV (United States, 1/2023).<br>TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable<br>fraction, finescale particles  |
| Heavy Paraffinic Oil | 64742-65-0 | OSHA PEL (United States, 5/2018). [Oil<br>mist, mineral]<br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br>ACGIH TLV (United States, 1/2023).<br>[Mineral Oil, pure, highly and severely<br>refined]<br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable<br>fraction<br>NIOSH REL (United States, 10/2020). [OIL<br>MIST MINERAL]<br>TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |

#### Occupational exposure limits (Canada)

| Ingredient name | CAS # | Exposure limits |
|-----------------|-------|-----------------|
| None.           |       |                 |

#### **Occupational exposure limits (Mexico)**

| Ingredient name CA | CAS # | Exposure limits |
|--------------------|-------|-----------------|
| None.              |       |                 |

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

Low Gloss Extra White

No exposure indices known.

| Appropriate engineering :<br>controls | If user operations generate dust, fumes, gas, vapor or mist, use process enclosures,<br>local exhaust ventilation or other engineering controls to keep worker exposure to<br>airborne contaminants below any recommended or statutory limits.  |
|---------------------------------------|---|
| Environmental exposure : controls     | This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).   |
|                                       | Emissions from ventilation or work process equipment should be checked to ensure<br>they comply with the requirements of environmental protection legislation. In some<br>cases, fume scrubbers, filters or engineering modifications to the process equipment<br>will be necessary to reduce emissions to acceptable levels.                 |
| Individual protection measures        |   |
| Hygiene measures :                    | Wash hands, forearms and face thoroughly after handling chemical products, before<br>eating, smoking and using the lavatory and at the end of the working period.<br>Appropriate techniques should be used to remove potentially contaminated clothing.<br>Wash contaminated clothing before reusing. Ensure that eyewash stations and safety |

| Date of issue/D | ate of revision | : 4/25/2024         | Date of previous issue | : 4/10/2024 | Version : 16.03  | 5/12 |
|-----------------|-----------------|---------------------|------------------------|-------------|------------------|------|
| B41W1951        | PROMAR® 200 H   | IP Zero VOC Interio | r Acrylic Eg-Shel      |             | SHW-85-NA-GHS-CA | 4    |

showers are close to the workstation location.

## Section 8. Exposure controls/personal protection

|                        | • •  |
|------------------------|--|
| Eye/face protection    | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.  |
| Skin protection        |  |
| Hand protection        | : Chemical-resistant, impervious gloves complying with an approved standard should be<br>worn at all times when handling chemical products if a risk assessment indicates this is<br>necessary. Considering the parameters specified by the glove manufacturer, check<br>during use that the gloves are still retaining their protective properties. It should be<br>noted that the time to breakthrough for any glove material may be different for different<br>glove manufacturers. In the case of mixtures, consisting of several substances, the<br>protection time of the gloves cannot be accurately estimated. |
| Body protection        | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| Other skin protection  | : Appropriate footwear and any additional skin protection measures should be selected<br>based on the task being performed and the risks involved and should be approved by a<br>specialist before handling this product.  |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.   |

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

| Odor threshold       :       Not available.         pH       :       8.8         Melting point/freezing point       :       Not available.         Boiling point, initial boiling       :       100°C (212°F)         point, and boiling range       :       Closed cup: Not applicable.         Evaporation rate       :       0.09 (butyl acetate = 1)         Flammability       :       Not available.         Lower and upper explosion       :       Not available.         Lower and upper explosion       :       Not available.         Imit/fammability limit       :       Not available.         Vapor pressure       :       2.3 kPa (17.5 mm Hg)         Relative density       :       1.4ir = 1]         Relative density       :       1.3         Solubility(ies)       :       .         Partition coefficient: n-       :       Not soluble         Partition coefficient: n-       :       Not available.         cotamol/water       :       Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : :16.03       6/12  | Appearance  |                                     |                                |             |                      |  |
|--|---|-------------------------------------|--------------------------------|-------------|----------------------|--|
| Odor       : Not available.         Odor threshold       : Not available.         pH       : 8.8         Melting point/freezing point       : Not available.         Boiling point, initial boiling       : 100°C (212°F)         point, and boiling range       :         Flash point       : Closed cup: Not applicable.         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Iminit/flammability limit       :         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Iminitian coefficient: n-       : Not soluble         Partition coefficient: n-       : Not soluble         Partition coefficient: n-       : Not available.         Date of issue/Date of revision       : :4/25/2024       Date of previous issue       : :4/10/2024       Version : :16.03       6/12         Batt Wright       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       SHW <th>Physical state</th> <th>: Liqu</th> <th>uid.</th> <th></th> <th></th> | Physical state  | : Liqu                              | uid.                           |             |                      |  |
| Odor threshold       : Not available.         pH       :: 8.8         Melting point/freezing point       : Not available.         Boiling point, initial boiling       : 100°C (212°F)         point, and boiling range       : Closed cup: Not applicable.         Evaporation rate       :: 0.09 (butyl acetate = 1)         Flash point       : Closed cup: Not applicable.         Evaporation rate       :: 0.09 (butyl acetate = 1)         Flammability       :: Not available.         Lower and upper explosion       : Not available.         Limit/flammability limit       Vapor pressure         Vapor pressure       :: 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Imit for a soluble  | Color   | : Whi                               | ite.                           |             |                      |  |
| pH       : 8.8         Melting point/freezing point       : Not available.         Boiling point, initial boiling       : 100°C (212°F)         point, and boiling range       : 100°C (212°F)         Flash point       : Closed cup: Not applicable.         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Limit/flammability limit       : Vapor pressure         Yapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Imition coefficient: n-       : Not applicable.         octanol/water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       : Not available.         Date of issue/Date of revision       :4/25/2024       Date of previous issue       :4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       SHW-85-NA-GHS-CA   | Odor  | : Not                               | available.                     |             |                      |  |
| Melting point/freezing point       : Not available.         Boiling point, initial boiling       : 100°C (212°F)         point, and boiling range       :         Flash point       : Closed cup: Not applicable.         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Iimit/flammability limit       :         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Imition coefficient: n-       : Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W 1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       6/12   | Odor threshold  | : Not                               | available.                     |             |                      |  |
| Boiling point, initial boiling       : 100°C (212°F)         point, and boiling range         Flash point       : Closed cup: Not applicable.         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Imit/flammability limit       : Not available.         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Imition coefficient: n-       : Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       6/12   | рН  | : 8.8                               |                                |             |                      |  |
| point, and boiling range         Flash point       : Closed cup: Not applicable.         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         Lower and upper explosion       : Not available.         Imit/flammability limit       :         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Imition coefficient: n-       : Not applicable.         octanol/water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-35-NA-GHS-CA       6/12   | Melting point/freezing point                            | : Not                               | available.                     |             |                      |  |
| Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         limit/flammability limit       :         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n- octanol/water       : Not available.         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       6/12   | Boiling point, initial boiling point, and boiling range | : 100                               | °C (212°F)                     |             |                      |  |
| Flamability       : Not available.         Lower and upper explosion       : Not available.         limit/flammability limit       : Not available.         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA   | Flash point   | : Clos                              | sed cup: Not applicable.       |             |                      |  |
| Lower and upper explosion       : Not available.         limit/flammability limit  | Evaporation rate  | : 0.09                              | 9 (butyl acetate = 1)          |             |                      |  |
| Ilimit/flammability limit         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       SHW-85-NA-GHS-CA  | Flammability  | mability : Not available.           |                                |             |                      |  |
| Relative vapor density       : 1 [Air = 1]         Relative density       : 1.3         Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       Auto-ignition temperature         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA       SHW-85-NA-GHS-CA  | Lower and upper explosion limit/flammability limit      | : Not                               | available.                     |             |                      |  |
| Relative density       : 1.3         Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       Auto-ignition temperature         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA  | Vapor pressure  | oor pressure : 2.3 kPa (17.5 mm Hg) |                                |             |                      |  |
| Solubility(ies)       :         Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       :         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA   | Relative vapor density                                  | : 1 [A                              | sir = 1]                       |             |                      |  |
| Media       Result         cold water       Not soluble         Partition coefficient: n-       : Not applicable.         octanol/water       Auto-ignition temperature         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA   | Relative density  | : 1.3                               |                                |             |                      |  |
| cold water       Not soluble         Partition coefficient: n-<br>octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA   | Solubility(ies)   | :                                   |                                |             |                      |  |
| Partition coefficient: n-       : Not applicable.         octanol/water  | Media   |                                     | Result                         |             |                      |  |
| octanol/water         Auto-ignition temperature       : Not available.         Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA   | cold water  |                                     | Not soluble                    |             |                      |  |
| Date of issue/Date of revision       : 4/25/2024       Date of previous issue       : 4/10/2024       Version       : 16.03       6/12         B41W1951       PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel       SHW-85-NA-GHS-CA  | Partition coefficient: n-<br>octanol/water              | : Not                               | applicable.                    |             |                      |  |
| B41W1951 PROMAR® 200 HP Zero VOC Interior Acrylic Eg-Shel SHW-85-NA-GHS-CA   | Auto-ignition temperature                               | : Not                               | available.                     |             |                      |  |
| ······································   | Date of issue/Date of revision                          | : 4/2                               | 25/2024 Date of previous issue | : 4/10/2024 | Version : 16.03 6/1. |  |
|  |   |                                     | OC Interior Acrylic Eg-Shel    |             | SHW-85-NA-GHS-CA     |  |

## Section 9. Physical and chemical properties

| Decomposition temperature | : Not available.                                    |
|---------------------------|---|
| Viscosity                 | : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) |
| Molecular weight          | : Not applicable.                                   |
| Heat of combustion        | : 0.363 kJ/g  |

## Section 10. Stability and reactivity

| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.           |
|------------------------------------|--|
| Chemical stability                 | : The product is stable.   |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| Conditions to avoid                | : No specific data.  |
| Incompatible materials             | : No specific data.  |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

## Information on toxicological effects

### Acute toxicity

| Product/ingredient name | Result                   | Species | Dose                       | Exposure |
|-------------------------|--------------------------|---------|----------------------------|----------|
| Heavy Paraffinic Oil    | LD50 Dermal<br>LD50 Oral |         | >5000 mg/kg<br>>5000 mg/kg | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result               | Species | Score | Exposure             | Observation |
|-------------------------|----------------------|---------|-------|----------------------|-------------|
| Titanium Dioxide        | Skin - Mild irritant | Human   | -     | 72 hours 300<br>ug l | -           |

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

### Carcinogenicity

Not available.

### **Classification**

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Titanium Dioxide        | -    | 2B   | -   |

### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

| Date of issue/Date | of revision                              | : 4/25/2024 | Date of previous issue | : 4/10/2024 | Version | :16.03     | 7/12 |
|--------------------|--|-------------|------------------------|-------------|---------|------------|------|
| B41W1951           | PROMAR® 200 HP Z<br>Low Gloss Extra Whit |             | r Acrylic Eg-Shel      |             | SHW-85- | -NA-GHS-CA |      |

## Section 11. Toxicological information

## Specific target organ toxicity (single exposure)

Not available.

## Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

| Name                 | Result                         |
|----------------------|--------------------------------|
| Heavy Paraffinic Oil | ASPIRATION HAZARD - Category 1 |

| Information on the likely routes of exposure | :   | Not available.                                    |
|--|-----|---|
| Potential acute health effe                  | cts |   |
| Eye contact                                  | :   | No known significant effects or critical hazards. |
| Inhalation                                   | 1   | No known significant effects or critical hazards. |
| Skin contact                                 | :   | No known significant effects or critical hazards. |
| Ingestion                                    | :   | No known significant effects or critical hazards. |
|  |     |   |

| Symptoms related to the | physical, chemical and toxicolo | ogical characteristics |
|-------------------------|---------------------------------|------------------------|
|                         |                                 |                        |

| Eye contact  | : No specific data. |
|--------------|---------------------|
| Inhalation   | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion    | : No specific data. |

| Delayed and immediate ef                             | fects and also chronic effects from short and long term exposure                         |
|--|--|
| Short term exposure                                  |  |
| Potential immediate<br>effects                       | : Not available.   |
| Potential delayed effects                            | : Not available.   |
| Long term exposure<br>Potential immediate<br>effects | : Not available.   |
| Potential delayed effects                            | : Not available.   |
| Potential chronic health e                           | ffects   |
| Not available.                                       |  |
| General  | : No known significant effects or critical hazards.                                      |
| Carcinogenicity                                      | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity   | : No known significant effects or critical hazards.                                      |
| Teratogenicity                                       | : No known significant effects or critical hazards.                                      |
| <b>Developmental effects</b>                         | : No known significant effects or critical hazards.                                      |
| Fertility effects                                    | : No known significant effects or critical hazards.                                      |

## Numerical measures of toxicity Acute toxicity estimates Not available.

| Date of issue/Date | of revision                                | : 4/25/2024 | Date of previous issue | : 4/10/2024 |
|--------------------|--|-------------|------------------------|-------------|
| B41W1951           | PROMAR® 200 HP Ze<br>Low Gloss Extra White |             | Acrylic Eg-Shel        |             |

## Section 12. Ecological information

| Toxicity                               |  |  |  |
|--|--|--|--|
| Product/ingredient name                | Result   | Species  | Exposure   |
| Titanium Dioxide                       | Acute LC50 >1000000 µg/l Marine water  | Fish - Fundulus heteroclitus   | 96 hours   |
| Persistence and degradabil             | <u>ity</u>   |  |  |
| Not available.                         |  |  |  |
| Bioaccumulative potential              |  |  |  |
| Not available.                         |  |  |  |
| <u>Mobility in soil</u>                |  |  |  |
| Soil/water partition coefficient (Koc) | : Not available.   |  |  |
| Other adverse effects                  | : No known significant effects or critical   | hazards.   |  |
| Section 13. Dispo                      | sal considerations   |  |  |
| Disposal methods                       | : This product contains a component<br>condition or an existing/proposed S<br>The generation of waste should be avo<br>of this product, solutions and any by-pr<br>requirements of environmental protecti<br>regional local authority requirements. I<br>via a licensed waste disposal contracto<br>the sewer unless fully compliant with th<br>Waste packaging should be recycled.<br>when recycling is not feasible. This may<br>safe way. Care should be taken when<br>cleaned or rinsed out. Empty containe<br>Avoid dispersal of spilled material and | NAC (Significant New Activity).<br>ided or minimized wherever poss<br>oducts should at all times comply<br>on and waste disposal legislation<br>Dispose of surplus and non-recyc<br>or. Waste should not be disposed<br>incineration or landfill should only<br>aterial and its container must be d<br>handling emptied containers that<br>rs or liners may retain some prod | ible. Disposal<br>with the<br>and any<br>lable products<br>of untreated t<br>with jurisdiction<br>be considered<br>isposed of in a<br>have not beer<br>uct residues. |

## Section 14. Transport information

and sewers.

|  | DOT<br>Classification                               | TDG<br>Classification | Mexico<br>Classification | IATA           | IMDG                                  |
|--|---|-----------------------|--------------------------|----------------|---------------------------------------|
| UN number                                | Not regulated.                                      | Not regulated.        | Not regulated.           | Not regulated. | Not regulated.                        |
| UN proper<br>shipping name               | -   | -                     | -                        | -              | -                                     |
| Transport<br>hazard class(es)            | -   | -                     | -                        | -              | -                                     |
| Packing group                            | -   | -                     | -                        | -              | -                                     |
| Date of issue/Date of rev<br>41W1951 PRO | v <b>ision</b> : 4/25/20<br>MAR® 200 HP Zero VOC In |                       | issue : 4/10/2024        |                | <br>ion : 16.03 9/1<br>/-85-NA-GHS-CA |

| Environmental<br>hazards              | No. |  | No.  | No.  | No.  | No.  |
|---------------------------------------|-----|--|--|--|--|--|
| Additional<br>information             | -   |  | -  | -  | -  | -  |
| Special precaution                    |     | conside<br>mode o<br>suitably<br>to shipn<br>of the p<br>dangero | r container sizes. T<br>f transport (sea, ai<br>for that mode of tr<br>nent, and compliar<br>erson offering the<br>bus goods must be | The presence of a s<br>r, etc.), does not ind<br>ansport. All packag<br>ce with the applicat<br>product for transpor | hipping descripti<br>licate that the pro-<br>ing must be revie<br>ble regulations is<br>t. People loading<br>e risks deriving fr | oduct is packaged<br>ewed for suitability prior<br>the sole responsibility |
| Fransport in bulk a o IMO instruments |     | : Not avail  | able.  |  |  |  |
|                                       |     |  |  |  |  |  |

## Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

#### **International regulations**

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

## Section 16. Other information

## Hazardous Material Information System (U.S.A.)



| Date of issue/Date | of revision                                | : 4/25/2024 | Date of previous issue | : 4/10/2024 |  |
|--------------------|--|-------------|------------------------|-------------|--|
| B41W1951           | PROMAR® 200 HP Ze<br>Low Gloss Extra White |             | Acrylic Eg-Shel        |             |  |

## Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

|                                | Justification<br>Calculation method   |  |  |
|--------------------------------|---|--|--|
| CARCINOGENICITY - Cat          |   |  |  |
| History                        |   |  |  |
| Date of printing               | : 4/25/2024   |  |  |
| Date of issue/Date of revision | : 4/25/2024   |  |  |
| Date of previous issue         | : 4/10/2024   |  |  |
| Version                        | : 16.03   |  |  |
| Key to abbreviations           | IATA = International Air Transport Association<br>IBC = Intermediate Bulk Container<br>IMDG = International Maritime Dangerous Goods<br>LogPow = logarithm of the octanol/water partition coe | ition Factor<br>monized System of Classification and Labelling of Chemicals<br>Air Transport Association<br>Bulk Container<br>al Maritime Dangerous Goods<br>of the octanol/water partition coefficient<br>ional Convention for the Prevention of Pollution From Ships, 1973<br>Protocol of 1978. ("Marpol" = marine pollution)<br>Group |  |

✓ Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 4/10/2024

: 4/10/2024