SAFETY DATA SHEET

K37W2751

Section 1. Identification

Product name	: Emerald® Urethane Trim Enamel Satin High Hide White
Product code	: K37W2751
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related material	l.
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: The Sherwin-Williams Company 418 North Service Road East Oakville, Ontario L6H 5R2 Canada
Emergency telephone number of the company Product Information Telephone Number	 : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year : US / Canada: 1-800-474-3794 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

K37W2751 Emerald® L High Hide V	rethane Trim Enamel Satin /hite	SHW-85-NA-GHS-CA
Date of issue/Date of revision	: 4/25/2024 Date of previous issue : 4/19/2024	Version : 7.02 1/12
Storage	: Store locked up.	
Response	: IF exposed or concerned: Get medical advice or attention.	
Prevention	: Obtain special instructions before use. Do not handle until been read and understood. Wear protective gloves, protect protection.	
General	: Read label before use. Keep out of reach of children. If m product container or label at hand.	
Precautionary statement	<u>s</u>	
Hazard statements	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.	
Signal word	: Warning	
Hazard pictograms		
GHS label elements		
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2	

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	22.64	13463-67-7
Amorphous Silica	1.05	7631-86-9
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	0.11	77-99-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary firs	<u>t aid measures</u>
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed Potential acute health effects

I	Date of issue/Date	of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	:7.02	2/12
	K37W2751	Emerald® Urethane Tr High Hide White	rim Enamel Satir	1		SHW-85-	NA-GHS-CA	

Section 4. First aid measures

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of previous issue

: 4/19/2024

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nta	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste

disposal contractor.
 Large spill
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date	of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	: 7.02	4/12
K37W2751	Emerald® Urethane Trin High Hide White	m Enamel Satin	1		SHW-85-	NA-GHS-CA	

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable
Amorphous Silica	7631-86-9	fraction, finescale particles NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS]
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	77-99-6	TWA: 6 mg/m ³ 10 hours. None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering : controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure : controls	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

Date of issue/Date of revision : 4/25/2024 Date of previous issue : 4/19/2024 Version : 7.02 5/12 K37W2751 Emerald® Urethane Trim Enamel Satin High Hide White Emerald® Urethane Trim Enamel Satin SHW-85-NA-GHS-CA SHW-85-NA-GHS-CA

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.	
Color	: White.	
Odor	: Not available.	
Odor threshold	: Not available.	
рН	: 9.2	
Melting point/freezing point	: Not available.	
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)	
Flash point	: Closed cup: Not applicable.	
Evaporation rate	: 0.09 (butyl acetate = 1)	
Flammability	: Not available.	
Lower and upper explosion limit/flammability limit	: Not available.	
Vapor pressure	: 2.3 kPa (17.5 mm Hg)	
Relative vapor density	: 1 [Air = 1]	
Relative density	: 1.29	
Solubility(ies)	:	
Medie	Beault	

Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: Not	applicable.		
Auto-ignition temperature	: Not available.			
Decomposition temperature	: Not	: Not available.		
Viscosity	: Kin	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)		
Molecular weight	: Not applicable.			
Heat of combustion	: 0.69	07 kJ/g		

Date of issue/Date	of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	: 7.02	6/12
K37W2751	Emerald® Urethane T High Hide White	rim Enamel Satir	I		SHW-85-	NA-GHS-CA	L

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
1	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	ug l 24 hours 25 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Amorphous Silica	-	2B 3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date	of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	:7.02	7/12
K37W2751	Emerald® Urethane Tr High Hide White	rim Enamel Sati	n		SHW-85-	NA-GHS-CA	

Section 11. Toxicological information

Not available.

Aspiration hazard

Not available.

Information on the likely	÷	Not available.
routes of exposure	Ĵ	
Potential acute health effect	:ts	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	÷	No known significant effects or critical hazards.
Symptoms related to the pl	hv	sical, chemical and toxicological characteristics
Eye contact		No specific data.
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effe	<u>ec</u>	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ec	its
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	÷	No known significant effects or critical hazards.
Teratogenicity	:	Suspected of damaging the unborn child.
Developmental effects	÷	No known significant effects or critical hazards.
Fertility effects	;	Suspected of damaging fertility.
Numerical measures of fex		

Numerical measures of toxicity Acute toxicity estimates

Date of issue/Date of re-	vision : 4/25/2024	Date of previous issue	: 4/19/2024	Version	: 7.02	8/12
K37W2751 Emerald® Urethane Trim Enamel Satin High Hide White				SHW-85-	-NA-GHS-CA	

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Amorphous Silica	Acute EC50 2.2 g/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	Acute EC50 13000000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
·,- FF	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Ethyl-2-(hydroxymethyl) -1,3-propanediol	-	<1	Low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined.


Date of issue/Date	of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	: 7.02	10/12
K37W2751	Emerald® Urethane Trin High Hide White	m Enamel Satin			SHW-85-	NA-GHS-CA	

Section 15. Regulatory information

Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification	
CARCINOGENICITY - Cat TOXIC TO REPRODUCTI		Calculation method Calculation method	
History			
Date of printing	: 4/25/2024		
Date of issue/Date of revision	: 4/25/2024		
Date of previous issue	: 4/19/2024		
Version	: 7.02		
Version : 7.02 Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations			

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is

Date of i	ssue/Date of revision	: 4/25/2024	Date of previous issue	: 4/19/2024	Version	: 7.02	11/12
K37W27	51 Emerald® Urethane High Hide White	e Trim Enamel Sat	in		SHW-85-	NA-GHS-CA	

Section 16. Other information

responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.