

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Industrial Wash Primer - Green

Product code : P60G2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.

: Industrial use only.

1.3 Details of the supplier of the safety data sheet

Mfg. in U.S.A and exported by:
The Sherwin-Williams Company
101 Prospect Avenue N.W.
Cleveland, OH 44115

EU Only Representative: Valspar B.V.
Zuiveringweg 89
8243 PE Lelystad
P.O. Box 2139
The Netherlands
Phone: +31 (0)320 29 22 00

e-mail address of person responsible for this SDS : sds@sherwin.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +431 406 43 43

Supplier

Telephone number : +1 703-741-5970

Hours of operation : Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Dam. 1, H318

Skin Sens. 1, H317

Carc. 1A, H350

STOT SE 3, H335

STOT SE 3, H336

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

Response

: Collect spillage. IF exposed or concerned: Get medical advice or attention.

Storage

: Not applicable.

Disposal

: Not applicable.

Hazardous ingredients

: 2-Propanol
Methyl Isobutyl Ketone
2-Methyl-1-propanol
Pentazinc Chromate Octahydroxide
Epoxy Polymer
Epoxy Polymer

Supplemental label elements

: FOR INDUSTRIAL USE ONLY

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

Special packaging requirements

Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification


: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixture

:

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
2-Propanol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≥25 - ≤50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2] 
Methyl Isobutyl Ketone	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≥25 - ≤50	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335 EUH066	[1] [2]
2-Methyl-1-propanol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	[1] [2]
Pentazinc Chromate Octahydroxide	EC: 256-418-0 CAS: 49663-84-5 Index: 024-007-00-3	≤10	Acute Tox. 4, H302 Skin Sens. 1, H317 Carc. 1A, H350 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1] [2]
Epoxy Polymer	EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
Xylene, mixed isomers	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤5	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
Epoxy Polymer	CAS: 25036-25-3	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains zinc chromates including zinc potassium chromate, reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), Epoxy Polymer. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, carbon dioxide, powders.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
Keep unnecessary and unprotected personnel from entering.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- : Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
Keep away from heat, sparks and flame. No sparking tools should be used.
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
Put on appropriate personal protective equipment (see Section 8).
Never use pressure to empty. Container is not a pressure vessel.
Always keep in containers made from the same material as the original one.
Comply with the health and safety at work laws.
Do not allow to enter drains or watercourses.

Information on fire and explosion protection

SECTION 7: Handling and storage

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

7.3 Specific end use(s)**Recommendations**

: Not available.

Industrial sector specific solutions

: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
2-Propanol	Regulation on Limit Values - MAC (Austria, 9/2018). TWA: 200 ppm 8 hours. TWA: 500 mg/m ³ 8 hours. PEAK: 800 ppm, 4 times per shift, 15 minutes. PEAK: 2000 mg/m ³ , 4 times per shift, 15 minutes.
Methyl Isobutyl Ketone	Regulation on Limit Values - MAC (Austria, 9/2018). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 83 mg/m ³ 8 hours. PEAK: 50 ppm, 4 times per shift, 15 minutes. PEAK: 208 mg/m ³ , 4 times per shift, 15 minutes.
2-Methyl-1-propanol	Regulation on Limit Values - MAC (Austria, 9/2018). PEAK: 200 ppm, 4 times per shift, 15 minutes. TWA: 150 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. PEAK: 600 mg/m ³ , 4 times per shift, 15 minutes.
Pentazinc Chromate Octahydroxide	Regulation on Limit Values - Technical Guidance Values (Austria, 9/2018). Skin sensitizer. TWA: 0.05 mg/m ³ , (measured as CrO ₃) 8 hours. Form: aerosol,

SECTION 8: Exposure controls/personal protection

Xylene, mixed isomers

inhalable fraction

PEAK: 0.2 mg/m³, (measured as CrO₃), 4 times per shift, 15 minutes. Form: aerosol, inhalable fraction

Regulation on Limit Values - MAC (Austria, 9/2018).

PEAK: 442 mg/m³, 4 times per shift, 15 minutes.

TWA: 50 ppm 8 hours.

PEAK: 100 ppm, 4 times per shift, 15 minutes.

TWA: 221 mg/m³ 8 hours.

Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- : Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-Propanol	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	500 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	319 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	89 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Oral	26 mg/kg bw/day	General population [Consumers]	Systemic
Methyl Isobutyl Ketone	DNEL	Short term Inhalation	208 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	208 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	83 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	83 mg/m ³	Workers	Local
	DNEL	Long term Dermal	11.8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	155.2 mg/m ³	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	155.2 mg/m ³	General population [Consumers]	Local
	DNEL	Long term Inhalation	14.7 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	14.7 mg/m ³	General population [Consumers]	Local
	DNEL	Long term Inhalation	14.7 mg/m ³	General population [Consumers]	Local

SECTION 8: Exposure controls/personal protection

2-Methyl-1-propanol	DNEL	Long term Dermal	4.2 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	4.2 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	310 mg/m³	Workers	Local
	DNEL	Long term Oral	25 mg/kg	General population [Human via the environment]	Systemic
Xylene, mixed isomers	DNEL	Long term Inhalation	55 mg/m³	General population [Human via the environment]	Local
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	108 mg/kg bw/day	General population [Human via the environment]	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	289 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	289 mg/m³	Workers	Local
	DNEL	Long term Inhalation	14.8 mg/m³	General population [Human via the environment]	Systemic
	DNEL	Short term Inhalation	174 mg/m³	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	174 mg/m³	General population [Consumers]	Local
	DNEL	Short term Inhalation	174 mg/m³	General population [Consumers]	Local

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2-Propanol	Fresh water	140.9 mg/l	-
	Marine water	140.9 mg/l	-
	Sewage Treatment Plant	2251 mg/l	-
	Sediment	552 mg/kg dwt	-
	Soil	28 mg/kg	-
	Secondary Poisoning	160 mg/kg	-
Methyl Isobutyl Ketone	Fresh water	0.6 mg/l	-
	Marine water	0.06 mg/l	-
	Sewage Treatment Plant	27.5 mg/l	-
	Fresh water sediment	8.27 mg/kg dwt	-
	Marine water sediment	0.83 mg/kg dwt	-
	Soil	1.3 mg/kg dwt	-
2-Methyl-1-propanol	Marine water sediment	0.152 mg/kg	-
	Soil	0.0699 mg/kg	-
	Fresh water	0.4 mg/l	-
	Marine water	0.04 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	1.52 mg/kg	-
	Fresh water sediment	1.52 mg/kg	-

SECTION 8: Exposure controls/personal protection

Xylene, mixed isomers	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Fresh water sediment	12.46 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Soil	2.31 mg/kg	-
	Marine water sediment	12.46 mg/l	-

8.2 Exposure controls

- Appropriate engineering controls**
- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
 - : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures

- Hygiene measures**
- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection**
- : Use safety eyewear designed to protect against splash of liquids.

Skin protection**Hand protection****Gloves**

- : Wear suitable gloves tested to EN374.
- : Gloves for short term exposure/splash protection (less than 10 min.): Nitrile>0.12 mm
Gloves for splash protection need to be changed immediately when in contact with chemicals.
Gloves for repeated or prolonged exposure (breakthrough time > 240 min.)
When the hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcohol (PVA) gloves 0.2-0.3 mm
Otherwise use: Butyl gloves >0.3 mm
For long term exposure or spills (breakthrough time >480 min.): Use PE laminated gloves as under gloves
Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.
The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG)
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The breakthrough time must be greater than the end use time of the product.
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Always ensure that gloves are free from defects and that they are stored and used correctly.
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

SECTION 8: Exposure controls/personal protection

- Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Application methods:
Brush or roller. Approved/certified respirator with organic vapor cartridge. Filter type: A2 P2 (EN14387).
Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Solvent.
- Odor threshold** : Not Available (Not Tested).
- pH** : Not relevant/applicable due to nature of the product.
- Melting point/freezing point** : Not relevant/applicable due to nature of the product.
- Initial boiling point and boiling range** : 81°C
- Flash point** : Closed cup: 45°C [Pensky-Martens Closed Cup]
- Evaporation rate** : 1.62 (butyl acetate = 1)
- Flammability (solid, gas)** : Not relevant/applicable due to nature of the product.
- Upper/lower flammability or explosive limits** : LEL: 1% (Xylene, mixed isomers)
UEL: 12.7% (2-Propanol)
- Vapor pressure** : 4.4 kPa [at 20°C]
- Vapor density** : 2.07 [Air = 1]
- Relative density** : 0.89
- Solubility(ies)** : Not relevant/applicable due to nature of the product.
- Partition coefficient: n-octanol/water** : Not relevant/applicable due to nature of the product.
- Auto-ignition temperature** : Not relevant/applicable due to nature of the product.
- Decomposition temperature** : Not relevant/applicable due to nature of the product.
- Viscosity** : Kinematic (40°C): >0.205 cm²/s
- Explosive properties** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Oxidizing properties** : Under normal conditions of storage and use, hazardous reactions will not occur.

SECTION 9: Physical and chemical properties**SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains zinc chromates including zinc potassium chromate, reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), Epoxy Polymer. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Propanol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Methyl Isobutyl Ketone	LD50 Oral	Rat	2080 mg/kg	-
2-Methyl-1-propanol	LC50 Inhalation Vapor	Rat	19200 mg/m ³	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	2460 mg/kg	-
Xylene, mixed isomers	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-

Acute toxicity estimates

SECTION 11: Toxicological information

Route	ATE value
Oral Dermal Inhalation (gases) Inhalation (vapors)	6692.73 mg/kg 30839.43 mg/kg 187840.17 ppm 35.94 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Propanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
Methyl Isobutyl Ketone	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 UI	-
	Eyes - Severe irritant	Rabbit	-	40 mg	-
Epoxy Polymer	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 UI	-
Xylene, mixed isomers	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-

Conclusion/Summary : Not available.

Sensitization

No data available

Conclusion/Summary : Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-Propanol	Category 3	-	Narcotic effects
Methyl Isobutyl Ketone	Category 3	-	Respiratory tract irritation
2-Methyl-1-propanol	Category 3	-	Respiratory tract irritation
Xylene, mixed isomers	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation

SECTION 11: Toxicological information

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Xylene, mixed isomers	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
2-Propanol	Acute EC50 7550 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Methyl Isobutyl Ketone	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
	Acute LC50 505000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 78 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 168 mg/l Fresh water	Fish - Pimephales promelas - Embryo	33 days
2-Methyl-1-propanol	Acute LC50 600 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 1030000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Xylene, mixed isomers	Acute LC50 1330000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 4000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-Propanol	-	-	Readily
Methyl Isobutyl Ketone	-	-	Readily
2-Methyl-1-propanol	-	-	Readily
Xylene, mixed isomers	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Pentazinc Chromate Octahydroxide	-	60960	high
Epoxy Polymer	-	31	low
Xylene, mixed isomers	-	8.1 to 25.9	low

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.
: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC) : waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging






Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) : packaging containing residues of or contaminated by hazardous substances 15 01 10*

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL. Marine pollutant (Pentazinc Chromate Octahydroxide, Epoxy Polymer)	PAINT RELATED MATERIAL
14.3 Transport Hazard Class(es)/ Label(s)	3  	3  	3 
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel code D/E	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.


SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture


EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
Pentazinc Chromate Octahydroxide	Carcinogen	Listed	31	8/22/2014 

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
Pentazinc Chromate Octahydroxide	Carcinogen	Recommended	ED/77/2011	8/22/2014 

SECTION 15: Regulatory information

Annex XVII - Restrictions : Restricted to professional users.
*on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles*

Other EU regulations

VOC content (2010/75/EU) : 75.2 w/w
670 g/l

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative
N/A = Not available

Key literature references and sources for data : Regulation (EC) No. 1272/2008 [CLP]
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830
Directive 2012/18/EU, and relative amendments & additions
Directive 2008/98/EC, and relative amendments & additions
Directive 2009/161/EU, and relative amendments & additions
CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 1A, H350	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

SECTION 16: Other information

Full text of abbreviated H statements	: H225	Highly flammable liquid and vapor.
	H226	Flammable liquid and vapor.
	H302	Harmful if swallowed.
	H304	May be fatal if swallowed and enters airways.
	H312	Harmful in contact with skin.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H332	Harmful if inhaled.
	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H350	May cause cancer.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	EUH066	Repeated exposure may cause skin dryness or cracking.
Full text of classifications [CLP/GHS]	: Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
	Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
	Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Carc. 1A	CARCINOGENICITY - Category 1A
	Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	Skin Sens. 1	SKIN SENSITIZATION - Category 1
	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Date of printing	: 09, Oct, 2020.	
Date of issue/ Date of revision	: 09, Oct, 2020	
Date of previous issue	: 13, May, 2020	
	: If there is no previous validation date please contact your supplier for more information.	
Version	: 11	

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Industrial Wash Primer - Green

P60G2

SECTION 16: Other information

handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.