



SHERWIN-WILLIAMS

AEROSPACE COATINGS

PRODUCT DATA

Pre-Prep Cleaning Solvent

CM0120540

ADVANTAGES

- Cleaning solvent for bare aluminum or previously painted aged surfaces.
- Easy wipe on-wipe off application.
- Leaves NO residual solvent on the surface.
- May be spray applied by hand or by pressure sprayer.

DESCRIPTION

CM0120540 is a pre-cleaning solvent used to remove wax and grease type contaminants on bare aluminum or on previously painted aged urethane/epoxy surfaces. It is an excellent solvent to clean and repair panel areas before sanding for re-paint.

COATING PROPERTIES

Wt./Gal.	7.15 lbs.
Sp. Gravity	0.86
VOC:	7.15 lbs./gal (856 g/L)

SHELF LIFE

Shelf Life is applicable only for materials stored in unopened and undamaged original factory filled containers.

Minimum Storage Temp. 40°F / 4°C
Maximum Storage Temp. 90°F / 32°C

CM0120540: 7 years

APPLICATION

Wipe the area with CM0120540 using clean cotton cloths. Follow the wiping process with a clean cotton cloth as you clean, before the solvent has flashed off.

Use a new clean cloth, when the solvent rag is discolored with contaminants. This will help assure that all the surface contaminants have been removed.

Proper cleaning before sanding a previously painted panel, will prevent possible fish-eye conditions in the applied urethane paint coating.

The area should now be ready to sand for full panel re-painting, or prepped for a spot-in procedure.

PRODUCT INFORMATION

Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.