



Basecoat Surface Cleaner

CM0110158

ADVANTAGES

- Designed to not soften or attack coatings.
- Easy wipe on-wipe off Application.
- Leaves NO residual solvent on The surface.
- May be spray applied by hand or by pressure sprayer.
- Removes wax, oil, grease and silicone.
- Does not swell or soak into the surface. Does not burn.
- Removes sanding residue before applying the next paint layer
- Removes masking tape gum residue.

DESCRIPTION

CM0110158 Basecoat Surface Cleaner is a low odor fast-evaporating solvent wipe developed to remove light contamination.

This solvent is ideal to use as part of the in paint cycle cleaning process, where significant hand finishing and/or back masking has occurred multiple times.

CM0110158 Basecoat Surface Cleaner is particularly beneficial on solid or effect basecoat systems, its mild formula will not damage the freshly painted surface.

Ideal for all Sherwin Williams Aerospace coatings, but particularly useful when used with 850 and 855 Series SKYscapes Basecoat systems.

COATING PROPERTIES

Wt./Gal.	6.21
Sp. Gravity	0.75
VOC:	
Total	6.21 lbs./gal (744 g/L)
Non-exempt solvent	6.21 lbs./gal (744 g/L)
Volatile HAPS	0.00 lb/gal 0.000 kg/l
Mixing Ratio	Use at package consistency
Flash point	44°F TCC
Freeze Hazard	No

SHELF LIFE

Shelf Life is applicable only for materials stored in unopened and undamaged original factory filled containers.

Minimum Storage Temp. 40°F / 4°C
Maximum Storage Temp. 90°F / 32°C

CM0110158: 7 years

APPLICATION

1. Saturate a clean cloth with CM0110158 Basecoat Surface Cleaner.
2. Apply to areas to be painted and adjacent panels. Wipe surface thoroughly with CM0110158 Basecoat Surface Cleaner and apply only to one panel at a time.
3. Wipe off with a second clean, dry cloth before CM0110158 Basecoat Surface Cleaner is allowed to dry. If drying occurs, repeat application.
4. Allow 5 minutes flash time for complete surface drying/evaporation before painting.
5. Should be used before sanding and can also be used after sanding prior to apply another scheme color or clear coating.

PRODUCT INFORMATION

Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.