

**PRODUCT INFORMATION**

**UNIFLEX™ MS Hybrid Roof Bonding Tape-Fleece Backed** has an advanced S-Polymer technology that prevents plasticizer migration often associated with other tapes when they have prolonged contact with TPO, PVC, EPDM, asphalt, and other common roof substrates. UNIFLEX Bonding Tape is used for repairing roofs prior to coating applications to seal holes, tears, and seams in gutters, flashings, skylights, roofing membranes and more.

**RECOMMENDED USES**

Adheres to TPO, PVC, EPDM, metal, asphalt, vinyl and more.

**PRODUCT CHARACTERISTICS**

Vehicle Base.....S-polymer synthetic technology

**PACKAGING**

SMIS#	SIZE/QTY PER CASE
6504-33378	4" x 50' roll / 6
6504-33386	6" x 50' roll / 4

**PERFORMANCE CHARACTERISTICS**

Adhesion.....9.8 pli c.f. ASTM D330  
 Elongation.....>500% (adhesive)  
 Low Temp Flexibility.....1/2"radius @ -35°F  
 Self Sealability.....Passes ASTM D 1970

**SAFETY PRECAUTION**

Refer to the MSDS sheet before use

**Published technical data and instructions are subject to change without notice. Contact your UNIFLEX representative for additional technical data and instructions.**

**SURFACE PREPARATION**

Refer to System Specifications for UNIFLEX® detailed surface preparation requirements by roof type.

**For best results, ensure surfaces are clean, dry, sound and frost-free. Note: On PVC membranes, rough surface with sand paper and brush away dust before applying tape.**

**APPLICATION CONDITIONS**

Application Temperature.....-20°F to 150°F  
 Service Temperature.....-70°F to 150°F

**INSTALLATION**

Remove release liner. Apply tape to surface using pressure. UNIFLEX MS Hybrid Roof Bonding Tape's adhesive characteristics are activated by the amount of pressure applied during application and the length of time allowed to adhere to the substrate before trying to remove. Length of time for full adhesion is dependent on substrate and application temperatures. Rool out any air bubbles using a weighted roofer's roller. For difficult bubbles, cut the bubbles with a razor and roll over the bubble with the roller. UNIFLEX MS Hybrid Roof Bonding Tape will reseal itself.

**DISCLAIMER**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of UNIFLEX™ Fluid Applied Roofing Systems — A Business Unit of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your UNIFLEX® representative to obtain the most recent Product Data Information and Application Bulletin.

**WARRANTY**

This product is manufactured of good materials and by competent workmen. Seller and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product for his/her intended use; and user assumes all risk and liability.