

PRODUCT DESCRIPTION

Uniflex® Seam Tape is a self-adhering, modified butyl rubber waterproofing tape. A strong polyester fabric facing has been added for additional strength. It maintains the flexibility necessary to respond to the dynamics of roof movement and it easily conforms to irregular roof configurations.

GENERAL USES

For sealing seams, flashings and penetrations on metal, smooth BUR, modified bitumen, EPDM and CPSE Hypalon single-ply roofs.

PACKAGING INFORMATION

SKU	SIZE
KST020802-99	2" x 50' per roll
KST020804-99	4" x 50' per roll
KST020806-99	6" x 50' per roll
KST020808-99	8" x 50' per roll

COVERAGE RATES

Approximately 1 roll of Uniflex Seam Tape seals 50 lineal feet. Over corrugated and irregular metal surfaces, allow for additional surface area by multiplying total lineal feet by 1.15-1.25 depending upon corrugation size.

WARRANTY

This product is manufactured of good materials and by competent workmen. Seller and manufacturer's only obligation shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential arising from the use or the inability to use the product for his/her intended use, and user assumes all risk and liability. Color fade is not covered under warranty.

PRODUCT CHARACTERISTICS

Color	Gray
Vehicle	Butyl rubber
Adhesive	20 mil butyl rubber
Service Temperature	-10° F to 180° F
Bond Time	Immediate aggressive adhesion Full bonding 24 hours
Low Temperature Flexibility	Passes, no cracking
Shelf Life	18 to 24 months
VOC / VOS	0 g/L free of solvents & asphalt
Tensile Strength	475 psi @ 60% elongation
Peel Strength	10 lbs per linear inch

APPLICATION CONDITIONS

Apply at temperatures between 40° F and 100° F. Caution: Sides of rolls will quickly adhere to any surface it comes in contact with. Keep rolls in original packaging until ready to use.

Refer to system specifications for information on use with various approved roof types.

With all systems, it is recommended that seam tape be coated over with Uniflex Elastomeric the same day as installation. Coating over the tape should extend 1-2" beyond tape edges.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings- A Business Unit of the Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Uniflex representative to obtain the most recent Product Data Information.

If further information is needed, contact Uniflex Technical Service at
1-888-321-3539