



PITCH PAN ROOFING SEALANT 58-360 BLACK

PRODUCT DESCRIPTION

Uniflex® Pitch Pan Roofing Sealant is a single component, semi self-leveling sealant that provides a water-resistant flexible seal. It can be applied in damp wet conditions, with no mixing required.

GENERAL USES

Metal, asphalt, EPDM, primed TPO, primed PVC, concrete, and other roofing materials.

PACKAGING INFORMATION

SKU	SIZE
KST058360-LT	67 oz pouch

APPLICATION CONDITIONS

KEEP FROM FREEZING. Refer to product application bulletin for detailed application information.

Can be used in damp or dry conditions, but not standing water conditions.

APPLICATION PROCEDURES

To apply, remove cap from pouch and pour into place. To re seal pouch, squeeze out excess air and replace cap. Surface Prep: Wire brush area, remove all previously applied caulk, asphalt, pitch, cement and other contaminants surrounding the penetration.

WARRANTY

This product is manufactured in accordance to ISO 9001-2008 standards. Seller and manufacturer's only obligation shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential arising from the use or the inability to use the product for his/her intended use, and user assumes all risk and liability. Color fade is not covered under warranty.

PRODUCT CHARACTERISTICS

Color	Black
Vehicle Base	Hybrid
Dry Time	
Tack Free	40 minutes at 75° F / 50% RH
Cure Time	1/8" to 1/4" per week
	<i>Drying Time is temperature, humidity and film thickness dependent</i>
VOC	4 g/L
Shelf life	12 months
Grade	Semi, Self-Level

PERFORMANCE CHARACTERISTICS

Elongation at Break (%)	217.49%
Tensile at Peak	110.97
Type "A" Hardness	34

CLEAN UP

Remove Uniflex Pitch Pan Roofing Sealant from tools before it cures. This may be done by scraping and use of solvents such as lacquer thinner, toluene, xylene or chlorinated solvents.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings- A Business Unit of the Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of the publication. Consult your Uniflex Technical Representative to obtain the most recent Product Data Information.

Warning: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. Do not take internally. Keep out of reach of children.

If further information is needed, contact Uniflex Technical Service at
1-888-321-3539