

**WHITE
LIGHTNING®**



PRISTINE™

Premium Acrylic Sealant

White Lightning® Pristine™ is a premium acrylic sealant with a stay-clean formula that resists dirt and stains. It has excellent mold and mildew resistance upon curing. White Lightning Pristine prevents flashing when painted after one hour. For use on: wood, metal, concrete, brick, plaster, glass, masonry, drywall, ceramic tile and most exterior substrates.


- Stay-Clean Formula
- Resists dirt and stains
- Excellent mold and mildew resistance
- Prevents flashing when painted
- Paintable in 1 hour




WATERPROOF



PAINTABLE



INTERIOR/
EXTERIOR



| PART # | UPC | COLOR | SIZE |
|------------|----------------|-------|------------|
| W310000010 | 0-23275-004214 | White | 10 fl. oz. |



APPLY desired amount with gun, spatula or brush. Allow to cure for 24 hours before painting. LIMITED WARRANTY: This product is warranted to be free of defects in material and workmanship for a period of one year from the date of purchase. If a defect is found, the user may return the product to the place of purchase for a full refund. See the back of the box for complete details. © 2020 White Lightning Products, Inc. All rights reserved. Made in the USA. Formulation and design are trademarks of White Lightning Products, Inc.



PRISTINE™

Premium Acrylic Sealant

Physical Properties:

Type: Acrylic

Color: White

Shelf Life: 24 months

Flash Point: n/a (water-based)

Flammability: n/a (water-based)

Full Cure Time: 5-7 days at 75 °F

Tack-Free Time: 25 minutes at 75 °F

Application Temperature: Above 40 °F

Service Temperature: -30 °F to 140 °F

Vehicle: Water

Solids by Weight: 75.9% +/-0.2%

Weight/Gallon: 12.0 +/- 0.7

Paintable: Yes

Primers: Not Required

Mildew Resistance: Excellent

Water Resistant: Good

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze/Thaw Stability: Passes through 5 Cycles

Cleanup: Water; promptly clean tools and excess sealant with water or damp cloth

Flexibility: Excellent; 50% Total Joint Movement

Linear Coverage: 10 oz. cartridge 24 ft. at 1/4" wide by 1/4" deep bead

Painting: A minimum of 1 hour dry time is required before painting with latex or oil-based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

ASTM:

Meets performance requirements of ASTM C-920, Class 25.

White Lightning® Pristine™ has achieved GREENGUARD Gold Certification.

Application:

1. Remove all existing caulk.
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach) and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

10 oz. Cartridge

- Cut cartridge tip at a 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Cleanup:

Water; promptly clean tools and excess sealant with water or a damp cloth.

Cautions:

See SDS.

Limitations:

For best results, apply at temperatures above 40 °F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost-covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

This warranty is made to you, the property owner purchaser, and is only transferable by a contractor, if the contractor purchased and applied the product to the property for you. If the product fails to perform in accordance with applicable product literature for as long as you own the property, White Lightning shall, either replace an equivalent quantity of product free of charge or refund the original purchase price upon presentation of proof of purchase. For a replacement or a refund please visit the store where the product was purchased or contact customer service at 1-800-241-5295. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy, and White Lightning's sole liability under this warranty is the replacement of product or refund by White Lightning and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL WHITE LIGHTNING BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED TO A ONE-YEAR PERIOD FROM THE DATE OF PURCHASE.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. wlcaulk.com

For more information, please call or write:

White Lightning Products 101 W Prospect Ave., Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
wlcaulk.com